

Package ‘wrMisc’

June 8, 2026

Version 2.1.0

Title Analyze Experimental High-Throughput (Omics) Data

Author Wolfgang Raffelsberger [aut, cre]

Maintainer Wolfgang Raffelsberger <w.raffelsberger@gmail.com>

Description The efficient treatment and convenient analysis of experimental high-throughput (omics) data gets facilitated through this collection of diverse functions. Several functions address advanced object-conversions, like manipulating lists of lists or lists of arrays, reorganizing lists to arrays or into separate vectors, merging of multiple entries, etc. Another set of functions provides speed-optimized calculation of standard deviation (sd), coefficient of variance (CV) or standard error of the mean (SEM) for data in matrixes or means per line with respect to additional grouping (eg n groups of replicates). A group of functions facilitate dealing with non-redundant information, by indexing unique, adding counters to redundant or eliminating lines with respect redundancy in a given reference-column, etc. Help is provided to identify very closely matching numeric values to generate (partial) distance matrixes for very big data in a memory efficient manner or to reduce the complexity of large data-sets by combining very close values. Other functions help aligning a matrix or data.frame to a reference using partial matching or to mine an experimental setup to extract patterns of replicate samples. Many times large experimental datasets need some additional filtering, adequate functions are provided. Convenient data normalization is supported in various different modes, parameter estimation via permutations or boot-strap as well as flexible testing of multiple pair-wise combinations using the framework of 'limma' is provided, too. Batch reading (or writing) of sets of files and combining data to arrays is supported, too.

VignetteBuilder knitr

Depends R (>= 3.1.0)

Imports grDevices, graphics, MASS, stats, utils

Suggests BBmisc, boot, coin, data.table, data.tree, fdrtool, flexclust, knitr, limma, markdown, mixdist, NbClust, preprocessCore, qvalue, Rcpp, RColorBrewer, readxl, rmarkdown, som, stringi, VGAM, vsn, wrGraph

License GPL-3

Encoding UTF-8

Config/roxygen2/version 8.0.0

NeedsCompilation no

Repository CRAN

Date/Publication 2026-06-08 19:10:02 UTC

Contents

.addLetterWoLast	8
.allRatioMatr1to2	8
.allRatios	9
.arrLstMean	10
.arrLstSEM	11
.asDF2	12
.breakInSer	12
.bringToCtr	13
.checkArgNa	14
.checkConsistentArrList	14
.checkConvt2Vect	15
.checkFactor	16
.checkFileNameExtensions	17
.checkLegendLoc	17
.checkLmConfInt	18
.checkRegrArguments	19
.chooseGrpCol	19
.combineListAnnot	20
.compareByDiff	21
.compareByLogRatio	22
.compareByPPM	23
.complCols	23
.composeCallName	24
.convertMatrToNum	25
.convertNa	25
.corDuplItemsByIncrem	26
.cutAtSearch	27
.cutStr	28
.datSlope	28
.doubleExt	29
.extrNAneighb	30
.extrNumHeadingCap	31
.extrNumHeadingSepChar	31
.filterNetw	32
.filterSw	33
.filtSize	34
.findBorderOverlaps	34

.firstMin	35
.fuse2ArrBy2ndDim	36
.getAmean	36
.getAmean2	37
.getMvalue2	38
.getPWseparator	38
.growTree	40
.insp1dimByClustering	40
.inspectHeader	41
.keepCenterId	42
.keepFiniteCol	43
.maybeNum	44
.medianSpecGrp	45
.mergeMatrices	46
.minDif	47
.neighbDis	47
.normalize	48
.normConstSlope	49
.pasteCols	50
.plotCountPie	51
.plusLowerCaps	52
.predRes	52
.raiseColLowest	53
.removeCol	54
.removeEmptyCol	55
.replSpecChar	56
.retain1stPart	56
.rowGrpCV	57
.rowGrpMeans	58
.rowGrpSds	58
.rowGrpSums	59
.rowNorm	60
.rowNormFact	61
.scale01	62
.scaleSpecGrp	63
.scaleXY	64
.seqCutStr	64
.setLowestTo	65
.sortMid	66
.stackArray	66
.summarizeCols	67
.trimFromEnd	68
.trimFromStart	69
.trimLeft	70
.trimRight	71
.uniqueWName	71
.vector2Matr	72
addBeforeFileExtension	73

addBeforFileExtension	74
adjBy2ptReg	75
adjustUnitPrefix	76
appendNR	77
arrayCV	78
asSepList	79
blockNormalize	80
buildTree	83
cbindNR	84
checkAvSd	85
checkFilePath	86
checkGrpOrder	88
checkGrpOrderSEM	89
checkSimValueInSer	90
checkStrictOrder	91
checkUnitPrefix	92
checkVectLength	94
chooseGroupNames	95
cleanReplicates	96
closeMatchMatrix	97
coinPermTest	99
colCVs	100
colMedSds	101
colorAccording2	101
colSds	103
combinatIntTable	103
combineAsN	104
combineByEitherFactor	106
combineOverlapInfo	107
combineRedBasedOnCol	109
combineRedundLinesInList	110
combineRedundLinesInListAcRef	111
combineReplFromListToMatr	112
combineSingleT	113
completeArrLst	114
concatMatch	115
confInt	116
contribToContigPerFrag	117
conv01toColNa	118
convColorToTransp	119
convMatr2df	120
convPairwiseSetup	121
convToNum	122
coordOfFilt	124
correctToUnique	125
correctWinPath	126
countCloseToLimits	127
countSameStartEnd	128

cutArrayInCluLike	129
cutAtMultSites	130
cutToNgrp	130
diffCombin	131
diffPPM	132
elimCloseCoord	133
equLenNumber	134
exclExtrValues	135
exponNormalize	136
extr1chan	138
extractLast2numericParts	139
extrColsDeX	140
extrNumericFromMatr	141
extrSpcText	142
filt3dimArr	143
filterLiColDeList	144
filterList	145
filterNetw	146
filtSizeUniq	148
findCloseMatch	149
findHeadAndTail	151
findRepeated	152
findSimilFrom2sets	153
findUsableGroupRange	154
firstLineOfDat	155
firstOfRepeated	156
firstOfRepLines	157
fuseAnnotMatr	158
fuseCommonListElem	159
fusePairs	160
get1stOfRepeatedByCol	161
getPairwiseSetup	162
getPWseparator	164
getValuesByUnique	165
gitDataUrl	166
htmlSpecCharConv	167
indexGroupsFromPW	168
keepCommonText	169
levIndex	171
linModelSelect	172
linRegrParamAndPVal	174
listBatchReplace	175
listGroupsByNames	176
lmSelClu	177
lrbind	179
makeMAList	180
makeNRedMatr	181
matchMatrixLinesToRef	182

matchNamesWithReverseParts	184
matchSampToPairw	185
matr2list	186
mergeMatrices	187
mergeMatrixList	188
mergeSelCol	190
mergeSelCol3	191
mergeVectors	192
mergeW2	194
minDiff	195
moderTest2grp	196
moderTestXgrp	198
multiCharReplace	201
multiMatch	202
naOmit	203
nFragments	204
nFragments0	205
nNonNumChar	206
nonAmbiguousMat	207
nonAmbiguousNum	208
nonredDataFrame	209
nonRedundLines	210
normalizeThis	210
numPairDeColNames	213
orderMatrToRef	214
organizeAsListOfRepl	216
packageDownloadStat	217
pairsAsPropensMatr	218
partialDist	219
partUnlist	220
pasteC	221
presenceFilt	222
presenceGrpFilt	223
protectSpecChar	225
pVal2lfd	226
pwSeparatorList	227
randIndFx	228
rankToContigTab	229
ratioAllComb	230
ratioToPpm	231
readCsvBatch	232
readTabulatedBatch	233
readVarColumns	235
readXlsxBatch	236
reduceTable	238
regrBy1or2point	239
regrMultBy1or2point	240
renameColumns	241

reorgByCluNo	242
replacePWseparator	243
replicateStructure	244
replNAbyLow	246
replPlateCV	247
rmDupl2colMatr	248
rmEnumeratorName	249
rmOrphans	251
rmSharedWords	252
rnormW	253
rowCVs	255
rowGrpCV	256
rowGrpMeans	256
rowGrpNA	257
rowGrpSds	259
rowGrpSums	260
rowMedSds	261
rowNormalize	261
rowSds	263
rowSEMs	264
sampNoDeMArrayLM	265
scaleXY	266
searchDataPairs	268
searchLinesAtGivenSlope	269
simpleFragFig	271
singleLineAnova	272
sortBy2CategorAnd1IntCol	273
sortByNRepeated	274
stableMode	275
standardW	276
stdErrMedBoot	277
summarizeCols	278
sumNAperGroup	280
sysDate	281
tableToPlot	282
test2factLimma	283
top3mean	285
transpGraySca	286
treatTxtDuplicates	286
triCoord	287
trimmedMean	288
trimRedundText	289
tTestAllVal	290
unifyEnumerator	291
uniqCountReport	293
upperMaCoord	294
vectorDistAngle	295
volcanoFilter	296

withinRefRange	299
writeCsv	300
XYToDiffPpm	302

Index	303
--------------	------------

`.addLetterWoLast` *Add letter to all elements but not last*

Description

This function allows to add 'addChr' to all entries, without the last entry

Usage

```
.addLetterWoLast(x, addChr)
```

Arguments

x	(character) main input
addChr	(character)

Value

This function returns a modified character vector

See Also

[paste](#); used in [cutAtMultSites](#)

Examples

```
.addLetterWoLast(c("abc", "efgh"), "Z")
```

`.allRatioMatr1to2` *Calculate ratios for each column to each column of reference-matrix*

Description

This function calculates ratio(s) for each column of matrix 'x' versus all/each column(s) of matrix 'y' (reference)

Usage

```
.allRatioMatr1to2(x, y, asLog2 = TRUE, sumMeth = "mean", callFrom = NULL)
```

Arguments

- x (matrix or data.frame) main input1
- y (matrix or data.frame) main input2
- asLog2 (logical)
- sumMeth (character) method
- callFrom (character) allow easier tracking of messages produced

Value

This function returns a numeric vector or matrix in dimension of 'x' (so far summarize all ratios from mult division from mult ref cols as mean or median)

See Also

[makeMAList](#), [grep](#)

Examples

```
.allRatioMatr1to2(matrix(11:14, ncol=2), matrix(21:24, ncol=2))
```

.allRatios	<i>Search character-string and cut either before or after</i>
------------	---

Description

This function extracts/cuts text-fragments out of txt following specific anchors defined by arguments cutFrom and cutTo.

Usage

```
.allRatios(dat, ty = "log2", colNaSep = "_")
```

Arguments

- dat (matrix or data.frame) main input
- ty (character) type of ratio (eg 'log2')
- colNaSep (character) separator

Value

This function returns a numeric vector

See Also

[makeMAList](#), [grep](#)

Examples

```
.allRatios(matrix(11:14, ncol=2))
```

```
.arrLstMean
```

Summarize along columns of multiple arrays in list

Description

This function allows summarizing along columns of multiple arrays in list

Usage

```
.arrLstMean(  
  arrLst,  
  sumType = "mean",  
  arrOutp = FALSE,  
  signifDig = 3,  
  formatCheck = FALSE,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

arrLst	(list) main input
sumType	(character)
arrOutp	(logical)
signifDig	(integer)
formatCheck	(logical)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

array (1st dim will be summary along cols, rows will be layers of 3rd array-dim)

See Also

used in [cutArrayInCluLike](#)

Examples

```
.datSlope(c(3:6))
```

.arrLstSEM *Summarize along columns of mult arrays in list*

Description

This function allows summarizing along columns of mult arrays in list

Usage

```
.arrLstSEM(  
  arrLst,  
  arrOutp = FALSE,  
  signifDig = 3,  
  formatCheck = FALSE,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

arrLst	(list) main input
arrOutp	(logical)
signifDig	(integer)
formatCheck	(logical)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

array (1st dim will be summary along cols, rows will be layers of 3rd array-dim ie dim(arrLst[[1]])[3])

See Also

used in [cutArrayInCluLike](#)

Examples

```
.datSlope(c(3:6))
```

<code>.asDF2</code>	<i>Convert anything to data.frame</i>
---------------------	---------------------------------------

Description

This function allows converting anything to data.frame

Usage

```
.asDF2(z)
```

Arguments

`z` (numeric vector, factor, matrix or list) main input

Value

data.frame

See Also

[as.data.frame](#)

Examples

```
.asDF2(c(3:6))
```

<code>.breakInSer</code>	<i>Get series of values after last discontinuity</i>
--------------------------	--

Description

This function aims to get series of values after last discontinuity

Usage

```
.breakInSer(x, getFrom = "last")
```

Arguments

`x` (numeric) main input
`getFrom` (character)

Value

This function returns a numeric vector of reduced length

See Also

[dist](#)

Examples

```
.breakInSer(c(11:14, 16:18))
```

<code>.bringToCtr</code>	<i>Bring most extreme to center</i>
--------------------------	-------------------------------------

Description

This function aims to bring most extreme value to center

Usage

```
.bringToCtr(aa, ctr, ctrFa = 0.75)
```

Arguments

<code>aa</code>	(numeric) main input
<code>ctr</code>	(numeric) 'control'
<code>ctrFa</code>	(numeric <1) modulate amplitude of effect

Value

This function returns an adjusted numeric vector

See Also

[dist](#)

Examples

```
.bringToCtr(11:14, 9)
```

`.checkArgNa` *Check argument names*

Description

This function allows checking of argument names

Usage

```
.checkArgNa(x, argNa, lazyEval = TRUE)
```

Arguments

<code>x</code>	(character) main input
<code>argNa</code>	(character) argument name
<code>lazyEval</code>	(logical) decide if argument should be evaluated with abbreviated names, too

Value

This function returns a elongated character vector

See Also

[chartr](#)

Examples

```
.checkArgNa("Abc", c("ab", "Ab", "BCD"))
```

`.checkConsistentArrList`
Check list of arrays for consistent dimensions of all arrays

Description

This function allows to check list of arrays for consistent dimensions of all arrays

Usage

```
.checkConsistentArrList(  
  arrLst,  
  arrNDim = 3,  
  fxName = NULL,  
  varName = NULL,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

<code>arrLst</code>	(list) main input
<code>arrNDim</code>	(integer) number of dimensions for arrays
<code>fxName</code>	(character) this name will be given in message
<code>varName</code>	(character)
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

list

See Also

used in [cutArrayInCluLike](#)

Examples

```
.datSlope(c(3:6))
```

`.checkConv2Vect` *Convert To Simple Vector (similar to unlist)*

Description

This function allows converting 'dat' (may be list, data.frame etc) to simple vector, more elaborate than `unlist()`

Usage

```
.checkConv2Vect(dat, toNumeric = TRUE)
```

Arguments

<code>dat</code>	(list, data.frame) main input
<code>toNumeric</code>	(logical)

Value

This function returns a character (or numeric) vector

See Also

[unlist](#); used in [equLenNumber](#)

Examples

```
aa <- matrix(11:14, ncol=2)
.checkConv2Vect(aa)
```

.checkFactor *Check Factor*

Description

This function was designed to check a factor object

Usage

```
.checkFactor(  
  fac,  
  facNa = NULL,  
  minLev = 2,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

<code>fac</code>	(factor) main input
<code>facNa</code>	(character) level-names
<code>minLev</code>	(integer) minium number of levels
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

This function returns a corrceted/adjusted factor

See Also

[factor](#)

Examples

```
.checkFactor(gl(3,2))
```

.checkFileNameExtensions

Check File Name Extensions Function for checking file-names.

Description

Check File Name Extensions Function for checking file-names.

Usage

```
.checkFileNameExtensions(fileNa, ext)
```

Arguments

fileNa	(character) file name to be checked
ext	(character) file extension

Value

modified character vector

Examples

```
.checkFileNameExtensions("testFile.txt","txt")
```

.checkLegendLoc *Check argument for Location of legend*

Description

This function allows checking an argument for Location of legend, if value provided not found as valid, it returns 'defLoc

Usage

```
.checkLegendLoc(  
  legLoc,  
  defLoc = "topright",  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

legLoc (character) main input
 defLoc (character)
 silent (logical) suppress messages
 debug (logical) additional messages for debugging
 callFrom (character) allow easier tracking of messages produced

Value

This function returns a character vector designating the potential location of legend

See Also

[legend](#)

Examples

```
.checkLegendLoc("abc")
```

.checkLmConfInt	<i>Compare 'dat' to confidence interval of linare model 'lMod' (eg from lm())</i>
-----------------	---

Description

This function allows to compare 'dat' to confidence interval of linare model 'lMod' (eg from lm())

Usage

```
.checkLmConfInt(dat, lMod, level = 0.95)
```

Arguments

dat matrix or data.frame, main input
 lMod linear model, only used to extract coefficients offset & slope
 level (numeric) alpha threshold for linear model

Value

This function returns a logical vector for each value in 2nd col of 'dat' if INSIDE confid interval

See Also

[searchLinesAtGivenSlope](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
```

`.checkRegrArguments` *Check regression arguments*

Description

This function allows to check arguments for linear regression. Used as argument checking for `regrBy1or2point` and `regrMultBy1or2point`

Usage

```
.checkRegrArguments(inData, refList, regreTo, callFrom = NULL)
```

Arguments

<code>inData</code>	(numeric vector) main input
<code>refList</code>	(list)
<code>regreTo</code>	(numeric vector)
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

list

See Also

[append](#); [lrbind](#)

Examples

```
.datSlope(c(3:6))
```

`.chooseGrpCol` *Automatic choice of colors*

Description

This function allows to do automatic choice of colors: if single-> grey, if few -> RColorBrewer, if many : gradient green -> grey/red

Usage

```
.chooseGrpCol(
  nGrp,
  paired = FALSE,
  alph = 0.2,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

nGrp	(numeric vector) main input
paired	(logical)
alph	(numeric vector)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced#'

Value

This function returns a character vector with color codes

See Also

[rgb](#); [colorAccording2](#)

Examples

```
.chooseGrpCol(4)
```

<code>.combineListAnnot</code>	<i>Combine annotation information from list of matrixes</i>
--------------------------------	---

Description

This function allows to combine information (annotation) from list of matrixes (ie replace when NA), using always the columns specified in 'useCol' (numeric)

Usage

```
.combineListAnnot(
  lst,
  useCol = 1:2,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

- `lst` (list) main input
- `useCol` (numeric vector) which columns should be used
- `silent` (logical) suppress messages
- `debug` (logical) additional messages for debugging
- `callFrom` (character) allow easier tracking of messages produced

Value

This function returns a single matrix of combined (non-redundant) info

See Also

used in [cutArrayInCluLike](#)

Examples

```
.datSlope(c(3:6))
```

<code>.compareByDiff</code>	<i>Compare by distance/difference</i>
-----------------------------	---------------------------------------

Description

This function allows to compare by distance/difference

Usage

```
.compareByDiff(dat, limit, distVal = FALSE)
```

Arguments

- `dat` list of 2 numerical vectors
- `limit` (numeric, length=1) threshold value for retaining values, used with `distace`-type specified in argument `'compTy'`
- `distVal` (logical) to toggle output as matrix of numeric (distance values above `'limit'`, others NA) or matrix of logical

Value

This function returns a list with close matches of `'x'` to given `'y'`, the numeric value depends on `'sortMatch'` (if `FASLE` then always value of `'y'` otherwise of longest of `x&y`)

See Also

[findCloseMatch](#), [checkSimValueInSer](#), and also `.compareByLogRatio`, for convient output [countCloseToLimits](#)

Examples

```
cc <- list(aa=11:14, bb=c(13.1,11.5,14.3,20:21))
```

`.compareByLogRatio` *Compare by log-ratio*

Description

This function allows to compare by log-ratio

Usage

```
.compareByLogRatio(dat, limit, distVal = FALSE)
```

Arguments

<code>dat</code>	list of 2 numerical vectors
<code>limit</code>	(numeric, length=1) threshold value for retaining values, used with <code>distace</code> -type specified in argument <code>'compTy'</code>
<code>distVal</code>	(logical) to toggle output as matrix of numeric (distance values above <code>'limit'</code> , others NA) or matrix of logical

Value

This function returns a list with close matches of `'x'` to given `'y'`, the numeric value depends on `'sortMatch'` (if `FASLE` then always value of `'y'` otherwise of longest of `x&y`)

See Also

[findCloseMatch](#), [checkSimValueInSer](#), and also `.compareByDiff`, for convenient output [countCloseToLimits](#)

Examples

```
cc <- list(aa=11:14, bb=c(13.1,11.5,14.3,20:21))  
.compareByLogRatio(cc, 1)
```

.compareByPPM *Compare by PPM*

Description

This function allows to compare by ppm

Usage

```
.compareByPPM(dat, limit, distVal = FALSE)
```

Arguments

dat list of 2 numerical vectors
limit (numeric, length=1) threshold value for retaining values, used with distace-type specified in argument 'compTy'
distVal (logical) to toggle output as matrix of numeric (distance values above 'limit', others NA) or matrix of logical

Value

This function returns a list with close matches of 'x' to given 'y', the numeric value depends on 'sortMatch' (if FASLE then always value of 'y' otherwise of longest of x&y)

See Also

[findCloseMatch](#), [checkSimValueInSer](#), and also [.compareByDiff](#), for convient output [countCloseToLimits](#)

Examples

```
cc <- list(aa=11:14, bb=c(13.1,11.5,14.3,20:21))  
.compareByPPM(cc, 1)
```

.complCols *Search (complementing) Columns For Best Coverage Of Non-NA Data For rowNormalization (main)*

Description

This function was designed to complete the selection of columns of sparse matrix 'dat' with sets of 'nCombin' columns at complete 'coverage' Context : In sparse matrix 'dat' search subsets of columns with some rows as complete (no NA).

Usage

```
.complCols(x, dat, nCombin)
```

Arguments

x	(integer, length=1) column number for with other columns to combine & give (some) complete non-NA lines are seeked
dat	(matrix) .. init data, smay be parse matrix with numerous NA
nCombin	(integer) .. number of columns used to make complete subset

Value

This function returns a matrix of column-indexes complementing (nCombin rows)

See Also

[rowNormalize](#); [normalizeThis](#)

Examples

```
.complCols(3, dat=matrix(c(NA,12:17,NA,19),ncol=3), nCombin=3)
```

.composeCallName *Compose Sequence Of (Function-)Calls*

Description

This function was designed for tracing the hierarchy of function-calls. It allows to remove any tailing space or ':' from 'callFrom' (character vector) and return with added 'newNa' (+ 'add2Tail')

Usage

```
.composeCallName(newNa, add2Head = "", add2Tail = " : ", callFrom = NULL)
```

Arguments

newNa	(character vector) main input
add2Head	(character)
add2Tail	(character)
callFrom	(character) may also contain multiple separate names (ie length >1), will be concatenated using '->'

Value

This function returns a character vector (history of who called whom)

See Also

[paste](#)

Examples

```
.composeCallName("newFunction", callFrom="initFunction")
```

.convertMatrToNum *Convert numeric matrix to numeric*

Description

Take matrix and return vector

Usage

```
.convertMatrToNum(matr, useCol = NULL)
```

Arguments

matr (matrix) main input
useCol (integer) design the columns to be used

Value

numeric vector

See Also

[matrix](#)

Examples

```
.convertMatrToNum(matrix(1:6, ncol=2))
```

.convertNa *Convert/standardize names of 'query' to standard names from 'ref'*

Description

This function converts/standardizes names of 'query' to standard names from 'ref' (list of possible names (char vect) where names define standardized name). It takes 'query' as character vector and return character vector (same length as 'query') with 'converted/corrected' names

Usage

```
.convertNa(query, ref, partMatch = TRUE)
```

Arguments

query	(matrix or data.frame, min 2 columns) main input
ref	(list) list of multiple possible names associated to given group, reference name for each group is name of list
partMatch	(logical) allows partial matching (ie name of 'ref' must be in head of 'query')

Value

This function returns a character vector

Examples

```
daPa <- matrix(c(1:5,8,2:6,9), ncol=2)
```

.corDuplItemsByIncrem Avoid duplicating items between 'curNa' and 'newNa' by incrementing digits after 'extPref' (in newNa)

Description

This function aims to avoid duplicating items between 'curNa' and 'newNa' by incrementing digits after 'extPref' (in newNa)

Usage

```
.corDuplItemsByIncrem(newNa, curNa, extPref = "_s")
```

Arguments

newNa	(character) main input 1
curNa	(character) main input 2
extPref	(character) extension

Value

This function returns the corrected input vector newNa

See Also

[duplicated](#)

Examples

```
.corDuplItemsByIncrem(letters[1:6], letters[8:4])
```

<code>.cutAtSearch</code>	<i>Search character-string and cut either before or after</i>
---------------------------	---

Description

This function extracts/cuts text-fragments out of `txt` following specific anchors defined by arguments `cutFrom` and `cutTo`.

Usage

```
.cutAtSearch(  
  x,  
  searchChar,  
  after = TRUE,  
  silent = TRUE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

<code>x</code>	character vector to be treated
<code>searchChar</code>	(character) text to look for
<code>after</code>	(logical)
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

This function returns a modified character vector

See Also

[grep](#)

Examples

```
.cutAtSearch("abcdefg", "de")
```

`.cutStr` *Cut string to get all variants from given start with min and max length*

Description

This function allows truncating character vector to all variants from given start, with min and optional max length Used to evaluate argument calls without giving full length of argument

Usage

```
.cutStr(txt, startFr = 1, minLe = 1, maxLe = NULL, reverse = TRUE)
```

Arguments

<code>txt</code>	(character) main input, may be length >1
<code>startFr</code>	(integer) where to start
<code>minLe</code>	(integer) minimum length of output
<code>maxLe</code>	(integer) maximum length of output
<code>reverse</code>	(logical) return longest text-fragments at beginning of vector

Value

This function returns a character vector

See Also

used in [pasteC](#); [substr](#)

Examples

```
.cutStr("abcdefg", minLe=2)
```

`.datSlope` *Model linear regression and optional plot*

Description

This function allows to model a linear regression and optionally to plot the results

Usage

```
.datSlope(  
  dat,  
  typeOfPlot = "sort",  
  toNinX = FALSE,  
  plotData = FALSE,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

- dat (vector or matrix) main input
- typeOfPlot (character)
- toNinX (logical)
- plotData (logical)
- silent (logical) suppress messages
- debug (logical) display additional messages for debugging
- callFrom (character) allow easier tracking of messages produced

Value

numeric vector with intercept and slope, optional plot

See Also

[append](#); [lrbind](#)

Examples

```
.datSlope(c(3:6))
```

.doubleExt	<i>Return File-name Extensions Including Double Extensions (eg txt.gz)</i>
------------	--

Description

This function allows retrieving extensions to filenames similar to [file_ext](#), but also allows to retrieve selected double-extensions (txt.gz). The leading dot will be excluded similar to [file_ext](#)

Usage

```
.doubleExt(fiNa, termExt = c("gz", "zip"))
```

Arguments

`fiNa` (character) name of file to be tested (may include path)
`termExt` (character) additional terminal extensions

Details

The argument `termExt` allows specifying additional (terminal) extensions to be recognized.

Value

This function returns a character vector with file-extensions (excluding the leading dot). (Only purely alphanumeric extensions are recognized.)

See Also

[file_ext](#), [checkFilePath](#)

Examples

```
fi <- c("ab", "ab.c", "ab.c.gz", "ab.d", "ab.d.zip", "ab.e")
.doubleExt(fi)
```

<i>.extrNAneighb</i>	<i>Extract NA-neighbour values</i>
----------------------	------------------------------------

Description

This function allows extracting NA-neighbour value

Usage

```
.extrNAneighb(x, grp)
```

Arguments

`x` initial matrix to treat
`grp` (factor) grouping of replicates

Value

This function returns a numeric vector

See Also

[unique](#), [nonAmbiguousNum](#), faster than [firstOfRepeated](#) which gives more detail in output (lines/elements/indexes of omitted)

Examples

```
.extrNAneighb(c(11:14,NA), rep(1,5))
```

`.extrNumHeadingCap` *Extract number(s) before capital character*

Description

This function aims to extract number(s) before capital character

Usage

```
.extrNumHeadingCap(x)
```

Arguments

x character vector to be treated

Value

This function returns a numeric vector

See Also

[grep](#), [nchar](#)

Examples

```
.extrNumHeadingCap(" 1B ")
```

`.extrNumHeadingSepChar` *Extract numbers before separator followed by alphabetic character*

Description

This function aims to extract number(s) before separator followed by alphabetic character (return named numeric vector, NAs when no numeric part found)

Usage

```
.extrNumHeadingSepChar(x, sep = "_")
```

Arguments

x character vector to be treated
sep (character) separator

Value

This function returns a numeric vector

See Also

[nchar](#)

Examples

```
.extrNumHeadingSepChar(" 1B ")
```

<code>.filterNetw</code>	<i>Filter nodes & edges for extracting networks (main) This function allows extracting and filtering network-data based on fixed threshold (limInt) and add sandwich-nodes (nodes inter-connecting initial nodes) out of node-based queries.</i>
--------------------------	--

Description

Filter nodes & edges for extracting networks (main)

This function allows extracting and filtering network-data based on fixed threshold (limInt) and add sandwich-nodes (nodes inter-connecting initial nodes) out of node-based queries.

Usage

```
.filterNetw(
  lst,
  remOrphans = TRUE,
  reverseCheck = TRUE,
  filtCol = 2,
  callFrom = NULL,
  silent = FALSE,
  debug = FALSE
)
```

Arguments

<code>lst</code>	(list, composed of multiple matrix or data.frames) main input (each list-element should have same number of columns)
<code>remOrphans</code>	(logical) remove networks consisting only of 2 connected edges
<code>reverseCheck</code>	(logical)
<code>filtCol</code>	(integer, length=1) which column of lst should be used to filter using thresholds limInt and sandwLim
<code>callFrom</code>	(character) allow easier tracking of message(s) produced
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) display additional messages for debugging

Value

This function returns a matrix or data.frame

See Also

[filterNetw](#) and other CRAN package dedicated to networks

Examples

```
ab <- 1:10
```

.filterSw	<i>Filter 3-dim array of numeric data (main)</i>
-----------	--

Description

Filtering of matrix or array x (may be 3-dim array) according to fiTy and checkVa

Usage

```
.filterSw(x, fiTy, checkVa, indexRet = TRUE)
```

Arguments

- x array (3-dim) of numeric data
- fiTy (character) which type of testing to perform ('eq','inf','ineq','sup','supeq','>','<','>=','<=','==')
- checkVa (logical) s
- indexRet (logical) if TRUE (default) rather return index numbers than filtered values

Value

This function returns either index (position within 'x') or concrete (filtered) result

See Also

[filt3dimArr](#); [filterList](#); [filterLiColDeList](#);

Examples

```
arr1 <- array(11:34, dim=c(4,3,2), dimnames=list(c(LETTERS[1:4]),
  paste("col",1:3,sep=""),c("ch1","ch2")))
filt3dimArr(arr1,displCrit=c("col1","col2"),filtCrit="col2",filtVal=7)
.filterSw(arr1, fiTy="inf", checkVa=7)
```

`.filtSize` *Filter for size*

Description

This function aims to filter for size

Usage

```
.filtSize(x, minSize = 5, maxSize = 36)
```

Arguments

<code>x</code>	main input
<code>minSize</code>	(integer) minimum number of characters, if NULL set to 0
<code>maxSize</code>	(integer) maximum number of characters

Value

This function returns a list of filtered input

See Also

[filtSizeUniq](#); [correctToUnique](#), [unique](#), [duplicated](#)

Examples

```
aa <- 1:10
```

`.findBorderOverlaps` *Find overlap instances among range of values in lines*

Description

This function aims to find overlap instances among range of values in lines of 'x' (typically give just min & max)

Usage

```
.findBorderOverlaps(x, rmRedund = FALSE, callFrom = NULL)
```

Arguments

<code>x</code>	(matrix of numeric values or all-numeric data.frame) main input
<code>rmRedund</code>	(logical) report overlaps only in 1st instance (will show up twice otherwise)
<code>callFrom</code>	(character) allow easier tracking of message(s) produced

Value

This function returns a matrix with line for each overlap found, cols 'refLi' (line no), 'targLi' (line no), 'targCol' (col no)

See Also

[nchar](#)

Examples

```
aa <- 11:15
```

.firstMin

Get first minimum

Description

This function allows to find the first minimum of a numeric vector

Usage

```
.firstMin(x, positionOnly = FALSE)
```

Arguments

x (numeric vector) main input
positionOnly (logical)

Value

numeric vector

See Also

[which.min](#)

Examples

```
.firstMin(c(4,3:6))
```

```
.fuse2ArrBy2ndDim      fuse 2 instances of 3dim arr as mult cols in 3dim array
```

Description

This function allows fusing 2 instances of 3dim arr as mult cols in 3dim array (ie fuse along 2nd dim, increase cols)

Usage

```
.fuse2ArrBy2ndDim(arr1, arr2, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

<code>arr1</code>	(array)
<code>arr2</code>	(array)
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

This functuin returns a numeric vector with numer of non-numeric characters (ie not '.' or 0-9)

See Also

[array](#)

Examples

```
aa <- 11:15
```

```
.getAmean      Get A value for each group of replicates
```

Description

This function calculates the 'A' value (ie group mean) for each group of replicates (eg for MA-plot)

Usage

```
.getAmean(dat, grp)
```

Arguments

`dat` (matrix or data.frame) main input
`grp` (factor) grouping of replicates

Value

This function returns a numeric vector

See Also

[makeMAList](#)

Examples

```
.getAmean(matrix(11:18, ncol=4), gl(2,2))
```

<code>.getAmean2</code>	<i>Get A value for each group of replicates based on comp</i>
-------------------------	---

Description

This function calculates the 'A' value (ie group mean) for each group of replicates (eg for MA-plot)
`comp` is matrix telling which groups to use/compare, assuming that `dat` are already group-means

Usage

```
.getAmean2(dat, comp)
```

Arguments

`dat` (matrix or data.frame) main input
`comp` (matrix) tells which groups to use/compare, assuming that `dat` are already group-means

Value

This function returns a numeric vector

See Also

[makeMAList](#)

Examples

```
.getAmean(matrix(11:18, ncol=4), gl(2,2))
```

<code>.getMvalue2</code>	<i>Get M value for each group of replicates based on comp</i>
--------------------------	---

Description

This function calculates the 'M' value (ie log-ratio) for each group of replicates based on comp (eg for MA-plot) comp is matrix telling which groups to use/compare, assuming that dat are already group-means)

Usage

```
.getMvalue2(dat, comp)
```

Arguments

<code>dat</code>	(matrix or data.frame) main input
<code>comp</code>	(matrix) tells which groups to use/compare, assuming that dat are already group-means)

Value

This function returns a numeric vector

See Also

[makeMAList](#)

Examples

```
.getAmean(matrix(11:18, ncol=4), gl(2,2))
```

<code>.getPWseparator</code>	<i>Find Separator In Vector Of Pairwise Group-Names This function allows identifying separator used when pairwise groups are presented.</i>
------------------------------	---

Description

Find Separator In Vector Of Pairwise Group-Names

This function allows identifying separator used when pairwise groups are presented.

Usage

```
.getPWseparator(  
  compNames,  
  potSep = "split1",  
  includeGrp = FALSE,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

<code>compNames</code>	(character or integer) names of pairwise combined group-names
<code>potSep</code>	(character) potential separators to be checked if occurring in useComp; the first fitting will used
<code>includeGrp</code>	(logical) if <code>includeGrp=TRUE</code> a list including also the group-names is returned
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Details

Note : Potential separators `potSep` to be tested must be at least 1 character long

The character '.' may used as `potSep`, it will be protected internally for correct results. Note : The indexing is relative to the levels of `grp`, thus to sorted group-names !

Value

This function returns a character vector (length=1) of the (first) separator fitting to all data, or a list with `$sep` and `$grpNa` if `includeGrp=TRUE`

See Also

[indexGroupsFromPW](#), [getPWseparator](#), colnames of testing results from [moderTestXgrp](#), used by [replacePWseparator](#)

Examples

```
.getPWseparator(compNames=c("B-C", "B-D", "C-D"))
```

`.growTree` *Grow Tree*

Description

This function allows growing tree-like structures (data.tree objects)

Usage

```
.growTree(tm, setX, addToObj = NULL)
```

Arguments

<code>tm</code>	(list) main input, \$disDat .. matrix with integer start & end sites for fragments; \$lo (logical) which fragments may be grown; \$start (integer) index for which line of \$disDat to start; \$it numeric version of \$lo; \$preN for previous tree objects towards root; \$iter for iterator (starting at 1))
<code>setX</code>	.. data.tree object (main obj from root)
<code>addToObj</code>	.. data.tree object (branch on which to add new branches/nodes)

Value

This function returns a list

See Also

[buildTree](#)

Examples

```
.datSlope(c(3:6))
```

`.insp1dimByClustering` *Segment (1-dim vector) 'dat' into clusters*

Description

This function allows segmenting (1-dim vector) 'dat' into clusters. If 'automClu=TRUE ..' first try automatic clustering, if too few clusters, run km with $\text{length}(\text{dat})^{0.3}$ clusters This function requires the package NbClust to be installed.

Usage

```
.insp1dimByClustering(  
  dat,  
  automClu = TRUE,  
  cluChar = TRUE,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

dat	matrix or data.frame, main input
automClu	(logical) run automatic clustering
cluChar	(logical) to display cluster characteristics
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns clustering (class index) or (if 'cluChar'=TRUE) list with clustering and cluster-characteristics

See Also

[searchLinesAtGivenSlope](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
```

.inspectHeader *Inspect 'matr' and check if 1st line can be used/converted as header*

Description

This function inspects 'matr' and check if 1st line can be used/converted as header. If colnames of 'matr' are either NULL or 'V1',etc the 1st row will be tested if it contains any of the elements (if not, 1st line won't be used as new colnames) If 'numericCheck'=TRUE, all columns will be tested if they can be converted to numeric

Usage

```
.inspectHeader(
  matr,
  headNames = c("Plate", "Well", "StainA"),
  numericCheck = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

matr	(matrix or data.frame) main input to be inspected
headNames	(character) column-names to look for
numericCheck	(logical) allows reducing complexity by drawing for very long x or y
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a matrix vector or data.frame similar to input

See Also

[head](#) for looking at first few lines

Examples

```
ma1 <- matrix(letters[1:6], ncol=3, dimnames=list(NULL,c("ab","Plate","Well")))
.inspectHeader(ma1)
```

.keepCenter1d	<i>Refine/filter 'dat1' (1dim dataset, eg cluster) with aim of keeping center of data</i>
---------------	---

Description

This function allows to refine/filter 'dat1' (1dim dataset, eg cluster) with aim of keeping center of data. It is done based on most freq class of histogram keep/filter data if 'core' (

Usage

```
.keepCenter1d(  
  dat1,  
  core = NULL,  
  keepOnly = TRUE,  
  displPlot = FALSE,  
  silent = TRUE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

dat1	simple numeric vector
core	numeric vactor (betw 0 and 1) for fraction of data to keep; if null trimmed-Mean/max hist occurance will be used, limited within 30-70 perent; may also be 'high' or 'low' for forcing low (20-60percent) or high (75-99) percent of data to retain
keepOnly	(logical)
displPlot	(logical) show plot of hist & boundaries
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns the index of values retained or if 'keepOnly' return list with 'keep' index and 'drop' index

See Also

[searchLinesAtGivenSlope](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
```

.keepFiniteCol *Remove all columns where all data are not finite*

Description

This function aims to remove all columns where all data are not finite

Usage

```
.keepFiniteCol(  
  dat,  
  msgStart = NULL,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

dat	(matrix or data.frame) main input
msgStart	(character)
silent	(logical) suppresses messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a corrected matrix or data.frame

See Also

[renameColumns](#); [is.finite](#)

Examples

```
ma1 <- matrix(c(1:5, Inf), ncol=2)  
.keepFiniteCol(ma1)
```

.maybeNum

Check if vector may be numeric content

Description

This function allows to checking if a given vector may be numeric content

Usage

```
.maybeNum(x, pattern = NULL)
```

Arguments

x	(numeric vector) main input
pattern	(character) custom pattern to check

Value

This functions returns a logical/boolean vector for each of the elements of 'x'

See Also

[numeric](#); [convMatr2df](#)

Examples

```
.maybeNum(c(3:6))
```

.medianSpecGrp	<i>Rescale respective to specific group</i>
----------------	---

Description

This function allows to rescale data 'x' so that specific group 'grpNum' gets normalized to predefined value 'grpVal'. In normal case x will be multiplied by 'grpVal' and divided by value obtained from 'grpNum'. If summary of 'grpNum-positions' or 'grpVal' is 0, then grpVal will be attained by subtraction of summary & adding grpVal

Usage

```
.medianSpecGrp(x, grpNum, grpVal, sumMeth = "median", callFrom = NULL)
```

Arguments

- x (numeric vector) main input
- grpNum (numeric)
- grpVal (numeric)
- sumMeth (character) method for summarizing
- callFrom (character) allow easier tracking of messages produced

Value

numeric vector

See Also

[which.min](#)

Examples

```
.firstMin(c(4,3:6))
```

<code>.mergeMatrices</code>	<i>Merge Multiple Matrices (main)</i>
-----------------------------	---------------------------------------

Description

This function allows merging of multiple matrix-like objects from an initial list.

Usage

```
.mergeMatrices(
  inpl,
  mode = "intersect",
  useColumn = 1,
  extrRowNames = FALSE,
  na.rm = TRUE,
  argL = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<code>inpl</code>	(list containing matrices or data.frames) main input (multiple matrix or data.frame objects)
<code>mode</code>	(character) allows choosing restricting to all common elements (mode= 'intersect') or union (mode='union')
<code>useColumn</code>	(integer, character or list) the column(s) to consider, may be 'all' to use all, integer to select specific indexes or list of indexes or colnames for custom-selection per matrix
<code>extrRowNames</code>	(logical) decide whether columns with all values different (ie no replicates or max divergency) should be excluded
<code>na.rm</code>	(logical) suppress NAs
<code>argL</code>	(list of arguments)
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

This function returns a matrix containing all selected columns of the input matrices to fuse

See Also

[mergeMatrixList](#), [merge](#), [mergeMatrices](#) for separate entries

Examples

```
mat1 <- matrix(11:18, ncol=2, dimnames=list(letters[3:6],LETTERS[1:2]))
```

.minDif *find closest neighbour to numeric vector*

Description

This function aims to find closest neighbour to numeric vector

Usage

```
.minDif(z, initOrder = TRUE, rat = TRUE)
```

Arguments

z (numeric) vector to search minimum difference
initOrder (logical) return matrix so that 'x' matches exactly 2nd col of output
rat (logical) express result as ratio

Value

This function returns a matrix with index,value,dif,best

See Also

[dist](#)

Examples

```
.minDif(c(11:15,17))
```

.neighbDis *Distances beteenw sorted points of 2-columns*

Description

This function returns distances beteenw sorted points of 2-column matrix 'x'

Usage

```
.neighbDis(x, asSum = TRUE)
```

Arguments

x	(matrix or data.frame, min 2 columns) main input
asSum	(logical) if TRUE (default) the sum of all distances will be returned, otherwise the individual distances

Value

This function returns a numeric vector with distances

Examples

```
daPa <- matrix(c(1:5,8,2:6,9), ncol=2)
.neighbDis(daPa)
```

.normalize	<i>Main Normalization function</i>
------------	------------------------------------

Description

This function aims to normalize a matrix or data.frame by columns. It assumes all checks have been done before calling this function.

Usage

```
.normalize(
  dat,
  meth,
  mode,
  param,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	matrix or data.frame of data to get normalized
meth	(character) may be "mean", "median", "NULL", "none", "standardize", "trimMean", "rowNormalize", "slope", "exponent", "twoPointSlope", "vsn"; When NULL or 'none' is chosen the input will be returned
mode	(character) may be "proportional", "additive"; decide if normalization factors will be applied as multiplicative (proportional) or additive; for log2-omics data mode="additive" is suggested
param	(list) additional parameters
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a numeric vector

See Also

[normalizeThis](#)

Examples

```
aa <- matrix(1:12, ncol=3)
.normalize(aa,"median",mode="proportional",param=NULL)
```

.normConstSlope	<i>Normalize Columns Of 2-dim Matrix To Common Linear Regression Fit</i>
-----------------	--

Description

This function aims to normalize columns of 2dim matrix to common linear regression fit within range of 'useQuant'

Usage

```
.normConstSlope(
  mat,
  useQuant = c(0.2, 0.8),
  refLines = NULL,
  diagPlot = TRUE,
  plotLog = "",
  datName = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

- mat matrix or data.frame of data to get normalized
- useQuant (numeric) quantiles to use
- refLines (NULL or numeric) allows to consider only specific lines of 'dat' when determining normalization factors (all data will be normalized)
- diagPlot (logical) draw diagnostic plot
- plotLog (character) indicate which axis should be displayed on log-scale, may be 'x', 'xy' or 'y'
- datName (character) use as title in diag plot

silent (logical) suppress messages
 debug (logical) additional messages for debugging
 callFrom (character) allows easier tracking of messages produced

Value

This function returns a numeric vector

See Also

[normalizeThis](#)

Examples

```
aa <- matrix(1:12, ncol=3)
```

<code>.pasteCols</code>	<i>Paste-concatenate all columns of matrix</i>
-------------------------	--

Description

This function allows paste columns

Usage

```
.pasteCols(mat, sep = "")
```

Arguments

mat initial matrix
 sep (character) separator

Value

This function returns a simplified/non-redundant vector/matrix (ie fewer lines for matrix), or respective index

See Also

[unique](#), [nonAmbiguousNum](#), faster than [firstOfRepeated](#) which gives more detail in output (lines/elements/indexes of omitted)

Examples

```
.pasteCols(matrix(11:16, ncol=2), sep="_")
```

.plotCountPie *Pie plot for counting results*

Description

This function allows to inspect results of `table` or `uniqCountReport` on a pie-plot Note : fairly slow for long vectors !!

Usage

```
.plotCountPie(  
  count,  
  tit = NULL,  
  col = NULL,  
  radius = 0.9,  
  sizeTo = NULL,  
  clockwise = FALSE,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

<code>count</code>	(integer vector) counting result
<code>tit</code>	(character) optional title in plot
<code>col</code>	(character) custom colors in pie
<code>radius</code>	(numeric) radius passed to pie
<code>sizeTo</code>	(numeric or character) optional reference group for size-population relative adjusting overall surface of pie
<code>clockwise</code>	(logical) argument passed to pie
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

vector with counts of `n` (total), `nUnique` (wo any repeated), `nHasRepeated` (first of repeated), `nRedundant`), optional figure

See Also

[uniqCountReport](#), [correctToUnique](#), [unique](#)

Examples

```
.plotCountPie(table(c(1:5,4:2)))
```

<code>.plusLowerCaps</code>	<i>Add lower caps to character vector</i>
-----------------------------	---

Description

This function allows adding all content as lower caps to/of character vector

Usage

```
.plusLowerCaps(x)
```

Arguments

x (character) main input

Value

This function returns a elongated character vector

See Also

[chartr](#)

Examples

```
.plusLowerCaps(c("Abc", "BCD"))
```

<code>.predRes</code>	<i>Calculate residues of (2-dim) linear model 'lMod'-prediction off/for 'dat'</i>
-----------------------	---

Description

This function calculates residues of (2-dim) linear model 'lMod'-prediction off/for 'dat' (using 2nd col of 'useCol') (indexing in 'dat', matrix or data.frame with min 2 cols), using 1st col of 'useCol' as 'x'. It may be used for comparing/identifying data close to regression (eg re-finding data on autoregression line in FT-ICR)

Usage

```
.predRes(dat, lMod, regTy = "lin", useCol = 1:2)
```

Arguments

dat matrix or data.frame, main input
 lMod linear model, only used to extract coefficients offset & slope
 regTy (character) type of regression model
 useCol (integer) columns to use

Value

This function returns a numeric vector of residues (for each line of dat)

See Also

[searchLinesAtGivenSlope](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
```

.raiseColLowest *Raise all values close to lowest value*

Description

This function aims to raise all values close to lowest value to end up as at value of 'raiseTo'. This is done independently for each col of mat. This function sets all data to common raiseTo (which is min among all cols)

Usage

```
.raiseColLowest(
  mat,
  raiseTo = NULL,
  minFa = 0.1,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

mat (matrix of numeric values) main input
 raiseTo (numeric)
 minFa (numeric) minimum factor
 silent (logical) suppress messages
 debug (logical) display additional messages for debugging
 callFrom (character) allow easier tracking of message(s) produced

Value

This function returns a numeric vector with number of non-numeric characters (ie not '.' or 0-9)

See Also

[nchar](#)

Examples

```
aa <- 11:15
```

<code>.removeCol</code>	<i>Remove columns indicated by col-number</i>
-------------------------	---

Description

This function aims to remove columns indicated by col-number

Usage

```
.removeCol(matr, rmCol)
```

Arguments

<code>matr</code>	(matrix or data.frame) main input
<code>rmCol</code>	(integer) column index for removing

Value

This function returns an matrix or data.frame

See Also

[dist](#)

Examples

```
aa <- matrix(1:6, ncol=3)  
.removeCol(aa, 2)
```

<code>.removeEmptyCol</code>	<i>Search for (empty) columns containing only entries defined in 'searchFields' and remove such columns</i>
------------------------------	---

Description

This function aims to search for (empty) columns containing only entries defined in 'searchFields' and remove such columns. If 'fromBackOnly' =TRUE .. only trailing empty columns will be removed (other columns with "empty" entries in middle will be kept). If ""=TRUE columns containing all NAs will be excluded as well This function will also remove columns containing (exclusively) mixtures of the various 'searchFields'.

Usage

```
.removeEmptyCol(  
  dat,  
  fromBackOnly = TRUE,  
  searchFields = c("", " ", "NA.", NA),  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

<code>dat</code>	(matrix or data.frame) main input
<code>fromBackOnly</code>	(logical)
<code>searchFields</code>	(character)
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allows easier tracking of messages produced

Value

This function returns a corrected matrix or data.frame

See Also

[renameColumns](#); [is.finite](#)

Examples

```
ma1 <- matrix(c(1:5, NA), ncol=2)  
.removeEmptyCol(ma1)
```

`.replSpecChar` *Replace Special Characters*

Description

This function allows replacing special characters Note that (most) special characters must be presented with protection for `grep` and `sub`.

Usage

```
.replSpecChar(x, findSp = c("\\(", "\\)", "\\$"), replBy = "_")
```

Arguments

<code>x</code>	(character) main input
<code>findSp</code>	(character) special characters to replace (may have to be given as protected)
<code>replBy</code>	(character) replace by

Value

This function returns a corrected/adjusted factor

See Also

[factor](#)

Examples

```
.replSpecChar(c("jhjh(ab)", "abc"))
```

`.retain1stPart` *Trim character string: keep only text before 'sep'*

Description

This functions trims character strings: It keeps only text before 'sep' (length=1 !)

Usage

```
.retain1stPart(chr, sep = " = ", offSet = 1)
```

Arguments

<code>chr</code>	character vector to be treated
<code>sep</code>	(character) separator
<code>offSet</code>	(integer) off-set

Value

This function returns a modified character vector

See Also

[substr](#)

Examples

```
.retain1stPart("abc = def")
```

.rowGrpCV	<i>row group CV (main)</i>
-----------	----------------------------

Description

This function calculates CVs for matrix with multiple groups of data, ie one CV for each group of data.

Usage

```
.rowGrpCV(x, grp, means)
```

Arguments

x	numeric matrix where replicates are organized into separate columns
grp	(factor) defining which columns should be grouped (considered as replicates)
means	(numeric) alternative values instead of means by .rowGrpMeans()

Value

This function returns a matrix of CV values

See Also

[rowGrpCV](#), [rowCVs](#), [arrayCV](#), [replPlateCV](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
grp1 <- gl(4,3,labels=LETTERS[1:4])[2:11]
head(.rowGrpCV(dat1, grp1, .rowGrpMeans(dat1, grp1)))
```

`.rowGrpMeans` *row group mean (main)*

Description

This function calculates CVs for matrix with multiple groups of data, ie one CV for each group of data.

Usage

```
.rowGrpMeans(x, grp, na.replVa = NULL, na.rm = TRUE)
```

Arguments

`x` numeric matrix where replicates are organized into separate columns
`grp` (factor) defining which columns should be grouped (considered as replicates)
`na.replVa` (numeric) value to replace NA values
`na.rm` (logical) remove all NA values

Value

This function returns a matrix of mean values per row and group of replicates

See Also

[rowGrpCV](#), [rowCVs](#), [arrayCV](#), [replPlateCV](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
grp1 <- gl(4,3,labels=LETTERS[1:4])[2:11]
head(.rowGrpMeans(dat1, grp1))
```

`.rowGrpSds` *row group sd (main)*

Description

This function calculates sd for matrix with multiple groups of data, ie one sd for each group of data.

Usage

```
.rowGrpSds(x, grp)
```

Arguments

- x numeric matrix where replicates are organized into separate columns
- grp (factor) defining which columns should be grouped (considered as replicates)

Value

This function returns a matrix of sd values per row and group of replicates

See Also

[rowGrpCV](#), [rowCVs](#), [arrayCV](#), [replPlateCV](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
grp1 <- gl(4,3,labels=LETTERS[1:4])[2:11]
head(.rowGrpSds(dat1, grp1))
```

.rowGrpSums *row group rowSums per group (main)*

Description

This function calculates row-sums for matrix with multiple groups of data, with multiple groups of data, ie one sd for each group of data.

Usage

```
.rowGrpSums(x, grp, na.replVa = NULL, na.rm = TRUE)
```

Arguments

- x numeric matrix where replicates are organized into separate columns
- grp (factor) defining which columns should be grouped (considered as replicates)
- na.replVa (numeric) value to replace NA values
- na.rm (logical) remove all NA values

Value

This function returns a matrix of row-sums for matrix with multiple groups of data

See Also

[rowGrpCV](#), [rowCVs](#), [arrayCV](#), [replPlateCV](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
grp1 <- gl(4,3,labels=LETTERS[1:4])[2:11]
head(.rowGrpSums(dat1, grp1))
```

`.rowNorm`*Row-normalization Procedure On Matrix Or Data.frame (main)*

Description

This function performs a row-normalization procedure on matrix or data.frame 'dat'

Usage

```
.rowNorm(
  dat,
  refLi,
  method,
  proportMode,
  maxFact = 10,
  fact0val = 10,
  retFact = FALSE,
  debug = FALSE,
  silent = FALSE,
  callFrom = NULL
)
```

Arguments

<code>dat</code>	(matrix) .. init data, smay be parse matrix with numerous NA
<code>refLi</code>	(NULL or numeric) allows to consider only specific lines of 'dat' when determining normalization factors (all data will be normalized)
<code>method</code>	(character) may be "mean","median" (plus "NULL","none"); When NULL or 'none' is chosen the input will be returned as is
<code>proportMode</code>	(logical) decide if normalization should be done by multiplicative or additive factor
<code>maxFact</code>	(numeric, length=2) max normalization factor
<code>fact0val</code>	(integer)
<code>retFact</code>	(logical)
<code>debug</code>	(logical) additional messages for debugging
<code>silent</code>	(logical) suppress messages
<code>callFrom</code>	(character) This function allows easier tracking of messages produced

Value

This function returns a matrix of normalized data same dimensions as 'dat'

See Also

[rowNormalize](#); [normalizeThis](#)

Examples

```
.rowNorm(matrix(11:31, ncol=3), refLi=1, method="mean", proportMode=TRUE)
```

.rowNormFact	<i>Obtain Normalization Factor (main)</i>
--------------	---

Description

This function was designed to obtain normalization factors.

Usage

```
.rowNormFact(
  dat,
  combOfN,
  comUse,
  method = "median",
  refLi = NULL,
  refGrp = NULL,
  proportMode = TRUE,
  minQuant = NULL,
  maxFact = 10,
  omitNonAlignable = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

- dat (matrix) .. init data, smay be parse matrix with numerous NA
- combOfN (matrix) .. # matrix of index for all sub-groups (assumed as sorted)
- comUse (list) .. index of complete lines for each col of combOfN
- method (character) may be "mean","median" (plus "NULL","none"); When NULL or 'none' is chosen the input will be returned as is
- refLi (NULL or numeric) allows to consider only specific lines of 'dat' when determining normalization factors (all data will be normalized)

refGrp	(integer) Only the columns indicated will be used as reference, default all columns (integer or colnames)
proportMode	(logical) decide if normalization should be done by multiplicative or additive factor
minQuant	(numeric) optional filter to set all values below given value as NA
maxFact	(numeric, length=2) max normalization factor
omitNonAlignable	(logical) allow omitting all columns which can't get aligned due to sparseness
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) This function allows easier tracking of messages produced

Value

This function returns a matrix of column-indexes complementing (nCombin rows)

See Also

[rowNormalize](#); [normalizeThis](#)

Examples

```
ma1 <- matrix(11:41, ncol=3)
```

.scale01	<i>Scale between 0 and 1 (main)</i>
----------	-------------------------------------

Description

This function rescales between 0 and 1

Usage

```
.scale01(x)
```

Arguments

x numeric vector to be re-scaled

Value

This function returns a numeric vector of same length with re-scaled values

See Also

[scaleXY](#) , [scale](#)

Examples

```
.scale01(11:15)
```

<code>.scaleSpecGrp</code>	<i>Rescale respective to specific group</i>
----------------------------	---

Description

This function allows to rescale data 'x' so that 2 specific groups get normalized to predefined values (and all other values follow proportionally) 'grp1Num' and 'grp2Num' should be either numeric for positions in 'x' or character for names of 'x'; if 'grp1Num' and/or 'grp2Num' design multiple locations: perform median or mean summarization, according to 'sumMeth'

Usage

```
.scaleSpecGrp(  
  x,  
  grp1Num,  
  grp1Val,  
  grp2Num = NULL,  
  grp2Val = NULL,  
  sumMeth = "mean",  
  callFrom = NULL  
)
```

Arguments

x	(numeric vector) main input
grp1Num	(numeric)
grp1Val	(numeric)
grp2Num	(numeric)
grp2Val	(numeric)
sumMeth	(character) method for summarizing
callFrom	(character) allow easier tracking of messages produced

Value

numeric vector

See Also

[which.min](#)

Examples

```
.firstMin(c(4,3:6))
```

<code>.scaleXY</code>	<i>Scale between min and max value (main)</i>
-----------------------	---

Description

This function rescales between user-defined min and max values

Usage

```
.scaleXY(x, minim = 2, maxim = 3)
```

Arguments

<code>x</code>	numeric vector to be re-scaled
<code>minim</code>	(numeric) minimum value for resultant vector
<code>maxim</code>	(numeric) minimum value for resultant vector

Value

This function returns a matrix of CV values

See Also

[scaleXY](#), [scale](#)

Examples

```
.scaleXY(11:15, min=1, max=100)
```

<code>.seqCutStr</code>	<i>Cut string to get all variants from given start with min length, deprecated</i>
-------------------------	--

Description

This function is deprecated, please use `/cutStr` instead ! This function allows truncating character vector to all variants from given start, with min and optional max length Used to evaluate argument calls without giving full length of argument

Usage

```
.seqCutStr(txt, startFr = 1, minLe = 1, reverse = TRUE)
```

Arguments

- txt (character) main input, may be length >1
- startFr (integer) where to start
- minLe (integer) minimum length of output
- reverse (logical) return longest text-fragments at beginning of vector

Value

This function returns a character vector

See Also

[pasteC](#); [substr](#)

Examples

```
.seqCutStr("abcdefg", minLe=2)
```

.setLowestTo *Set lowest value to given value*

Description

This function aims to set lowest value of x to value 'setTo'

Usage

```
.setLowestTo(x, setTo)
```

Arguments

- x (numeric) main vector to be treated
- setTo (numeric) replacement value

Value

This function returns a numeric vector

See Also

[nchar](#)

Examples

```
.setLowestTo(9:4, 6)
```

<code>.sortMid</code>	<i>Choose most frequent or middle of sorted vector</i>
-----------------------	--

Description

This function chooses the (first) most frequent or middle of sorted vector, similar to the concept of mode

Usage

```
.sortMid(x, retVal = TRUE)
```

Arguments

<code>x</code>	(numeric) main input
<code>retVal</code>	(logical) return value of most frequent, if FALSE return index of (1st) 'x' for most frequent

Value

This function returns a numeric vector

See Also

simple/partial functionality in [summarizeCols](#), [checkSimValueInSer](#)

Examples

```
.sortMid(11:14)
.sortMid(rep("b", 3))
```

<code>.stackArray</code>	<i>Reorganize array by reducing dimension 'byDim' (similar to stack() for data-frames)</i>
--------------------------	--

Description

This function aims to reorganize an array by reducing dimension 'byDim' (similar to stack() for data-frames) It returns an array/matrix of 1 dimension less than 'arr', 1st dim has more lines (names as paste with '_')

Usage

```
.stackArray(arr, byDim = 3)
```

Arguments

arr (array) main input
 byDim (integer)

Value

This function returns an array/matrix of 1 dimension less than 'arr', 1st dim has more lines (names as paste with '_')

See Also

[dist](#)

Examples

```
(arr1 <- array(11:37, dim=c(3,3,3)))
.stackArray(arr1, 3)
```

.summarizeCols	<i>Summarize columns of matrix (or data.frame) 'x' using apply (main)</i>
----------------	---

Description

This function summarizes columns of matrix (or data.frame) 'x' using apply In case of character entries the 'median' of sorted values will be returned

Usage

```
.summarizeCols(
  x,
  me = "median",
  nEq = FALSE,
  vectAs1row = TRUE,
  supl = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x data.frame matrix of data to be summarized by comlumn
 me (character, length=1) summarization method (eg 'min', 'max', 'mean', 'mean.trim', 'median', 'sd', 'CV', 'medianComplete' or 'meanComplete' etc, see [summarizeCols](#))
 nEq (logical) if TRUE, add additional column indicating the number of equal lines for choice (only with min or max)

<code>vectAs1row</code>	(logical) if TRUE will interpret non-matrix 'x' as matrix with 1 row (correct effect of automatic conversion when extracting 1 line)
<code>sup1</code>	(numeric) supplemental parameters for the various summarizing functions (currently used with 'me=mean.trim' to assign upper and lower trimming fraction, passed to)
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

vector with summary for each column (unless 'me=="summary"', in this case a matrix or list will be returned)

See Also

[summarizeCols](#), [table](#) [table](#)

Examples

```
m1 <- matrix(c(28,27,11,12,11,12), nrow=2, dimnames=list(1:2,c("y","x","ref")))
.summarizeCols(m1, me="median")
```

`.trimFromEnd` *Trim from end (Deprecated)*

Description

Deprecated Version - This function allows trimming/removing redundant text-fragments from end

Usage

```
.trimFromEnd(x, ..., callFrom = NULL, debug = FALSE, silent = TRUE)
```

Arguments

<code>x</code>	character vector to be treated
<code>...</code>	more vectors to be treated
<code>callFrom</code>	(character) allow easier tracking of messages produced
<code>debug</code>	(logical) display additional messages for debugging
<code>silent</code>	(logical) suppress messages

Value

This function returns a modified character vector

See Also

[trimRedundText](#); Inverse : Find/keep common text [keepCommonText](#); you may also look for related functions in package [stringr](#)

Examples

```
txt1 <- c("abcd_ccc", "bcd_ccc", "cde_ccc")
.trimRight(txt1)
```

.trimFromStart	<i>Trim from start (Deprecated)</i>
----------------	-------------------------------------

Description

Deprecated Version - This function allows trimming/removing redundant text-fragments from start

Usage

```
.trimFromStart(
  x,
  ...,
  minNchar = 1,
  silent = TRUE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

- x character vector to be treated
- ... more vectors to be treated
- minNchar (integer) minimum number of characters that must remain
- silent (logical) suppress messages
- debug (logical) display additional messages for debugging
- callFrom (character) allow easier tracking of messages produced

Value

This function returns a modified character vector

See Also

[trimRedundText](#); Inverse : Find/keep common text [keepCommonText](#); you may also look for related functions in package [stringr](#)

Examples

```
txt1 <- c("abcd_ccc", "bcd_ccc", "cde_ccc")
.trimLeft(txt1) # replacement
```

`.trimLeft`

Trim From Left Side

Description

This function allows trimming/removing redundant text-fragments from left side.

Usage

```
.trimLeft(x, minNchar = 1, silent = TRUE, debug = FALSE, callFrom = NULL)
```

Arguments

<code>x</code>	character vector to be treated
<code>minNchar</code>	(integer) minimum number of characters that must remain
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) display additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

This function returns a modified character vector

See Also

[trimRedundText](#); Inverse : Find/keep common text [keepCommonText](#); you may also look for related functions in package [stringr](#)

Examples

```
txt1 <- c("abcd_ccc", "bcd_ccc", "cde_ccc")
.trimLeft(txt1)
```

.trimRight *Trim From Right Side*

Description

This function allows trimming/removing redundant text-fragments from right side.

Usage

```
.trimRight(x, minNchar = 1, silent = TRUE, debug = FALSE, callFrom = NULL)
```

Arguments

x	character vector to be treated
minNchar	(integer) minimum number of characters that must remain
silent	(logical) suppress messages
debug	(logical) display additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a modified character vector

See Also

[trimRedundText](#); Inverse : Find/keep common text [keepCommonText](#); you may also look for related functions in package [stringr](#)

Examples

```
txt1 <- c("abcd_ccc", "bcd_ccc", "cde_ccc")  
.trimRight(txt1)
```

.uniqueWName *Check regression arguments*

Description

This function is an enhanced version of unique, names of elements are maintained

Usage

```
.uniqueWName(
  x,
  splitSameName = TRUE,
  silent = TRUE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	(numeric or character vector) main input
splitSameName	(logical)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

vector like input

See Also

[unique](#)

Examples

```
aa <- c(a=11, b=12,a=11,d=14, c=11)
.uniqueWName(aa)
.uniqueWName(aa[-1]) # value repeated but different name
```

.vector2Matr

Convert numeric vector to matrix

Description

Take (numeric) vector and return matrix, if 'colNa' given will be used as colname

Usage

```
.vector2Matr(x, colNa = NULL, rowsKeep = TRUE)
```

Arguments

x	(numeric or character) main input
colNa	(integer) design the comumn-name to be given
rowsKeep	(logical) is TRUE make matrix of 1 column, otherwise of 1 row

Value

matrix

See Also[matrix](#)**Examples**

```
.vector2Matr(c(3:6))
```

`addBeforeFileExtension`*Add Text Before File-Extension*

Description

This function helps changing character strings like file-names and allows adding the character vector 'add' (length 1) before the extension (defined by last '.') of the input string 'x'. Used for easily creating variants/additional filenames but keeping current extension.

Usage

```
addBeforeFileExtension(  
  x,  
  add,  
  sep = "_",  
  silent = FALSE,  
  callFrom = NULL,  
  debug = FALSE  
)
```

Arguments

x	main character vector of file-names
add	character vector to be added
sep	(character) separator between 'x' & 'add' (character, length 1)
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced
debug	(logical) additional messages for debugging

Details

Since this function replaces the deprecated `addBeforFileExtension` (to correct a typo in the name of the old version of the function).

Value

modified character vector

Examples

```
addBeforeFileExtension(c("abd.txt", "ghg.ijij.txt", "kjh"), "new")
```

addBeforFileExtension *Add Text Before File-Extension*

Description

This function helps changing character strings like file-names and allows adding the character vector 'add' (length 1) before the extension (defined by last '.') of the input string 'x'. Used for easily creating variants/additional filenames but keeping current extension.

Usage

```
addBeforFileExtension(  
  x,  
  add,  
  sep = "_",  
  silent = FALSE,  
  callFrom = NULL,  
  debug = FALSE  
)
```

Arguments

x	main character vector of file-names
add	character vector to be added
sep	(character) separator between 'x' & 'add' (character, length 1)
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced
debug	(logical) additional messages for debugging

Details

This function will get deprecated and is replaced by addBeforeFileExtension (to correct a typo in the name of this function).

Value

modified character vector

Examples

```
addBeforFileExtension(c("abd.txt", "ghg.ijij.txt", "kjh"), "new")
```

`adjBy2ptReg`*Adjust Values By Two-Point Regression*

Description

This function performs linear rescaling of numeric data based on specified limits (ie a specified window). Values are adjusted to fit within a target range defined by 'regrTo'.

Usage

```
adjBy2ptReg(  
  dat,  
  lims,  
  regrTo = c(0.1, 0.9),  
  refLines = NULL,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

<code>dat</code>	A numeric vector or matrix of values to adjust.
<code>lims</code>	A list of two numeric vectors, each of length 1 or 2, representing the lower and upper limits for rescaling. Example: <code>'lims = list(c(5, 9), c(60, 90))'</code> .
<code>regrTo</code>	A numeric vector of length 2 defining the target range for rescaling (default: <code>'c(0.1, 0.9)'</code>).
<code>refLines</code>	Optional numeric or character vector specifying reference lines (rows) in 'dat' to use for rescaling. If 'NULL', all rows are used.
<code>silent</code>	Logical. If 'TRUE', suppresses messages (default: 'FALSE').
<code>debug</code>	Logical. If 'TRUE', prints debugging messages (default: 'FALSE').
<code>callFrom</code>	Character string for tracking messages (default: 'NULL').

Details

Since this function shares significant overlap with [scaleXY](#) (which has more advanced options) it is rather suggested to use `_scaleXY()` instead. The function `_adjBy2ptReg()` will may be deprecated in the future.

Value

A numeric vector or matrix with adjusted values.

Examples

```
set.seed(2016); dat1 <- round(runif(50, 0, 100), 1)
adjBy2ptReg(dat1, lims = list(c(5, 9), c(60, 90)))
plot(dat1, adjBy2ptReg(dat1, lims=list(c(5,9), c(60,90))))
```

adjustUnitPrefix	<i>Adjust Value With Different Decimal Prefixes To Single Prefix Plus Unit</i>
------------------	--

Description

This function provides help converting values with with different unit-prefixes to a single prefix-unit type. This can be used to convert a vector of mixed prefixes like 'p' and 'n'. Any text to the right of the unit will be ignored.

Usage

```
adjustUnitPrefix(
  x,
  pref = c("z", "a", "f", "p", "n", "u", "m", "", "k", "M", "G"),
  unit = "sec",
  sep = c("_", ".", " ", "" ),
  minTrimNChar = 0,
  returnType = c("NAifInvalid", "allText"),
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	(character) vector containing digit uunit-prefix and unit terms
pref	(character) multiplicative unit-prefixes, assumes as increasing factors of 1000
unit	(character) unit name, the numeric part may be sepatated by one space-character
sep	(character) separator characters that may appear between integer numeric value and unit description
minTrimNChar	(integer) min number of text characters when trimming adjacent text on left and right of main numeric+prefix+unit
returnType	(character) set options for retuning results : 'NAifInvalid' .. return NA for invalid parts,'allText' .. return initial text if problem, 'trim'
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

The aim of this function is to allow adjusting a vector containing '100pMol' and '1nMol' to '100pMol' and '1000pMol' for better downstream analysis. Please note that the current version recognizes and converts only integer values; decimals or scientific writing won't be recognized properly. The resultant numeric vector expresses all values as lowest prefix unit level. In case of invalid entries NAs will be returned.

Please note that decimal/comma digits will not be recognized properly, since the function will consider (by default) the decimal sign as just another separator.

To avoid special characters (which may not work on all operating-systems) the letter 'u' is used for 'micro'.

Value

This function returns a character vector (same length as input) with adjusted unified decimal prefix and adjusted numeric content, the numeric content only is also given in the names of the output

See Also

[convToNum](#); [checkUnitPrefix](#); [trimRedundText](#)

Examples

```
adjustUnitPrefix(c("2.psec abc", "20 fsec etc"), unit="sec")

x1 <- c("50_amol", "5_fmol", "250_amol", "100_amol", NA, "500_amol", "500_amol", "1_fmol")
adjustUnitPrefix(x1, unit="mol")

x2 <- c("abCc 500_nmol ABC", "abEe5_umol", "", "abFF_100_nmol_G", "abGg 2_mol", "abH.1 mmol")
rbind( adjustUnitPrefix(x2, unit="mol", returnType="allText") ,
       adjustUnitPrefix(x2, unit="mol", returnType="trim"),
       adjustUnitPrefix(x2, unit="mol", returnType=""))
```

 appendNR

Append vectors or lists, without duplicating common elements

Description

This function allows combining two vectors or lists without duplicating common content (defined by name of list-elements).

Usage

```
appendNR(
  x,
  y,
  rmDuplicate = TRUE,
  silent = FALSE,
```

```

    debug = FALSE,
    callFrom = NULL
  )

```

Arguments

x	(vector or list) must have names to allow checking for duplicate names in y
y	(vector or list) must have names to allow checking for duplicate names in x
rmDuplicate	(logical) avoid duplicating list-elements present in both x and y (based on names of list-elements)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of message(s) produced

Details

When setting the argument `rmDuplicate=FALSE` the function will behave like `append`.

Value

If both x and y are vectors, the output will be a vector, otherwise it will be a list

See Also

[append](#); [lrbind](#)

Examples

```

li1 <- list(a=1, b=2, c=3)
li2 <- list(A=11, B=12, c=3)
appendNR(li1, li2)
append(li1, li2)

```

arrayCV

CV of array

Description

arrayCV gets CVs for replicates in 2 or 3 dim array and returns CVs as matrix. This function may be used to calculate CVs from replicate microtiter plates (eg 8x12) where replicates are typically done as multiple plates, ie initial matrixes that are the organized into arrays.

Usage

```
arrayCV(arr, byDim = 3, silent = TRUE, callFrom = NULL)
```

Arguments

arr	(3-dim) array of numeric data like where replicates are along one dimension of the array
byDim	(integer) over which dimension repliates are found
silent	(logical) suppres messages
callFrom	(character) allow easier tracking of message produced

Value

matrix of CV values

See Also

[rowCVs](#), [rowGrpCV](#), [replPlateCV](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200) +rep(1:10,20)), ncol=10)
head(arrayCV(dat1,byDim=2))
```

asSepList

Organize Data as Separate List-Entries

Description

asSepList allows reorganizing most types of input into a list with separate numeric vectors. For example, matrixes or data.frames will be split into separate columns (differnt to [partUnlist](#) which maintains the original structure). This function also works with lists of lists. This function may be helpful for reorganizing data for plots.

Usage

```
asSepList(  
  y,  
  minLen = 4,  
  asNumeric = TRUE,  
  exclElem = NULL,  
  sep = "_",  
  fillNames = TRUE,  
  silent = FALSE,  
  callFrom = NULL,  
  debug = FALSE  
)
```

Arguments

y	list to be separated/split in vectors
minLen	(integer) min length (or number of rows), as add'l element to eliminate arguments given without names when asSepList is called in vioplot2
asNumeric	(logical) to transform all list-elements in simple numeric vectors (won't work if some entries are character)
exclElem	(character) optional names to exclude if any (lazy matching) matches (to exclude other arguments be misinterpreted as data)
sep	(character) separator when combining name of list-element to colames
fillNames	(logical) add names for list-elements/ series when not given
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced
debug	(logical) display additional messages for debugging

Value

This function returns a list, partially unlisted to vectors

See Also

[partUnlist](#), [unlist](#)

Examples

```
bb <- list(fa=gl(2,2), c=31:33, L2=matrix(21:28,nc=2),
  li=list(li1=11:14, li2=data.frame(41:44)))
asSepList(bb)
## multi data-frame examples
ca <- data.frame(a=11:15, b=21:25, c=31:35)
cb <- data.frame(a=51:53, b=61:63)
cc <- list(gl(3,2), ca, cb, 91:94, short=81:82, letters[1:5])
asSepList(cc)
cd <- list(e1=gl(3,2), e2=ca, e3=cb, e4=91:94, short=81:82, e6=letters[1:5])
asSepList(cd)
```

blockNormalize

Normalize Blockwise Two Or Three Datasets

Description

This function provides for normalizing 2 entire data-sets against each other while preserving each set's characteristics. Several methods are possible: normalize blocks to common range, blocks to common median, to common distribution per block (quantile-normalization)

Usage

```

blockNormalize(
  x,
  y,
  z = NULL,
  method = "quantile.block",
  range = c(0, 1),
  q = c(0, 1),
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)

```

Arguments

x	(matrix or data.frame) first data-set (must be at least 2 columns and 3 lines)
y	(matrix or data.frame) second data-set (must be at least 2 columns and 3 lines)
z	(NULL or matrix or data.frame) optional 3rd data-set (if not NULL at least 2 columns and 3 lines)
method	Character string or function specifying the normalization method: - "quantile.block" (default): Aligns the distributions of all input datasets to a common target distribution (the mean of sorted values at each quantile). After normalization, 'sort(x)', 'sort(y)', and 'sort(z)' (if provided) are identical . This is useful for making datasets directly comparable. - "rescale": Rescales each dataset independently to the range specified by 'range'. Preserves the shape of each distribution but standardizes the scale (e.g., to '[0, 1]'). - "median": This procedure works in a proportional matter. It centers each dataset by dividing by its group median and multiplying by the overall median. This removes location differences while preserving spread. - "logMedian": This procedure is adopted for log-data. It centers each dataset by subtracting its group-median and adding the overall median. Removes location differences while preserving spread. - "none": No normalization
range	(numeric vector, length=2) vector specifying the target values to be used in case method="rescale" for rescaling; Default values 0 and 1 point to the min and max values to be adjusted to the value specified in this argument, ie the 'range'. When argument method="q" is other than 0 and 1, the respective quantiles will get adjusted to the values of this argument, other data will be treated in a linear fashion.
q	(numeric vector, length=2) vector specifying the quantiles to be used in case method="rescale" for rescaling; Default values 0 and 1 point to the min and max values to be adjusted to the value specified in this argument
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

Main methods for choice :

- `quantile.block`: This method runs a quantile-normalization on each block (but NOT on each column). Thus, all datasets will get the same (overall) distributions.
- `rescale`: Apply a linear transformation to each dataset to fit within given 'range'.
- `median`: Normalize each block to get the same overall median (individual columns may deviate, the original order is preserved).
- `logMedian`: This procedure is an median normalization adopted to log-data. Instead of dividing and multiplying per-group medians will be subtracted and the target median will be added.
- `none`: Besides, it is also possible to not do any normalization, the output will be identical to the input

NA Handling: For all approaches NAs will get ignored. With `method='quantile.block'` all precise positions where there is an NA in any of the data x, y or z will be ignored to maintain equal numbers of data. This is due to the fact that regular quantile-normalization requires equal numbers of data per column (here one dataset is treated like a column in regular normalization). This means that the dataset with the highest number of NAs will indirectly has the capacity to mask valid data in other data-sets.

Value

This function returns a list of the normalized sets for x and y (and z if given)

See Also

[normalizeThis](#)

[normalizeThis](#) for normalizing all columns of single data-set, [quantile](#), [scale](#) for standard scaling

Examples

```
## Basic usage with vectors
x <- c(1, 5, 3, 7, 2)
y <- c(10, 20, 30, 40, 50)
## Align distributions (default: x and y will have identical distributions)
norm1 <- blockNormalize(x, y)
table(sort(norm1$x) == sort(norm1$y)) # all TRUE with 'quantile.block'

## matrix-example (like with omics-data)
set.seed(2026); mat1 <- matrix(rnorm(70), nrow=10) *5 # 10 lines x 10 samples
set.seed(2025); mat2 <- matrix(rnorm(70, mean=5), nrow=10)^2 -15
mat2[which(mat2 < 1.8)] <- mat2[which(mat2 < 1.8)] + 32
norm2 <- blockNormalize(mat1, mat2, method="rescale", range=c(0.1, 10))
sapply(norm2, range)
norm3 <- blockNormalize(mat1, mat2, method="median")
sapply(norm3, quantile, c(0.25,0.5,0.75), na.rm=TRUE)
norm4 <- blockNormalize(mat1, mat2, method="quantile.block")
sapply(norm4, quantile, c(0.25,0.5,0.75), na.rm=TRUE)
```

```

## the resulting distribution
layout(matrix(1:4, ncol=2))
boxplot(cbind(mat1, NA, mat2), main="initial", las=1)
boxplot(cbind(norm2$x, NA, norm2$y), main="rescale block", las=1)
boxplot(cbind(norm3$x, NA, norm3$y), main="median block", las=1)
boxplot(cbind(norm4$x, NA, norm4$y), main="quantile.block", las=1)

## the overall distribution of blocks
layout(matrix(1:4, ncol=2))
boxplot(cbind(mat1=as.numeric(mat1), mat2=as.numeric(mat2)), main="initial (overall)", las=1)
boxplot(cbind(mat1=as.numeric(norm2$x), mat2=as.numeric(norm2$y)),
  main="rescale block norm (overall)", las=1)
boxplot(cbind(mat1=as.numeric(norm3$x), mat2=as.numeric(norm3$y)),
  main="median block norm (overall)", las=1)
boxplot(cbind(mat1=as.numeric(norm4$x), mat2=as.numeric(norm4$y)),
  main="quantile.block norm (overall)", las=1)

```

buildTree

Connect edges to from tree and extract all possible branches

Description

It is assumed that multiple fragments from a common ancestor may be characterized by their start- and end-sites by integer values. For example, if 'abcdefg' is the ancestor, the fragments 'bcd' (from position 2 to 4) and 'efg' may then be assembled. To do so, all fragments must be presented as matrix specifying all start- and end-sites (and fragment-names). buildTree searches contiguous fragments from columns 'posCo' (start/end) from 'disDat' to build tree & extract path information starting with line 'startFr'. Made for telling if dissociated fragments contribute to long assemblies. This function uses various functions of package [data.tree](#) which must be installed, too.

Usage

```

buildTree(
  disDat,
  startFr = NULL,
  posCo = c("beg", "end"),
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)

```

Arguments

disDat	(matrix or data.frame) integer values with 1st column, ie start site of fragment, 2nd column as end of fragments, rownames as unique IDs (node-names)
startFr	(integer) index for 1st node (typically =1 if 'disDat' sorted by "beg"), should point to a terminal node for consecutive growing of branches

posCo	(character) colnames specifying the begin & start sites in 'disDat', if NULL 1st & 2nd col will be used
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a list with \$paths (branches as matrix with columns 'sumLen' & 'n'), \$usedNodes (character vector of all names used to build tree) and \$tree (object from data.tree)

See Also

package [data.tree](#) original function used [Node](#); in this package : for exploiting edge/tree related issues [simpleFragFig](#), [countSameStartEnd](#) and [contribToContigPerFrag](#),

Examples

```
frag2 <- cbind(beg=c(2,3,7,13,13,15,7,9,7,3,7,5,7,3),end=c(6,12,8,18,20,20,19,12,12,4,12,7,12,4))
rownames(frag2) <- c("A","E","B","C","D","F","H","G","I","J","K","L","M","N")
buildTree(frag2)
countSameStartEnd(frag2)
```

cbindNR	<i>cbind to non-redundant</i>
---------	-------------------------------

Description

cbindNR combines all matrixes given as arguments to non-redundant column names (by ADDING the number of 'duplicated' columns !). Thus, this function works similar to cbind, but allows combining multiple matrix-objects containing redundant column-names. Of course, all input-matrixes must have the same number of rows ! By default, the output gets sorted by column-names. Note, due to the use of '...' arguments must be given by their full argument-names, lazy evaluation might not recognize properly argument names.

Usage

```
cbindNR(
  ...,
  convertDFtoMatr = TRUE,
  sortOutput = TRUE,
  summarizeAs = "sum",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

... all matrixes to get combined in cbind way
 convertDFtoMatr (logical) decide if output should be converted to matrix
 sortOutput (logical) optional sorting by column-names
 summarizeAs (character) decide of combined values should get summed (default, 'sum') or averaged ('mean')
 silent (logical) suppress messages
 debug (logical) additional messages for debugging
 callFrom (character) allow easier tracking of messages produced

Value

This function returns a matrix or data.frame (as cbind would return)

See Also

[cbind](#), [nonAmbiguousNum](#), [firstOfRepLines](#)

Examples

```
ma1 <- matrix(1:6, ncol=3, dimnames=list(1:2,LETTERS[3:1]))
ma2 <- matrix(11:16, ncol=3, dimnames=list(1:2,LETTERS[3:5]))
cbindNR(ma1, ma2)
cbindNR(ma1, ma2, summarizeAs="mean")
```

checkAvSd	<i>Check how multiple groups of data separate or overlap based on mean +/- sd</i>
-----------	---

Description

checkAvSd compares if/how neighbour groups separate/overlap via the 'engineering approach' (+/- 2 standard-deviations is similar to $\alpha=0.05$ t. test). This approach may be used as less elegant alternative to (multi-group) logistic regression. The function uses 'daAv' as matrix of means (rows are tested for up/down character/progression) which get compared with boundaries taken from daSd (for Sd values of each mean in 'daAv').

Usage

```
checkAvSd(
  daAv,
  daSd,
  nByGr = NULL,
  multSd = 2,
  codeConst = "const",
```

```

    extSearch = FALSE,
    outAsLogical = TRUE,
    silent = FALSE,
    callFrom = NULL
  )

```

Arguments

daAv	matrix or data.frame
daSd	matrix or data.frame
nByGr	optinal specifying number of Elements per group, allows rather using SEM (adopt to variable n of different groups)
multSd	(numeric) the factor specifyin how many sd values should be used as margin
codeConst	(character) which term/word to use when specifying 'constant'
extSearch	(logical) if TRUE, extend search to one group further (will call result 'nearUp' or 'nearDw')
outAsLogical	to switch between 2col-output (separate col for 'up' and 'down') or simple categorical vector ('const','okDw','okUp')
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of message(s) produced

Value

vector describing character as 'const' or 'okUp','okDw' (or if extSearch=TRUE 'nearUp','nearDw')

See Also

[rowGrpMeans](#)

Examples

```

mat1 <- matrix(rep(11:24,3)[1:40],byrow=TRUE,ncol=8)
checkGrpOrderSEM(mat1,grp=g1(3,3)[-1])
checkAvSd(rowGrpMeans(mat1,g1(3,3)[-1]),rowGrpSds(mat1,g1(3,3)[-1]) )
# consider variable n :
checkAvSd(rowGrpMeans(mat1,g1(3,3)[-1]),rowGrpSds(mat1,g1(3,3)[-1]),nByGr=c(2,3,3))

```

checkFilePath	<i>Verify File-name If Existing (in specified path), If Has Proper Extension Or Select Files With Proper Extension From Given Path</i>
---------------	--

Description

This function allows tesing if a given file-name corresponds to an existing file (eg for reading lateron). Indications to the path and file-extensions may be given separately. If no files do match .gz compressed versions may be searched, too.

Usage

```

checkFilePath(
  fileName = NULL,
  path = "./",
  expectExt = "",
  mode = "compressedOption",
  compressedOption = NULL,
  strictExtension = NULL,
  stopIfNothing = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)

```

Arguments

fileName	(character) name of file to be tested; may also include an absolute or relative path; if NULL and path as well as expectExt will take 1st file in given path and proper extension
path	(character, length=1) optional separate entry for path of fileName
expectExt	(character) file extension (will not be considered if "")
mode	(character) further details if function should give error or warning if no files found integrates previous argument compressedOption to also look for look for .gz compressed files; strictExtension to decide if extension (expectExt) - if given - should be considered obligatory; stopIfNothing to stop with error if no files found
compressedOption	deprecated (logical) also look for .gz compressed files
strictExtension	deprecated (logical) decide if extension (expectExt) - if given - should be considered obligatory
stopIfNothing	deprecated, please use argument mode instead !
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

When the filename given by the user exists but it's file-extension is not matching expectExt the argument strictExtension allows to decide if the filename will still be returned or not.

When expectExt is given, initial search will look for perfect matches. However, if nothing is found and strictExtension=FALSE, a more relaxed and non-case-sensitive search will be performed.

Value

This function returns a character vector with verified file-name(s) (and path), returns NULL if nothing found - unless mode="stopIfNothing"

See Also[file.exists](#)**Examples**

```
(RhomeFi <- list.files(R.home()))
file.exists(file.path(R.home(), "bin"))
checkFilePath(c("xxx", "unins000"), R.home(), expectExt="dat")
```

`checkGrpOrder`*checkGrpOrder*

Description

`checkGrpOrder` tests each line of 'x' if expected order appears. Used for comparing groups of measures with expected profile (simply by matching expected order)

Usage

```
checkGrpOrder(
  x,
  rankExp = NULL,
  revRank = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<code>x</code>	matrix or data.frame
<code>rankExp</code>	(numeric) expected order for values in columns, default 'rankExp' =1:ncol(x)
<code>revRank</code>	(logical) if 'revRank'=TRUE, the initial ranks & reversed ranks will be tested
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) display additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

vector of logical values

See Also[checkGrpOrderSEM](#)

Examples

```
set.seed(2005); mat1 <- rbind(matrix(round(runif(40),1),nc=4), rep(1,4))
checkGrpOrder(mat1)
checkGrpOrder(mat1,c(1,4,3,2))
```

checkGrpOrderSEM	<i>Check Order Of Multiple Groups Including Non-Overlapping SEM-Margins</i>
------------------	---

Description

This function tests each line of 'x' if expected order of (replicate-) groups (defined in 'grp') appears intact, while including SEM of groups (replicates) via a proportional weight 'sdFact' as $(avGr1-gr1SEM) < (avGr1+gr1SEM) < (avGr2-gr2SEM) < (avGr2+gr2SEM)$.

Usage

```
checkGrpOrderSEM(
  x,
  grp,
  sdFact = 1,
  revRank = TRUE,
  shrink1sampSd = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	matrix or data.frame
grp	(factor) to organize replicate columns of (x)
sdFact	(numeric) is proportional factor how many times the SD will be used for defining lower & upper bounds of each group (ie sdFact=2 will mimick 95-percent confidence intervals)
revRank	(logical) (not implemented yet : optionally revert rank)
shrink1sampSd	(logical)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

This function may be used for comparing groups of measures with expected profiles (by matching expected order) to check if data in 'x' represent ascending groups ('grp'). Groups of size=1: The sd (and SEM) can't be estimated directly without any replicates, however, an estimate can be given by shrinking if 'shrink1sampSd'=TRUE under the hypothesis that the overall mechanisms determining the variances is constant across all samples.

Value

This function returns a list with \$rankExp as logical vector telling if group-ranges are ascending and \$lims with the sd-based group-limits

See Also

takes only 10

Examples

```
mat1 <- matrix(rep(11:24,3)[1:40], byrow=TRUE, ncol=8)
dimnames(mat1) <- list(letters[1:nrow(mat1)], paste(rep(LETTERS[3:1], each=3)[-1],
  rep(1:3, 3)[-1], sep="."))
checkGrpOrderSEM(mat1, grp=gl(3,3, labels=LETTERS[3:1])[-1])
```

checkSimValueInSer *Check for similar values in series*

Description

This function checks all values of 'x' for similar neighbour values within (relative) range of 'ppm' (ie parts per milion as measure of distance). By default values will be sorted internally, so if a given value of x has anywhere in x another value close enough, this will be detected. However, if sortX=FALSE only the values next to left and right will be considered. Return logical vector : FALSE for each entry of 'x' if value inside of ppm range to neighbour (of sorted values)

Usage

```
checkSimValueInSer(
  x,
  ppm = 5,
  sortX = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	numeric vector
ppm	(numeric, length=1) ppm-range for considering as similar
sortX	(logical) allows speeding up function when set to FALSE, for large data that are already sorted
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a logical vector : TRUE for each entry of x where at least one neighbour is inside of ppm distance/range

See Also

similar with more options [withinRefRange](#)

Examples

```
va1 <- c(4:7,7,7,7,7,8:10)+(1:11)/28600; checkSimValueInSer(va1)
data.frame(va=sort(va1),simil=checkSimValueInSer(va1))
```

checkStrictOrder	<i>Check for strict (ascencing or descending) order</i>
------------------	---

Description

checkStrictOrder tests lines of 'dat' (matrix of data.frame) for strict order (ascending, descending or constant), each col of data is tested relative to the col on its left.

Usage

```
checkStrictOrder(
  dat,
  invertCount = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	matrix or data.frame
invertCount	(logical) inverse counting (ie return 0 for all elements in order)
silent	(logical) suppress messages
debug	(logical) display additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

matrix with counts of up pairs, down pairs, equal-pairs, if 'invertCount'=TRUE all non-events are counted, ie a resulting 0 means that all columns are following the described characteristics (with variable col-numbers easier to count)

See Also

[order](#), [checkGrpOrder](#)

Examples

```
set.seed(2005); mat1 <- rbind(matrix(round(runif(40),1),nc=4), rep(1,4))
checkStrictOrder(mat1); mat1[which(checkStrictOrder(mat1)[,2]==0),]
```

checkUnitPrefix

Check For Common Unit-Name in Text

Description

This function aims to find a unit abbreviation or name occurring in all elements of a character-vector x. The unit name may be preceded by different decimal prefixes (eg 'k','M'), as defined by argument pref and separators (sep). The unit name will be returned (or first of multiple).

Usage

```
checkUnitPrefix(
  x,
  pref = c("a", "f", "p", "n", "u", "m", "", "k", "M", "G", "T", "P"),
  unit = c("m", "s", "sec", "Mol", "mol", "g", "K", "cd", "A", "W", "Watt", "V", "Volt"),
  sep = c("", " ", ";", ",", "-", "."),
  sep2 = "",
  stringentSearch = FALSE,
  na.rm = FALSE,
  protSpecChar = TRUE,
  inclPat = FALSE,
  callFrom = NULL,
  silent = FALSE,
  debug = FALSE
)
```

Arguments

x	(character) vector containing digit uunit-prefix and unit terms
pref	(character) multiplicative unit-prefixes, assumes as increasing factors of 1000
unit	(character) unit name, the numeric part may be sepatated by one space-character
sep	(character) separator character(s) that may appear between integer numeric value and unit-prefix
sep2	(character) separator character(s) after unit, set to sep2="" for ignoring characters following unit
stringentSearch	(logical) if TRUE only matches with same separators (sep, sep2) pass, otherwise different elements may contain different separators
na.rm	(logical) remove NA from input
protSpecChar	(logical) protect special characters and use as they are instead of regex-meaning
inclPat	(logical) return list including pattern of successful search
callFrom	(character) allow easier tracking of messages produced
silent	(logical) suppress messages
debug	(logical) additional messages for debugging

Details

Basically this function searches the pattern : digit + separator(sep) + prefix(pref) + unit + optional separator2(sep2) and returns the first unit-name/abbreviation found in all elements of x.

If if() In case of invalid entries or no common unit-names NULL will be returned.

Please note the 'u' is used for 'micro' since handeling of special characters may not be portal between different operating systems.

Value

This function returns a charcter vector (length=1) with the common unit name, if inclPat=TRUE it returns a list with \$unit and \$pattern

See Also

[convToNum](#); [adjustUnitPrefix](#)

Examples

```
x1 <- c("10fg WW", "xx 10fg 3pW", " 1pg 2.0W")
checkUnitPrefix(x1)
## different separators between digit and prefix:
x2 <- c("10fg WW", "xx 8_fg 3pW", " 1 pg-2.0W")
checkUnitPrefix(x2, stringentSearch=TRUE)
checkUnitPrefix(x2, stringentSearch=FALSE)

x4 <- c("CT_mixture_QY_50_amo1_CN_UPS1_CV_Standards_Research_Group",
      "CT_mixture_QY_5_fm01_CN_UPS1_CV_Standards_Research_Group")
```

checkVectLength	<i>Check length of vector</i>
-----------------	-------------------------------

Description

checkVectLength checks argument 'x' for expected length 'expeL' and return either message or error when expectation not met. May be used for parameter ('sanity') checking in other user front-end functions.

Usage

```
checkVectLength(  
  x,  
  expeL = 1,  
  stopOnProblem = FALSE,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

x	(numeric or character vector) input to check length
expeL	(numeric) expected length
stopOnProblem	(logical) continue on problems with message or stop (as error message)
silent	(logical) suppress messages
debug	(logical) display additional messages for debugging
callFrom	(character) allow easier tracking of message(s) produced

Value

This function returns NULL; it produces either error-message if length is not OK or optional message if length is OK

Examples

```
aa <- 1:5; checkVectLength(aa,exp=3)
```

chooseGroupNames	<i>Choose Column Most Likely For Sample-Names</i>
------------------	---

Description

This function looks at all columns of `mat` which columns may be likely choices for sample-names and derives then group-names after stripping terminal enumerators. Ideal sample-names should contain some replicates indicates as terminal enumerators.

Usage

```
chooseGroupNames(
  mat,
  useCoNa = NULL,
  method = "median",
  sep = c("_", "-", " ", ".", "=", ";"),
  rmTxt = NULL,
  asUnique = TRUE,
  partEnumerator = FALSE,
  fullReport = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<code>mat</code>	(matrix or data.frame) contains possible choices for sample-names
<code>useCoNa</code>	(character) optional custom choice for columns of <code>mat</code> to check; if <code>NULL</code> all columns will be used/checked
<code>method</code>	(character) decide how to choose number of groups as : min, low, med, high, max or mode Note arguments <code>asUnique</code> and <code>partEnumerator</code> influence which columns of <code>mat</code> will be evaluated/checked
<code>sep</code>	(character) separators considered when searching and removing common words
<code>rmTxt</code>	(character, length=1) optional removing of custom text (eg variable file-extensions); no obligation that <code>rmTxt</code> occurs in all instances
<code>asUnique</code>	(logical) requires all (potential) samples-names to be unique (ie no repeats) to be considered for group-names; also removes all candidate columns with all different names
<code>partEnumerator</code>	(logical) when <code>TRUE</code> allows some instances of (potential) sample-names without numerator: a1, a2, b (ie some wo enumerator)
<code>fullReport</code>	(logical) if <code>TRUE</code> returns list with <code>\$group</code> , <code>\$sampleNames</code> , <code>\$col</code> (index of column from <code>mat</code> and name of <code>c</code>)
<code>silent</code>	(logical) suppress messages if <code>TRUE</code>
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allows easier tracking of messages produced

Details

The basic idea is that the column containing (good) samples-names contains all different entries and that by stripping terminal enumerators one can understand the grouping of replicates. Note arguments `asUnique` and `partEnumerator` influence which columns of `mat` will be evaluated/checked

Value

This function returns a character vector with group-names (and sample-names as names of entries) or if `fullReport=TRUE` a list with `$group`, `$sampleNames`, `$col` (index of column from `mat` and name of column)

See Also

[rmSharedWords](#), [replicateStructure](#), [protectSpecChar](#)

Examples

```
mat <- cbind(a=letters[1:6], b=paste(rep(c("b","B"), each=3), 1:3), c=rep(1,6),
  d=gl(3,2), e=rep(c("e","E"),3), f=paste(rep(c("F","f","ff"), each=2), 1:2))
chooseGroupNames(mat, method="median")          # col 2 (b/B)
chooseGroupNames(mat, method="median", fullReport=TRUE)
chooseGroupNames(mat, method="min")            # col 2 (b/B)
chooseGroupNames(mat, method="max")           # col 6 (F/f/ff)
chooseGroupNames(mat, method="max", asUnique=FALSE) # col 1 (a..)
```

cleanReplicates

Replace Most Distant Values by NA

Description

This procedure aims to straighten (clean) the most extreme values of noisy replicates by identifying the most distant points (among a set of replicates). The input 'x' (matrix or data.frame) is supposed to come from multiple different measures taken in replicates (eg weight of different individuals as rows taken as multiple replicate measures in subsequent columns).

Usage

```
cleanReplicates(
  x,
  centrMeth = "median",
  nOutl = 2,
  retOffPos = FALSE,
  silent = FALSE,
  callFrom = NULL
)
```

Arguments

x	matrix (or data.frame)
centrMeth	(character) method to summarize (mean or median)
nOut1	(integer) determines how many points per line will be set to NA (with n=1 the worst row of replicates will be 'cleaned')
retOffPos	(logical) if TRUE, replace the most extreme outlier only
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced

Details

With the argument `nOut1` the user chooses the total number of most extreme values to replace by NA. how many of the most extreme replicates of the whole dataset will be replaced by NA, ie with `nOut1=1` only the single most extreme outlier will be replaced by NA. Outlier points are determined as point(s) with highest distance to (row) center (median and mean choice via argument 'centrMeth'). Thus function returns input data with "removed" points set to NA, or if `retOffPos=TRUE` the most extreme/outlier positions.

Value

This function returns a matrix of same dimensions as input `x`, data-points which were tagged/removed are set to NA, or if `retOffPos=TRUE` the most extreme/outlier positions

Examples

```
mat3 <- matrix(c(19,20,30, 18,19,28, 16,14,35),ncol=3)
cleanReplicates(mat3, nOut1=1)
```

closeMatchMatrix *Reorganize results of search for close (similar) values in matrix-view*

Description

`closeMatchMatrix` reorganizes/refines results from simple search of similar values of 2 sets of data by `findCloseMatch` (as list for one-to many relations) to more human friendly/readable matrix. This function returns results combining two sets of data which were initially compared (eg measured and theoretical values) as matrix-view using output of `findCloseMatch` and both original datasets. Additional information (covariables, annotation, ...) may be included as optional columns for either 'predMatr' or 'measMatr'. Note : It is important to run `findCloseMatch` with `sortMatch=FALSE` ! Note : Results presented based on view of 'predMatr', so if multiple 'measMatr' are at within tolerated distance, lines of 'measMatr' will be repeated; Note : Distances 'disToMeas' and 'ppmTo-Pred' are oriented : neg value if measured is lower than predicted (and pos values if higher than predicted); Note : Returns NULL when nothing within given limits of comparison;

Usage

```
closeMatchMatrix(
  closeMatch,
  predMatr,
  measMatr,
  prefMatch = c("^x", "^y"),
  colPred = 1,
  colMeas = 1,
  limitToBest = TRUE,
  asDataFrame = FALSE,
  origNa = TRUE,
  silent = FALSE,
  callFrom = NULL,
  debug = FALSE
)
```

Arguments

closeMatch	(list) output from findCloseMatch , ie list with hits for each 'x' (1st argument) : named vectors of value & x index in name; run with 'sortMatch'=F
predMatr	(vector or matrix) predicted values, the column 'colPred' indicates which column is used for matching from findCloseMatch ; if column 'id' present this column will be used as identifier for matching
measMatr	(vector or matrix) measured values, the column 'colMeas' indicates which column is used for matching from findCloseMatch ; if column 'id' present this column will be used as identifier for matching
prefMatch	(character, length=2) prefixes ('^x' and/or '^y') they may have been added by findCloseMatch
colPred	(integer or text, length=1) column of 'predMatr' with main values of comparison
colMeas	(integer or text, length=1) column of 'measMatr' with main measures of comparison
limitToBest	(integer) column of 'measMatr' with main measures of comparison
asDataFrame	(logical) convert results to data.frame if non-numeric matrix produced (may slightly slow down big results)
origNa	(logical) will try to use original names of objects 'predMatr', 'measMatr', if they are not multi-column and not conflicting other output-names (otherwise 'predMatr', 'measMatr' will appear)
silent	(logical) suppress messages
callFrom	(character) allows easier tracking of message(s) produced
debug	(logical) for bug-tracking: more/enhanced messages

Value

results as matrix-view based on initial results from [findCloseMatch](#), including optional columns of supplemental data for both sets of data for comparison. Returns NULL when nothing within limits

See Also

[findCloseMatch](#), [checkSimValueInSer](#)

Examples

```
aA <- c(11:17); bB <- c(12.001,13.999); cC <- c(16.2,8,9,12.5,15.9,13.5,15.7,14.1,5)
(cloMa <- findCloseMatch(aA,cC,com="diff",lim=0.5,sor=FALSE))
# all matches (of 2d arg) to/within limit for each of 1st arg ('x'); 'y' ..to 2nd arg = cC
(maAa <- closeMatchMatrix(cloMa,aA,cC,lim=TRUE)) #
(maAa <- closeMatchMatrix(cloMa,aA,cC,lim=FALSE,origN=TRUE)) #
(maAa <- closeMatchMatrix(cloMa,cbind(valA=81:87,aA),cbind(valC=91:99,cC),colM=2,
  colP=2,lim=FALSE))
(maAa <- closeMatchMatrix(cloMa,cbind(aA,valA=81:87),cC,lim=FALSE,deb=TRUE)) #
a2 <- aA; names(a2) <- letters[1:length(a2)]; c2 <- cC; names(c2) <- letters[10+1:length(c2)]
(cloM2 <- findCloseMatch(x=a2,y=c2,com="diff",lim=0.5,sor=FALSE))
(maA2 <- closeMatchMatrix(cloM2,predM=cbind(valA=81:87,a2),measM=cbind(valC=91:99,c2),
  colM=2,colP=2,lim=FALSE,asData=TRUE))
(maA2 <- closeMatchMatrix(cloM2,cbind(id=names(a2),valA=81:87,a2),cbind(id=names(c2),
  valC=91:99,c2),colM=3,colP=3,lim=FALSE,deb=FALSE))
```

 coinPermTest

Compare Means Of Two Vectors By Permutation Test

Description

Run coin-flipping like permutation tests (to compare difference of 2 means: 'x1' and 'x2') without any distribution-assumptions. This function uses the package `coin`, if not installed, the function will return NULL and give a warning.

Usage

```
coinPermTest(
  x1,
  x2,
  orient = "two.sided",
  nPerm = 5000,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x1	numeric vector (to be compared with vector 'x2')
x2	numeric vector (to be compared with vector 'x1')
orient	(character) may be "two.sided", "greater" or "less"
nPerm	(integer) number of permutations

silent (logical) suppress messages
 debug (logical) additional messages for debugging
 callFrom (character) allow easier tracking of messages produced

Value

This function returns an object of "MCp" class numeric output with p-values

See Also

oneway_test in [LocationTests](#)

Examples

```
coinPermTest(2, 3, nPerm=200)
```

colCVs

rowCVs

Description

This function returns CV for values in each column (using speed optimized standard deviation).
 Note : NaN values get replaced by NA.

Usage

```
colCVs(dat, autoconvert = NULL, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

dat (numeric) matrix
 autoconvert (NULL or character) allows converting simple vectors in matrix of 1 row (autoconvert="row")
 silent (logical) suppress messages
 debug (logical) additional messages for debugging
 callFrom (character) allows easier tracking of messages produced

Value

This function returns a (numeric) vector with CVs for each column of 'dat'

See Also

[rowSums](#), [rowCVs](#), [rowGrpCV](#), [colSds](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200) +rep(1:10,20)),ncol=10)
head(colCVs(dat1))
```

`colMedSds`*Standard Error Of Median For Each Column By Bootstrap*

Description

Determine standard error (sd) of median by bootstrapping for multiple sets of data (rows in input matrix 'dat'). Note: The package `boot` must be installed from CRAN.

Usage

```
colMedSds(dat, nBoot = 99, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

<code>dat</code>	(numeric) matrix
<code>nBoot</code>	(integer, length=1) number of iterations
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

This function returns a (numeric) vector with estimated standard errors

See Also

[boot](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200) + rep(1:10,20)), ncol=10)
colMedSds(dat1)
```

`colorAccording2`*Transform Numeric Values To Color-Gradient*

Description

This function helps making color-gradients for plotting a numerical variable. Note : RColorBrewer palettes were not integrated here/yet.

Usage

```
colorAccording2(
  x,
  gradTy = "rainbow",
  nStartOmit = NULL,
  nEndOmit = NULL,
  revCol = FALSE,
  alpha = 1,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	(character) color input
gradTy	(character) type of gradient may be 'rainbow', 'heat.colors', 'terrain.colors', 'topo.colors', 'cm.colors', 'hcl.colors', 'grey.colors', 'gray.colorsW' or 'logGray'
nStartOmit	(integer) omit n steps from beginning of gradient range
nEndOmit	(integer or "sep") omit n steps from end of gradient range, if nEndOmit="sep" 20 percent of initial grades will be removed to obtain 'separate' ie non-closing color-circles/gradients eg with rainbow
revCol	(logical) reverse order
alpha	(numeric) optional transparency value (1 for no transparency, 0 for complete opaqueness)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a character vector (of same length as x) with color encoding

See Also

[cut](#)

Examples

```
set.seed(2015); dat1 <- round(runif(15),2)
plot(1:15,dat1,pch=16,cex=2,col=colorAccording2(dat1))
plot(1:15,dat1,pch=16,cex=2,col=colorAccording2(dat1,nStart0=0,nEnd0=4,revCol=TRUE))
plot(1:9,pch=3)
points(1:9,1:9,col=transpGraySca(st=0,en=0.8,nSt=9,trans=0.3),cex=42,pch=16)
```

colSds	<i>sd for each column</i>
--------	---------------------------

Description

This function is speed optimized sd per column of a matrix or data.frame and treats each column as independent set of data for sd (equiv to `apply(dat, 2, sd)`). NAs are ignored from data. Speed improvements may be seen at more than 100 columns

Usage

```
colSds(dat, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

dat	matrix (or data.frame) with numeric values (may contain NAs which will be ignored)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

numeric vector of sd values

See Also

[sd](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200) + rep(1:10,20)), ncol=10)
colSds(dat1)
```

combinatIntTable	<i>Planing for making all multiplicative combinations</i>
------------------	---

Description

Provide all combinations for each of n elements of vector 'nMax' (positive integer, eg number of max multiplicative value). For example, imagine, we have 3 cities and the (maximum) voting participants per city. Results must be read vertically and allow to see all total possible compositions.

Usage

```
combinatIntTable(
  nMax,
  include0 = TRUE,
  asList = FALSE,
  callFrom = NULL,
  silent = TRUE
)
```

Arguments

nMax	(positive integer) could be max number of voting participants form different cities, eg Paris max 2 persons, Lyon max 1 person ...
include0	(logical) include 0 occurrences, ie provide al combinations starting from 0 or from 1 up to nMax
asList	(logical) return result as list or as array
callFrom	(character) allow easier tracking of messages produced
silent	(logical) suppress messages

Value

list or array (as 2- or 3 dim) with possible number of occurrences for each of the 3 elements in nMax. Read results vertical : out[[1]] or out[,1] .. (multiplicative) table for 1st element of nMax; out[,2] .. for 2nd

See Also

[combn](#)

Examples

```
combinatIntTable(c(1,1,1,2), include0=TRUE, asList=FALSE, silent=TRUE)
## Imagine we have 3 cities and the (maximum) voting participants per city :
nMa <- c(Paris=2, Lyon=1, Strasbourg=1)
combinatIntTable(nMa, include0=TRUE, asList=TRUE, silent=TRUE)
```

Description

The aim of this function is to choose a fixed number (nCombin) of list-elments from lst and count the number of common values/words. Furthermore, one can define levels to fine-tune the types of combinations to examine. In case multiple combinations for a given level are possible, some basic summary statistics are provided, too.

Usage

```
combineAsN(
  lst,
  lev = NULL,
  nCombin = 3,
  remDouble = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

lst	(list of character or integer vectors) main input
lev	(character) define groups of lst
nCombin	(integer) number of list-elements to combine from lst
remDouble	(logical) remove intra-duplicates (defaults to TRUE)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

Note of caution : With very long lists and/or high numbers of repeats of given levels, however, the computational effort increases very much (like it does when using `table`). Thus, when exploring all different combinations of large data-sets may easily result in queries consuming many resources (RAM and processing time) ! It is recommended to start testing with test smaller sub-groups.

The main idea of this function is to count frequency of terms when combining different drawings. For example, you ask students from different cities which are their preferred hobbies, they may have different preference depending on the city (defined by `lev`). Now, if you want to make groups of 3 students, possibly with one from each city (A ,B and C), you want to count (/estimate) the frequency of different combinations possible. Thus, using this function all combinations of the students from city A with the students from city B and C will be made when counting the number of common hobbies (by `nCombin` students). Then, all counting results will be summarized to the average count for the various categories (which hobbies were seen once, twice or 3 times...), `sem` (standard error of the mean) and `CI` (95

Of course, the number of potential combinations may quickly get very large. Using the argument `remDouble=TRUE` you can limit the search to either finding all students giving the same answer plus all student giving different answers. In this case, when a given level appears multiple times, all possible combinations using one of the respective entries will be be made with the other levels.

Value

This function returns an array with 3 dimensions : i) ii) the combinations of `nCombin` list-elements, iii) the number of counts (n), `sem` (standard error of the mean), `CI` (confidence interval) and `sd`

See Also

[table](#), [replicateStructure](#)

Examples

```
## all list-elements are considered equal
tm1 <- list(a1=LETTERS[1:17], a2=LETTERS[3:19], a3=LETTERS[6:20], a4=LETTERS[8:22])
combineAsN(tm1, lev=gl(1,4))[,1,]

## different levels/groups in list-elements
tm4 <- list(a1=LETTERS[1:15], a2=LETTERS[3:16], a3=LETTERS[6:17], a4=LETTERS[8:19],
  b1=LETTERS[5:19], b2=LETTERS[7:20], b3=LETTERS[11:24], b4=LETTERS[13:25], c1=LETTERS[17:26],
  d1=LETTERS[4:12], d2=LETTERS[5:11], d3=LETTERS[6:12], e1=LETTERS[7:10])
te4 <- combineAsN(tm4, nCombin=4, lev=substr(names(tm4),1,1))
str(te4)
te4[, ,1]
```

combineByEitherFactor Create factor-like column regrouping data regrouping simultaneously by two factors

Description

This function aims to address the situation when two somehow different groupings (of the same data) exist and need to be joined. It is not necessary that both alternative groupings use the same labels, neither. `combineByEitherFactor` adds new (last) column named 'grp' to input matrix representing the combined factor relative to 2 specified columns from input matrix `mat` (via 'refC1', 'refC2'). Optionally, the output may be sorted and a column giving `n` per factor-level may be added. The function treats selected columns of `mat` as pairwise combination of 2 elements (that may occur multiple times over all lines of `mat`) and sorts/organizes all instances of such combined elements (ie from both selected columns) as repeats of a given group, who's class number is given in output column 'grp', the (total) number of repeats may be displayed in column 'nGrp' (`nByGrp=TRUE`). If groups are overlapping (after re-ordering), an iterative process of max 3x2 passes will be launched after initial matching. Works on numeric as well as character input.

Usage

```
combineByEitherFactor(
  mat,
  refC1,
  refC2,
  nByGrp = FALSE,
  convergeMax = TRUE,
  callFrom = NULL,
  debug = FALSE,
  silent = FALSE
)
```

Arguments

mat	main input matrix
refC1	(integer) column-number of 'mat' to use as 1st set
refC2	(integer) column-number of 'mat' to use as 2nd set
nByGrp	(logical) add last col with n by group
convergeMax	(logical) if TRUE, run 2 add'l iterative steps to search convergence to stable result
callFrom	(character) allow easier tracking of message(s) produced
debug	(logical) display additional messages for debugging
silent	(logical) suppress messages

Value

This function returns a matrix containing both selected columns plus additional column(s) indicating group-number of the pair-wise combination (and optional the total n by group)

Examples

```
nn <- rep(c("a","e","b","c","d","g","f"),c(3,1,2,2,1,2,1))
qq <- rep(c("m","n","p","o","q"),c(2,1,1,4,4))
nq <- cbind(nn,qq)[c(4,2,9,11,6,10,7,3,5,1,12,8),]
combineByEitherFactor(nq,1,2,nBy=TRUE); combineByEitherFactor(nq,1,2,nBy=FALSE)
combineByEitherFactor(nq,1,2,conv=FALSE); combineByEitherFactor(nq,1,2,conv=TRUE)
##
mm <- rep(c("a","b","c","d","e"),c(3,4,2,3,1)); pp <- rep(c("m","n","o","p","q"),c(2,2,2,2,5))
combineByEitherFactor(cbind(mm,pp), 1, 2, con=FALSE, nBy=TRUE)
combineByEitherFactor(cbind(mm,pp), 1, 2, con=TRUE, nBy=TRUE)
```

combineOverlapInfo *Find And Combine Points Located Very Close In x/y Space*

Description

Search points in x,y space that are located very close and thus likely to overlap. In case of points close enough, various options for joining names (and shortening longer descriptions) are available.

Usage

```
combineOverlapInfo(
  dat,
  suplInfo = NULL,
  disThr = 0.01,
  addNsimil = TRUE,
  txtSepChar = ",",
  combSym = "+",
  maxOverl = 50,
```

```

    callFrom = NULL,
    debug = FALSE,
    silent = FALSE
  )

```

Arguments

<code>dat</code>	(matrix) matrix or data.frame with 2 cols (used ONLY 1st & 2nd column !), used as x & y coordinates
<code>suplInfo</code>	(NULL or character) when points are considered overlapping the text from 'suplInfo' will be reduced to fragment before 'txtSepChar' and combined (with others from overlapping text) using 'combSym', if NULL \$combInf will appear with row-numbers
<code>disThr</code>	(numeric) distance-threshold for considering as similar via searchDataPairs()
<code>addNsimil</code>	(logical) include number of fused points
<code>txtSepChar</code>	(character) for use with .retain1stPart(): where to cut (& keep 1st part) text from 'suplInfo' to return in out\$CombInf; only 1st element used !
<code>combSym</code>	(character) concatenation symbol (character, length=1) for points considered overlaying, see also 'suplInfo'
<code>maxOverl</code>	(integer) if NULL no limit or max limit of group/clu size (avoid condensing too many neighbour points to single cloud)
<code>callFrom</code>	(character) allow easier tracking of messages produced
<code>debug</code>	(logical) additional messages for debugging
<code>silent</code>	(logical) suppress messages

Value

This function returns a matrix with fused (condensed) information for cluster of overlapping points

Examples

```

set.seed(2013)
datT2 <- matrix(round(rnorm(200)+3,1),ncol=2,dimnames=list(paste("li",1:100,sep=""),
  letters[23:24]))
# (mimick) some short and longer names for each line
inf2 <- cbind(sh=paste(rep(letters[1:4],each=26),rep(letters,4),1:(26*4),sep=""),
  lo=paste(rep(LETTERS[1:4],each=26),rep(LETTERS,4),1:(26*4),",",rep(letters[sample.int(26)],4),
  rep(letters[sample.int(26)],4),sep=""))[1:100,]
head(datT2,n=10)
head(combineOverlapInfo(datT2,disThr=0.03),n=10)
head(combineOverlapInfo(datT2,suplI=inf2[,2],disThr=0.03),n=10)

```

combineRedBasedOnCol *Combine/reduce redundant lines based on specified column*

Description

This function works similar to unique, but it takes a matrix as input and considers one specified column to find unique instances. It identifies 'repeated' lines of the input-matrix (or data.frame) 'mat' based on (repeated) elements in/of column with name 'colNa' (or column-number). Redundant lines (ie repeated lines) will disappear in output. Eg used with extracted annotation where 1 gene has many lines for different GO annotation.

Usage

```
combineRedBasedOnCol(mat, colNa, sep = ",", silent = FALSE, callFrom = NULL)
```

Arguments

mat	input matrix or data.frame
colNa	character vector (length 1) mactng 1 column name (if mult only 1st will be used), in case of mult matches only 1st used
sep	(character) separator (default=",")
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced

Value

matrix containing the input matrix without lines considered repeated (unique-like)

See Also

[findRepeated](#), [firstOfRepLines](#), [organizeAsListOfRepl](#), [combineRedundLinesInList](#)

Examples

```
matr <- matrix(c(letters[1:6], "h", "h", "f", "e", LETTERS[1:5]), ncol=3,  
  dimnames=list(letters[11:15], c("xA", "xB", "xC")))  
combineRedBasedOnCol(matr, colN="xB")  
combineRedBasedOnCol(rbind(matr[1,], matr), colN="xB")
```

 combineRedundLinesInList

Combine Redundant Lines In List

Description

This function provides help for combining/summarizing lines of numeric data which may be summarized according to reference vector or matrix of annotation (part of the same input-list). The data and reference will be aligned and data corresponding to redundant information be combined/summarized.

Usage

```
combineRedundLinesInList(
  lst,
  refNa = "ref",
  datNa = "quant",
  refColNa = "GeneName",
  supRefColNa = NULL,
  summarizeType = "av",
  NA.rm = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

lst	(list) main input, containing matrix or data.frame of numeric data (see datNa and annotation (see refNa) and possibly unrelated stuff
refNa	(character) name of list-element containing annotation
datNa	(character) name(s) of list-element(s) containing numeric/quantitation data
refColNa	(character) in case the list-element to be used as reference is matrix or data.frame, the column to be used must be specified here
supRefColNa	(character) in case the lst\$refNa has no rownames, the content of column lst\$supRefColNa will be used instead
summarizeType	(character) the summarization method gets specified here; so far 'sum', 'av', 'med', 'first' and 'last' are implemented
NA.rm	(logical) pass to summarizing functions order to omit NAs, defaults to TRUE
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

All input data should be in a list, ie one or multipl matrix or data.frame for numeric data (see argument datNa), as well as the reference (see argument refNa). The refergence may be a named character vecor or a matrix for which the column to be used should be specified using the argument refColNa. In case the annotation is a matrix, the rownames will be used as unique/independent identifiyers to adjust potentially different order of numeric data and annotation. In absence of row-names, an additional column supRefColNa of the annotation may be designed for adjusting the order of annotation and numeric data.

The numeric list may contain multiple matrixes or data.frames which will all be summarized by the same procedure as long as they have the same initial dimensions and are specified by refNa.

Please note that all other list elements from input not specified by refNa (or datNa) will be maintained in the output just as they are.

Value

This function returns a list of same length as input

See Also

[findRepeated](#), [firstOfRepLines](#), [organizeAsListOfRepl](#), [combineRedBasedOnCol](#)

Examples

```
x1 <- list(quant=matrix(11:34, ncol=3, dimnames=list(letters[8:1], LETTERS[11:13])),
  annot=matrix(paste0(LETTERS[c(1:4,6,3:5)],LETTERS[c(1:4,6,3:5)]), ncol=1,
  dimnames=list(paste(letters[1:8]),"xx")) )
combineRedundLinesInList(lst=x1, refNa="annot", datNa="quant", refColNa="xx")
```

combineRedundLinesInListAcRef

Combine Redundant Lines In List, Deprecated

Description

The function combineRedundLinesInListAcRef() has been deprecated and replaced by combineRedundLinesInList() from the same package

Usage

```
combineRedundLinesInListAcRef(
  lst,
  listNa = c("ref", "quant"),
  refColNa = "xx",
  summarizeType = "av",
  NA.rm = TRUE,
  silent = FALSE,
  debug = FALSE,
```

```

    callFrom = NULL
  )

```

Arguments

<code>lst</code>	(list) main input
<code>listNa</code>	(character) names of list-elements containing quantitation data (1st position) and protein/line annotation (2nd position)
<code>refColNa</code>	(character) in case the list-element to be used as reference is <code>matrix</code> or <code>data.frame</code> , the column to be used must be specified here
<code>summarizeType</code>	(character) the summarization method gets specified here; so far 'sum', 'av', 'med', 'first' and 'last' are implemented
<code>NA.rm</code>	(logical) pass to summarizing functions order to omit NAs, defaults to TRUE
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

This function returns a list of same length as input

See Also

[combineRedundLinesInList](#)

Examples

```

x1 <- list(quant=matrix(11:34, ncol=3, dimnames=list(letters[8:1], LETTERS[11:13])),
  annot=matrix(paste0(LETTERS[c(1:4,6,3:5)],LETTERS[c(1:4,6,3:5)]), ncol=1,
  dimnames=list(paste(letters[1:8],"xx"))) )
## please use combineRedundLinesInList()
combineRedundLinesInList(lst=x1, refNa="annot", datNa="quant", refColNa="xx")

```

combineReplFromListToMatr

Combine replicates from list to matrix

Description

Suppose multiple measures (like multiple channels) are taken for subjects and these measures are organized as groups in a list, like multiple parameters (= channels) or types of measurements (typically many parameters are recorded when screening compounds in microtiter plates). Within one parameter/channel all replicate-data from separate list-entries ('lst') will get combined according to names of list-elements. The function will trim any redundant text in names of list-elements, try to isolate separator (may vary among replicate-groups, but should be 1 character long). eg names "hct116 1.1.xlsx" & "hct116 1.2.xlsx" will be combined as replicates, "hct116 2.1.xlsx" will be considered as new group.

Usage

```
combineReplFromListToMatr(lst, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

lst (list) list of arrays (typically multi-parameter measures of micortiterplate data)
 silent (logical) suppress messages
 debug (logical) additional messages for debugging
 callFrom (character) allow easier tracking of messages produced

Value

This function returns a list of arrays now with same dimension of arrays (but shorter, since replicate-arrays were combined)

See Also

[extr1chan](#), [organizeAsListOfRepl](#)

Examples

```
lst2 <- list(aa_1x=matrix(1:12,nrow=4,byrow=TRUE),ab_2x=matrix(24:13,nrow=4,byrow=TRUE))
combineReplFromListToMatr(lst2)
```

combineSingleT

Get All Combinations With TRUE From Each Column

Description

This function addresses the case when multiple alternative ways exist to combine two elements. combineSingleT makes combinatory choices : if multiple TRUE in given column of 'mat' make all multiple selections with always one TRUE from each column The resultant output contains index for first and second input columns elements to be combined.

Usage

```
combineSingleT(mat, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

mat 2-column matrix of logical values
 silent (logical) suppress messages
 debug (logical) additional messages for debugging
 callFrom (character) allows easier tracking of messages produced

Value

This function returns a matrix with indexes of combinations of TRUE

Examples

```
## Example: First column indicates which boys want to dance and second column
## which girls want to dance. So if several boys want to dance each of the girls
## will have the chance to dance with each of them.
matr <- matrix(c(TRUE,FALSE,TRUE,FALSE,TRUE,FALSE),ncol=2)
combineSingleT(matr)
```

completeArrLst

Complete list of arrays for same dimensions

Description

This function aims to inspect repeating structures of data given as list of arrays and will try to complete arrays with fewer lines or columns (as this may appear eg with the very last set of high-throughput screening data if fewer measures remain in the last set). Thus, the dimensions of the arrays are compared and cases with fewer (lost) columns (eg fewer experimental replicates) will be adjusted/complete by adding column(s) of NA. Used eg when at reading microtiterplate data the last set is not complete.

Usage

```
completeArrLst(arrLst, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

arrLst	(list) list of arrays (typically 1st and 2nd dim for specific genes/objects, 3rd for different measures associated with)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of message(s) produced

Value

This function returns a list of arrays, now with same dimension of arrays

See Also

[organizeAsListOfRepl](#), [extr1chan](#)

Examples

```
arr1 <- array(1:24,dim=c(4,3,2),dimnames=list(c(LETTERS[1:4]),
  paste("col",1:3,sep=""),c("ch1","ch2")))
arr3 <- array(81:96,dim=c(4,2,2),dimnames=list(c(LETTERS[1:4]),
  paste("col",1:2,sep=""),c("ch1","ch2")))
arrL3 <- list(pl1=arr1,pl3=arr3)
completeArrLst(arrL3)
```

concatMatch

*Value Matching With Option For Concatenated Terms***Description**

This is a `_match()`-like function allowing to search among concatenated terms/IDs, additional options to remove text pattern like terminal lowercase extension are available. The function returns a named vector indicating the positions of (first) matches similar to [match](#).

Usage

```
concatMatch(
  x,
  table,
  sep = ",",
  sepPattern = NULL,
  globalPat = "digitExtension",
  nomatch = NA_integer_,
  incomparables = NULL,
  extensPat = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<code>x</code>	(vector) the values to be matched
<code>table</code>	(vector) the values to be matched against (ie reference)
<code>sep</code>	(character) separator character in case concatenation of entries is tested
<code>sepPattern</code>	(character or NULL) optional custom pattern for splitting concatenations of <code>x</code> and <code>table</code> (in case NULL) is not sufficient)
<code>globalPat</code>	(character) pattern for additional trimming of search-terms. If <code>globalPat="digitExtension"</code> all terminal digits will not be considered when matching
<code>nomatch</code>	(vector) similar to match the value to be returned in the case when no match is found
<code>incomparables</code>	(vector) similar to match , a vector of values that cannot be matched. Any value in <code>x</code> matching a value in this vector is assigned the <code>nomatch</code> value.

extensPat	(logical) similar to match the value to be returned in the case when no match is found
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

The main motivation to create this function was to be able to treat concatenated entries and to look if any of the concatenated values match to 'x'. This function offers additional options for trimming values before running the main comparison.

Of course, the concatenation strategy must be known and only a single concatenation separator (which may be multiple characters long) may be used for both `x` and `match`. Thus result will only indicate that at least one of the concatenated terms had a match, but not which one. Finally, both vectors `x` and `table` may contain concatenated terms. In this case this function will require much more computational resources due to the increased combinatorics when comparing larger vectors.

Please note, that in case of multiple to multiple matches, only the first hit gets reported.

The argument `globalPat="digitExtension"` allows eg reducing 'A1234-4' to 'A1234'.

Value

This function returns a character vector with verified path and file-name(s), returns NULL if nothing

See Also

[match](#) (for two simple vectors without concatenated terms), [grep](#)

Examples

```
tab1 <- c("AA", "BB-5", "CCab", "FF")
tab2 <- c("AA", "WW,Vde,BB-5,E", "CCab", "FF,Uef")
x1 <- c("ZZ", "YY", "AA", "BB-2", "DD", "CCdef", "Dxy") # modif of single ID (no concat)
concatMatch(x1, tab2)
x2 <- c("ZZ,Z", "YY,Y", "AA,Z,Y", "BB-2", "DD", "X,CCdef", "Dxy") # concatenated in 'x'
concatMatch(x2, tab2)
tab1 <- c("AA", "BB-5", "CCab", "FF") # no concatenated in 'table'
concatMatch(x2, tab1) # simple case of no concat anywhere
concatMatch(x1, tab1)
```

confInt

Confidence Interval To Given Alpha

Description

This little function returns the confidence interval associated to a given significance level `alpha` under the hypothesis of the Normal distribution is valid.

Usage

```
confInt(x, alpha = 0.05, distrib = "Normal", silent = FALSE, callFrom = NULL)
```

Arguments

x	(numeric) main input
alpha	(numeric) significance level, accepted type I error
distrib	(character) distribution, so far only Normal is implemented
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of message(s) produced

Value

This function returns the confidence interval to a given alpha under the hypothesis of the Normal distribution.

See Also

[TDist](#); [confint](#)

Examples

```
confInt(c(5,2:6))
```

contribToContigPerFrag

Characterize individual contribution of single edges in tree-structures

Description

This function helps investigating tree-like structures with the aim of indicating how much individual tree components contribute to compose long stretches. `contribToContigPerFrag` characterizes individual (isolated) contribution of single edges in tree-structures. Typically used to process/exploit summarized trees (as matrix) made by `buildTree` which makes use of the package `data.tree`. For example if A,B and C can be joined as well and B +D, this function will check if A+B+C is longer and if A contributes to the longest tree.

Usage

```
contribToContigPerFrag(joinMat, fullLength = NULL, nDig = 3)
```

Arguments

joinMat	(matrix) matrix with concatenated edges as rownames (separated by slashes), column sumLen for total length and column n for number of edges
fullLength	(integer) custom total length (useful if the concatenated edges do not cover 100 percent of the original precursor whose fragments are studied)
nDig	(integer) rounding: number of digits for 3rd column len.rat in output

Value

matrix of 3 columns: with length of longest tree-branches where given edge participates (column sumLen), the (total) number of edges therein (col n. frag) and a relative value (len.rat)

See Also

to build tree [buildTree](#)

Examples

```
path1 <- matrix(c(17,19,18,17, 4,4,2,3),ncol=2,
  dimnames=list(c("A/B/C/D", "A/B/G/D", "A/H", "A/H/I"),c("sumLen", "n")))
contribToContigPerFrag(path1)
```

conv01toColNa

Convert matrix of integer to matrix of x-times repeated column-names

Description

conv01toColNa transforms matrix of integers (eg 0 and 1) to repeated & concatenated text from argument colNa, the character string for 0 occurrences of argument zeroTex may be customized. Used eg when specifying (and concatenating) various counted elements (eg properties) along a vector like variable peptide modifications in proteomics.

Usage

```
conv01toColNa(mat, colNa = NULL, zeroTex = "", pasteCol = FALSE)
```

Arguments

mat	input matrix (with integer values)
colNa	alternative (column-)names to the ones from 'mat' (default colnames of 'mat')
zeroTex	text to display if 0 (default "")
pasteCol	(logical) allows to collapse all columns to single chain of characters in output

Value

character vector

Examples

```
(ma1 <- matrix(sample(0:3,40, repl=TRUE), ncol=4, dimnames=list(NULL, letters[11:14])))
conv01toColNa(ma1)
conv01toColNa(ma1, colNa=LETTERS[1:4], ze=".")
conv01toColNa(ma1, colNa=LETTERS[1:4], pasteCol=TRUE)
```

convColorToTransp *Assign new transparency to given colors*

Description

This function allows (re-)defining a new transparency. A color encoding vector will be transformed to the same color(s) but with new transparency (alpha).

Usage

```
convColorToTransp(color, alph = 1)
```

Arguments

color	(character) color input
alph	(numeric) transparency value (1 for no transparency, 0 for complete opacity), values <1 will be treated as percent-values

Value

character vector (of same length as input) with color encoding for new transparency

See Also

[rgb](#), [par](#)

Examples

```
col0 <- c("#998FCC", "#5AC3BA", "#CBD34E", "#FF7D73")
col1 <- convColorToTransp(col0, alph=0.7)
layout(1:2)
pie(rep(1, length(col0)), col=col0)
pie(rep(1, length(col1)), col=col1, main="new transparency")
```

convMatr2df

Convert matrix (eg with redundant) row-names to data.frame

Description

This function provides flexible converting of matrix to data.frame. For example repeated/redundant rownames are not allowed in data.frame(), thus the corresponding column-names have to be renamed using a counter-suffix. In case of non-redundant rownames, a new column 'addIniNa' will be introduced at beginning to document the initial (redundant) rownames, non-redundant rownames will be created. Finally, this functions converts the corrected matrix to data.frame and checks/converts columns for transforming character to numeric if possible. If the input is a data.frame containing factors, they will be converted to character before potential conversion. Note: for simpler version (only text to numeric) see from this package `.convertMatrToNum`.

Usage

```
convMatr2df(
  mat,
  addIniNa = TRUE,
  duplTxtSep = "_",
  silent = FALSE,
  callFrom = NULL
)
```

Arguments

mat	matrix (or data.frame) to be converted
addIniNa	(logical) if TRUE an additional column ('ID') with rownames will be added at beginning
duplTxtSep	(character) separator for enumerating replicated names
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of message(s) produced

Value

This functions returns a data.frame equivalent to the input matrix, an additional column named 'ID' will be added for initial rownames

See Also

[numeric](#), for simpler version (only text to numeric) see from this package `.convertMatrToNum`

Examples

```

dat1 <- matrix(1:10, ncol=2)
rownames(dat1) <- letters[c(1:3,2,5)]
## as.data.frame(dat1) ... would result in an error
convMatr2df(dat1)

df1 <- data.frame(a=as.character((1:3)/2), b=LETTERS[1:3], c=1:3)
str(convMatr2df(df1))

df2 <- df1; df2$b <- as.factor(df2$b)
str(convMatr2df(df2))

```

convPairwiseSetup *Check Comparison-Choice*

Description

This function aims to help getting organized with pairwise (statistical) testing since there are multiple ways of expressing how samples should be grouped for tests. For example this may be either as combined character strings (eg 'A-B') or as separate elements. This function takes most input-formats and returns multiple converted formats.

Usage

```

convPairwiseSetup(
  useComparison,
  grp,
  experSetup = NULL,
  sep = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)

```

Arguments

useComparison (numeric or character vector or matrix) the argument allowing to specify the pairwise comparisons may be character as result of combining two group-names (from argument *grp*) (eg 'A-B', beware, the separator may not appear inside group-names) or 2-column matrix of group-names (thus, without separator; names combined with separator may be shown as rownames) or 2-column matrix of indexes to sorted group-names; default setting of `useComparison='all'` will select all possible pairwise combinations

grp (character or factor) vector defining groups of replicates for additional checking (may also be just the levels of *grp*)

experSetup (list) optional experimental setup (list with `$ind`, `$pwGrpIndex`, `$sep` and `$pwGrpNa` as obtained using `getPairwiseSetup`)

sep	(character) optional custom separator to use for splitting useComparison
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Details

This function returns a list with \$pwGrpNa (matrix with separated elements), \$pwIndex (matrix with separated indexes), \$grpNa (levels of grp, ie sorted), \$sep (character vecor of separator found/used or suggested), \$concat (pairwise concatenated names, eg 'A-B')

Value

This function returns a list with \$data, \$nNA, \$randParam, \$NAneigLst, \$seed, \$filt, and \$annot

See Also

[presenceFilt](#), [getPWseparator](#), [indexGroupsFromPW](#), [getPairwiseSetup](#), [strsplit](#)

Examples

```
convPairwiseSetup(c("B-C", "D-A"), LETTERS[1:4])
convPairwiseSetup(c("B", "C"), LETTERS[1:3])
convPairwiseSetup("all", LETTERS[1:3])
convPairwiseSetup(2:3, LETTERS[1:3])
convPairwiseSetup(2:3, LETTERS[1:3], sep="__")
convPairwiseSetup(matrix(c("B", "D", "C", "A"), ncol=2), LETTERS[1:4])
```

convToNum

Convert Vector To Numeric

Description

This function checks if input vector/character string contains numbers (with or without comma) and attempts converting to numeric. This functions was designed for extracting the numeric part of character-vectors (or matrix) containing both numbers and character-elements. Depending on the parameters convert and remove text-entries can be converted to NA (in resulting numeric objects) or removed (the number of elements/lines gets reduced, in consequence). Note: if 'x' is a matrix, its matrix-dimensions & -names will be preserved. Note: so far Inf and -Inf do not get recognized as numeric.

Usage

```
convToNum(
  x,
  autoConv = TRUE,
  spaceRemove = TRUE,
  convert = c(NA, "sparseChar"),
  remove = NULL,
  euroStyle = TRUE,
  sciIncl = TRUE,
  callFrom = NULL,
  silent = TRUE,
  debug = FALSE
)
```

Arguments

x	vector to be converted
autoConv	(logical) simple automatic conversion based on function <code>as.numeric</code> ; if TRUE all other arguments except <code>spaceRemove</code> will not be considered
spaceRemove	(logical) to remove all heading and trailing (white) space (until first non-space character)
convert	(character) define which type of non-conform entries to convert to NAs. Note, if <code>remove</code> is selected to eliminate character-entries they cannot be converted any more. Use <code>'allChar'</code> for all character-entries; <code>'sparseChar'</code> sparse (ie rare) character entries; NA for converting <code>'Na'</code> or <code>'na'</code> to NA; if <code>'none'</code> or NULL no conversions at all.
remove	(character) define which type of non-conform entries to remove, removed items cannot be converted to NA any more. Use <code>'allChar'</code> for removing all character entries; NA for removing all instances of NA (except those created by converting text); all elements will be kept if <code>'none'</code> or NULL.
euroStyle	(logical) if TRUE will convert all <code>'.'</code> (eg used as European decimal-separator) to <code>'.'</code> (as internally used by R as decimal-separator), thus allowing converting the European decimal format.
sciIncl	(logical) include recognizing scientific notation (eg <code>2e-4</code>)
callFrom	(character) allow easier tracking of messages produced
silent	(logical) suppress messages
debug	(logical) additional messages for debugging

Details

This function may be used in two modes, depending if argument `autoConv` is TRUE or FALSE. The first option allows accessing an automatic mode based on `as.numeric`, while the second option investigates all characters if they may belong to numeric expressions and allows removing specific text-elements.

Value

This function returns a numeric vector (or matrix (if 'x' is matrix))

See Also

[numeric](#) and `as.numeric` (on same help-page)

Examples

```
x1 <- c("+4", " + 5", "6", "bb", "Na", "-7")
convToNum(x1)
convToNum(x1, autoConv=FALSE, convert=c("allChar"))
convToNum(x1, autoConv=FALSE)      # too many non-numeric instances for 'sparseChar'

x2 <- c("+4", " + 5", "6", "-7", " - 8", "1e6", "+ 2.3e4", "-3E4", "- 4E5")
convToNum(x2)
convToNum(x2, autoConv=FALSE, convert=NA, remove=c("allChar", NA))
convToNum(x2, autoConv=FALSE, convert=NA, remove=c("allChar", NA), sciIncl=FALSE)
```

coordOfFilt	<i>get coordinates of values/points in matrix according to filtering condition</i>
-------------	--

Description

Get coordinates of values/points in matrix according to filtering condition

Usage

```
coordOfFilt(mat, cond, sortByRows = FALSE, silent = FALSE, callFrom = NULL)
```

Arguments

mat	(matrix or data.frame) matrix or data.frame
cond	(logical or integer) condition/test to see which values of mat fulfill test, or integer of index passing
sortByRows	(logical) optional sorting of results by row-index
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of message(s) produced

Value

matrix columns 'row' and 'col'

See Also

[which](#)

Examples

```
set.seed(2021); ma1 <- matrix(sample.int(n=40,size=27,replace=TRUE), ncol=9)
## let's test which values are >37
which(ma1 >37)      # doesn't tell which row & col
coordOfFilt(ma1, ma1 >37)
```

correctToUnique	<i>Correct vector to unique</i>
-----------------	---------------------------------

Description

correctToUnique checks 'x' for unique entries, while maintaining the original length. If necessary a counter will added to non-unique entries.

Usage

```
correctToUnique(
  x,
  sep = "_",
  atEnd = TRUE,
  maxIter = 4,
  NAenum = TRUE,
  silent = FALSE,
  callFrom = NULL
)
```

Arguments

x	input character vector
sep	(character) separator used when counter
atEnd	(logical) decide location of placing the counter (at end or at beginning of initial text)
maxIter	(numeric) max number of iterations
NAenum	(logical) if TRUE all NAs will be enumerated (NA_1,NA_2,...)
silent	(logical) suppress messages
callFrom	(character) for better tracking of use of functions

Value

This function returns a character vector

See Also

[unique](#) will simply remove repeated elements, ie length of 'x' won't remain constant, [filtSizeUniq](#) is more complex and slower, [treatTxtDuplicatas](#)

Examples

```
correctToUnique(c("li0", "n", NA, NA, rep(c("li2", "li3"), 2), rep("n", 4)))
```

 correctWinPath

Correct Mixed Slash And Backslash In File-Path

Description

This function corrects paths character strings for mixed slash and backslash in file path. In Windows the function `tempdir()` will use double backslashes as separator while `file.path()` uses regular slashes. So when combining these two one might encounter a mix of slashes and double backslashes which may cause trouble, unless this is streightened out to a single separator used. When pointing to given files inside html-files, paths need to have a prefix, this can be added using the argument `asHtml`.

Usage

```
correctWinPath(
  x,
  asHtml = FALSE,
  anyPlatf = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<code>x</code>	(character) input path to test and correct
<code>asHtml</code>	(logical) option for use in html : add prefix "file:"
<code>anyPlatf</code>	(logical, length=1) if TRUE, checking will only be performed in Windows environment
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allows easier tracking of messages produced

Value

This function returns a character vector with corrected path

See Also

[tempfile](#), [file.path](#)

Examples

```
path1 <- 'D:\\temp\\Rtmp6X8\\working_dir\\RtmpKC\\example.txt'
(path1b <- correctWinPath(path1, anyPlatf=TRUE))
(path1h <- correctWinPath(path1, anyPlatf=TRUE, asHtml=TRUE))
```

countCloseToLimits *Count From Two Vectors Number Of Values Close Within Given Limits*

Description

This functions summarizes the search of similar (or identical) numeric values from 2 initial vectors, it evaluates the result from initial search run by findCloseMatch(), whose output is a less convenient list. countCloseToLimits checks furthermore how many results within additional (more stringent) distance-limits may be found and returns the number of distance values within the limits tested. Designed for checking if threshold used with findCloseMatch() may be set more stringent, eg when searching reasonable FDR limits ...

Usage

```
countCloseToLimits(
  closeMatch,
  limitIdent = 5,
  prefix = "lim_",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

closeMatch	(list) output from findCloseMatch(), ie list indicating which instances of 2 series of data have close matches
limitIdent	(numeric) max limit or panel of threshold values to test (if single value, in addition a panel with values below will be tested)
prefix	(character) prefix for names of output
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns an integer vector with counts for number of list-elements with at least one absolute value below threshold, names

See Also

[findCloseMatch](#)

Examples

```

set.seed(2019); aa <- sample(12:15,20, repl=TRUE) +round(runif(20),2)-0.5
bb <- 11:18
match1 <- findCloseMatch(aa,bb,com="diff",lim=0.65)
head(match1)
(tmp3 <- countCloseToLimits(match1,lim=c(0.5,0.35,0.2)))
(tmp4 <- countCloseToLimits(match1,lim=0.7))

```

countSameStartEnd *Count Same Start- And End- Sites Of Edges (Or Fragments)*

Description

Suppose a parent sequence/string 'ABCDE' gets cut in various fragments (eg 'ABC','AB' ...). countSameStartEnd counts how many (ie re-occurring) start- and end- sites of edges do occur in the input-data. The input is presented as matrix of/indicating start- and end-sites of edges. The function is used to characterize partially redundant edges and accumulation of cutting/breakage sites.

Usage

```

countSameStartEnd(
  frag,
  minFreq = 2,
  nDig = 4,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)

```

Arguments

frag	(matrix) 1st column beg start-sites, 2nd column end end-sites of edges, row-names to precise fragment identities are recommended
minFreq	(integer) min number of accumulated sites for taking into account (allows filtering with large datasets)
nDig	(integer) rounding: number of digits for columns beg.rat and end.rat in output
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced# @return This function returns a matrix of 6 columns: input (beg and end), beg.n, beg.rat, end.n, end.rat

See Also

to build initial tree [buildTree](#), [contribToContigPerFrag](#), [simpleFragFig](#)

Examples

```
frag1 <- cbind(beg=c(2,3,7,13,13,15,7,9,7, 3,3,5), end=c(6,12,8,18,20,20,19,12,12, 4,5,7))
rownames(frag1) <- letters[1:nrow(frag1)]
countSameStartEnd(frag1)
simpleFragFig(frag1)
```

cutArrayInCluLike	<i>Cut 3-dim array in list of matrixes (or arrays) similar to organizing into clusters</i>
-------------------	--

Description

cutArrayInCluLike cuts 'dat' (matrix,data.frame or 3-dim array) in list (of appended lines) according to 'cluOrg', which serves as instruction which line of 'dat' should be placed in which list-element (like sorting according to cluster-numbers).

Usage

```
cutArrayInCluLike(dat, cluOrg, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

dat	array (3 dim)
cluOrg	(factor) organization of lines to clusters
silent	(logical) suppress messages
debug	(logical) display additional messages for debugging
callFrom	(character) allow easier tracking of message(s) produced

Value

This function retruns a list of matrixes (or arrays)

Examples

```
mat1 <- matrix(1:30,nc=3,dimnames=list(letters[1:10],1:3))
cutArrayInCluLike(mat1,cluOrg=factor(c(2,rep(1:4,2),5)))
```

cutAtMultSites *Cut character-vector at multiple sites*

Description

This function cuts character vector after 'cutAt' (ie keep the search substing 'cutAt', different to strsplit). Used for theoretical enzymatic digestion (eg in proteomics)

Usage

```
cutAtMultSites(y, cutAt)
```

Arguments

y	character vector (better if of length=1, otherwise one won't know which fragment stems from which input)
cutAt	(character) search substing, ie 'cutting rule'

Value

modified (ie cut) character vector

See Also

[strsplit](#), [nFragments0](#), [nFragments](#)

Examples

```
tmp <- "MSVSRTMEDSCELDLVYVTERIIAVSFPSTANEENFRSNLREVAQMLKSKHGNYLLFNLSERRPDITKLHAKVLEFGWPDHLHTPALEKI"
cutAtMultSites(c(tmp,"ojioRij"),c("R","K"))
```

cutToNgrp *Cut numeric vector to n groups (ie convert to factor)*

Description

This function is a more elaborate version of [cut](#) for cutting a the content of a numeric vector 'x' into a given number of groups, taken from the length of 'lev'. Besides, this function provides the group borders/limits for convention use with legends.

Usage

```
cutToNgrp(
  x,
  lev,
  NAuse = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	numeric vector
lev	(character or numeric), the length of this argument tells the number of groups to be used for cutting
NAuse	(logical) include NAs as separate group
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a list with \$grouped telling which element of 'x' goes in which group and \$legTxt with group-borders for convenient use with legends

See Also

[cut](#)

Examples

```
set.seed(2019); dat <- runif(30) +(1:30)/2
cutToNgrp(dat,1:5)
plot(dat,col=(1:5)[as.numeric(cutToNgrp(dat,1:5)$grouped)])
```

diffCombin

Compute Matrix Of Differences For All Pairwise Combinations Of Numeric Vector

Description

diffCombin returns matrix of differences (eg resulting from substitution) for all pairwise combinations of numeric vector 'x'.

Usage

```
diffCombin(
  x,
  diagAsNA = FALSE,
  prefix = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	numeric vector to compute differences for all combinations
diagAsNA	(logical) return all self-self combinations as NA (otherwise 0)
prefix	(logical) if TRUE, dimnames of output will specify orientation (prefix='from.' and 'to.')
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a numeric matrix of all pairwise differences

See Also

[diff](#) for simple differences

Examples

```
diffCombin(c(10,11.1,13.3,16.6))
```

diffPPM

Difference in ppm between numeric values

Description

This is a `diff()`-like function to return difference in ppm between subsequent values. Result is oriented, ie neg ppm value means decrease (from higher to lower value). Note that if the absolute difference remains the same the difference in ppm will not remain same. Any difference to NA is returned as NA, thus a single NA will result in two NAs in output (unless NA is 1st or last).

Usage

```
diffPPM(dat, toPrev = FALSE, silent = FALSE, callFrom = NULL)
```

Arguments

dat (numeric) vector for calculating difference to preceding/following value in ppm
toPrev (logical) determine orientation
silent (logical) suppress messages
callFrom (character) allows easier tracking of messages produced

Value

This function returns a list with close matches of 'x' to given 'y', the numeric value depends on 'sortMatch' (if FALSE then always value of 'y' otherwise of longest of x&y)

See Also

[checkSimValueInSer](#) and (from this package) [.compareByDiff](#), [diff](#)

Examples

```
aa <- c(1000.01, 1000.02, 1000.05, 1000.08, 1000.09, 1000.08)
.compareByPPM(list(aa,aa), 30, TRUE) # tabular 'long' version
diffPPM(aa)
```

elimCloseCoord *Eliminate close (overlapping) points (in x & y space)*

Description

elimCloseCoord reduces number of rows in 'dat' by eliminating lines where x & y coordinates (columns of matrix 'dat' defined by 'useCol') are identical (overlay points) or very close. The stringency for 'close' values may be fine-tuned using nDig), this function uses internally [firstOfRepeated](#).

Usage

```
elimCloseCoord(
  dat,
  useCol = 1:2,
  elimIdentOnly = FALSE,
  refine = 2,
  nDig = 3,
  callFrom = NULL,
  silent = FALSE
)
```

Arguments

dat	matrix (or data.frame) with main numeric input
useCol	(numeric) index for numeric columns of 'dat' to use/consider
elimIdentOnly	(logical) if TRUE, eliminate real duplicated points only (ie identical values only)
refine	(numeric) allows increasing stringency even further (higher 'refine' .. more lines considered equal)
nDig	(integer) number of significant digits used for rounding, if two 'similar' values are identical after this rounding the second will be eliminated.
callFrom	(character) allows easier tracking of message(s) produced
silent	(logical) suppress messages

Value

resultant matrix/data.frame

See Also

[findCloseMatch](#), [firstOfRepeated](#)

Examples

```
da1 <- matrix(c(rep(0:4,5),0.01,1.1,2.04,3.07,4.5),nc=2); da1[,1] <- da1[,1]*99; head(da1)
elimCloseCoord(da1)
```

equLenNumber

Equal character-length number

Description

equLenNumber convert numeric entry 'x' to text, with all elements getting the same number of characters (ie by adding preceding or tailing 0s, if needed). So far, this function cannot handle scientific annotations.

Usage

```
equLenNumber(x, silent = FALSE, callFrom = NULL, debug = FALSE)
```

Arguments

x	(character) input vector
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced
debug	(logical) additional messages for debugging

Value

This function returns a character vector formatted as equal number of characters per value

See Also

[sprintf](#)

Examples

```
equLenNumber(c(12,-3,321))
equLenNumber(c(12,-3.3,321))
```

exclExtrValues	<i>Exclude Extreme Values (Based On Distance To Mean)</i>
----------------	---

Description

This function aims to identify extreme values (values most distant to mean, thus potential outliers), mark them as NA or directly exclude them (depending on 'showNAs'). Note that every set of non-identical values will have at least one most extreme value. Extreme values are part of many distributions, they are not necessarily true outliers.

Usage

```
exclExtrValues(
  dat,
  result = "val",
  CVlim = NULL,
  maxExcl = 1,
  showNA = FALSE,
  goodValues = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	numeric vector, main input
result	(character) may be 'val' for returning data without extreme values or 'pos' for returning position/index of extreme values
CVlim	(NULL or numeric) allows to retain extreme values only if a certain CV (for all 'dat') is exceeded (to avoid calling extreme values form homogenous data-sets)
maxExcl	(integer) max number of elments to explude
showNA	(logical) will display extrelme values as NA
goodValues	(logical) allows to display rather the good values instead of the extreme values

silent (logical) suppress messages
debug (logical) additional messages for debugging
callFrom (character) allow easier tracking of messages produced

Value

This function returns a numeric vector without extreme values or index-position of extreme values

See Also

[firstOfRepLines](#), [get1stOfRepeatedByCol](#) for treatment of matrix

Examples

```
x <- c(rnorm(30), -6, 20)
exclExtrValues(x)
```

exponNormalize *Normalize By Adjusting Exponent*

Description

This function normalizes 'dat' by optimizing exponent function (ie dat^{exp}) to fit best to 'ref' (default: average of each line of 'dat').

Usage

```
exponNormalize(  
  dat,  
  useExpon,  
  dynExp = TRUE,  
  nStep = 20,  
  startExp = 1,  
  simMeas = "cor",  
  refDat = NULL,  
  refGrp = NULL,  
  refLines = NULL,  
  rSquare = FALSE,  
  silent = FALSE,  
  callFrom = NULL,  
  debug = FALSE  
)
```

Arguments

dat	matrix or data.frame of numeric data to be normalized
useExpon	(numeric vector or matrix) exponent values to be tested
dynExp	(logical) require 'useExpon' as 2 values (matrix), will gradually increase exponent from 1st to 2nd; may be matrix or data.frame for dynamic, in this case 1st line for exp for lowest data, 2nd line for highest
nStep	(integer) number of exponent variations (steps) when testing range from-to
startExp	(numeric)
simMeas	(character) similarity metric to be used (so far only "cor"), if rSquare=TRUE, the r-squared will be returned
refDat	(matrix or data.frame) if null average of each line from 'dat' will be used as reference in similarity measure
refGrp	(factor) designing which col of 'ref' should be used with which col of 'dat' (length equal to number of cols in 'dat'). Note: 'refGrp' not yet coded optimally to extract numeric part of character vector, potential problems when all lines or cols of dat are NA
refLines	(NULL or integer) optional subset of lines to be considered (only) when determining normalization factors
rSquare	(logical) if TRUE, add r-squared
silent	(logical) suppress messages
callFrom	(character) allows easier tracking of messages produced
debug	(logical) additional messages for debugging

Value

This function returns a matrix of normalized data

See Also

more evolved than [normalizeThis](#) with argument set to 'exponent'

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),nc=10)
head(rowGrpCV(dat1,gr=gl(4,3,labels=LETTERS[1:4])[2:11]))
set.seed(2016); dat1 <- c(0.1,0.2,0.3,0.5)*rep(c(1,10),each=4)
dat1 <- matrix(round(c(sqrt(dat1),dat1^1.5,3*dat1+runif(length(dat1)))),2),nc=3)
dat2a <- exponNormalize(dat1[,1],useExpon=2,nSte=1,refD=dat1[,3])
layout(matrix(1:2,nc=2))
plot(dat1[,1],dat1[,3],type="b",main="init",ylab="ref")
plot(dat2a$datNor[,1],dat1[,3],type="b",main="norm",ylab="ref")
dat2b <- exponNormalize(dat1[,1],useExpon=c(1.7,2.3),nSte=5,refD=dat1[,3])
plot(dat1[,1],dat1[,3],type="b",main="init",ylab="ref")
plot(dat2b$datNor[,1],dat1[,3],type="b",main="norm",ylab="ref")

dat2c <- exponNormalize(dat1[, -3],useExpon=matrix(c(1.7,2.3,0.6,0.8),nc=2),nSte=5,refD=dat1[,3]);
```

```
plot(dat1[,1],dat1[,3],type="b",main="init",ylab="ref ")
plot(dat2c$datNor[,1],dat1[,3],type="b",main="norm 1",ylab="ref")
plot(dat1[,2],dat1[,3],type="b",main="init",ylab="ref")
plot(dat2c$datNor[,2],dat1[,3],type="b",main="norm 2",ylab="ref");
```

 extr1chan

Extract Just One Series, ie One Channel, Of List Of Arrays

Description

This function was designed for handling measurements stored as list of multiple arrays, like eg compound-screens using microtiter-plates where multiple parameters ('channels') were recorded for each well (element). The elements (eg compounds screened) are typically stored in the 1st dimension of the arrays, the replicated in the secon dimension and different measure types/parameters in the 3rd channel. In order to keep the structure of of individual microtiter-plates, typically each plate forms a separate array (of same dimensions) in a list. The this function allows extracting a single channel of the list of arrays (3rd dim of each array) and return row-appended matrix.

Usage

```
extr1chan(
  arrLst,
  cha,
  na.rm = TRUE,
  rowSep = "__",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

arrLst	(list) list of arrays (typically 1st and 2nd dim for specific genes/objects, 3rd for different measures associated with)
cha	(integer) channel number
na.rm	(logical) default =TRUE to remove NAs
rowSep	(character) separator for rows
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a list with just single channel extracted

See Also

[organizeAsListOfRepl](#)

Examples

```
arr1 <- array(1:24,dim=c(4,3,2),dimnames=list(c(LETTERS[1:4]),
  paste("col",1:3,sep=""),c("ch1","ch2")))
arr2 <- array(74:51,dim=c(4,3,2),dimnames=list(c(LETTERS[1:4]),
  paste("col",1:3,sep=""),c("ch1","ch2")))
arrL1 <- list(pl1=arr1,pl2=arr2)
extr1chan(arrL1,ch=2)
```

extractLast2numericParts

Extract Last Two Numeric Parts From Character Vector

Description

This function extracts last 2 (integer) numeric parts between punctuations out of character vector 'x'. Runs faster than `gregexpr`. Note: won't work correctly with decimals or exponential signs !! (such characters will be considered as punctuation, ie as separator)

Usage

```
extractLast2numericParts(x, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

x	main character input
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a (numeric) matrix with 2 columns (eg from initial concatenated coordinates)

See Also

`gregexpr` from [grep](#)

Examples

```
extractLast2numericParts(c("M01.1-4", "M001/2.5", "M_0001_03-16", "zyx", "012", "a1.b2.3-7,2"))
```

extrColsDeX *Flexible extraction of columns*

Description

This function provides flexible checking if a set of columns may be extracted from a matrix or data.frame 'x'. If argument `extrCol` is list of character vectors, this allows to search among given options, the first matching name for each vector will be identified.

Usage

```
extrColsDeX(x, extrCol, doExtractCols = FALSE, callFrom = NULL, silent = FALSE)
```

Arguments

<code>x</code>	(matrix or data.frame) main input (where data should be extracted from)
<code>extrCol</code>	(character, integer or list) columns to be extracted, may be column-names or column index; if is list each first-level element will be considered as options for one choice
<code>doExtractCols</code>	(logical) if default FALSE only the column indexes will be returned
<code>callFrom</code>	(character) allows easier tracking of message(s) produced
<code>silent</code>	(logical) suppress messages

Value

integer-vector (if `doExtractCols=FALSE` return depending on input matrix or data.frame)

See Also

[read.table](#), [filterList](#)

Examples

```
dFr <- data.frame(a=11:14, b=24:21, cc=LETTERS[1:4], dd=rep(c(TRUE,FALSE),2))
extrColsDeX(dFr,c("b","cc","notThere"))
extrColsDeX(dFr,c("b","cc","notThere"), doExtractCols=TRUE)
extrColsDeX(dFr, list(c("nn","b","a"), c("cc","a"),"notThere"))
```

extrNumericFromMatr *Extract numeric part of matrix or data.frame*

Description

This function extracts numeric part of matrix or data.frame, removing remaining non-numeric elements if trimToData is set to TRUE. Note, that cropping entire lines where a (single) text element appeared may quickly reduce the overall content of the input data.

Usage

```
extrNumericFromMatr(  
  dat,  
  trimToData = TRUE,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

dat	matrix (or data.frame) for extracting numeric parts
trimToData	(logical) default to remove (crop) lines and cols contributing to NA, non-numeric data is transformed to NA
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of message(s) produced

Value

This function returns a matrix of numeric data

Examples

```
mat <- matrix(c(letters[1:7],14:16,LETTERS[1:6]),nrow=4,dimnames=list(1:4,letters[1:4]))  
mat; extrNumericFromMatr(mat)  
mat <- matrix(c(letters[1:4],1,"e",12:19,LETTERS[1:6]),nr=5,dimnames=list(11:15,letters[1:4]))  
mat; extrNumericFromMatr(mat)
```

`extrSpcText`*Extract Specific Text*

Description

This function extracts/cuts text-fragments out of `txt` following specific anchors defined by arguments `cutFrom` and `cutTo`.

Usage

```
extrSpcText(  
  txt,  
  cutFrom = " GN=",  
  cutTo = " PE=",  
  missingAs = NA,  
  exclFromTag = TRUE,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

<code>txt</code>	character vector to be treated
<code>cutFrom</code>	(character) text where to start cutting
<code>cutTo</code>	(character) text where to stop cutting
<code>missingAs</code>	(character) specific content of output at line/location of 'exclLi'
<code>exclFromTag</code>	(logical) to exclude text given in 'cutFrom' from result
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Details

In case `cutFrom` is not found `missingAs` will be returned. In case `cutTo` is not found, text gets extracted with `chaMaxEl` characters.

Value

This function returns a modified character vector

See Also

[substr](#)

Examples

```
extrSpcText(c(" ghjg GN=thisText PE=001", " GN=_ PE=", NA, "abcd"))
extrSpcText(c("ABCDEF.3-6", "05g", "bc.4-5"), cutFr="\\. ", cutT="-")
```

 filt3dimArr

Filter three-dimensional array of numeric data

Description

Filtering of matrix or (3-dim) array x : filter column according to filtCrit (eg 'inf') and threshold filtVal

Usage

```
filt3dimArr(
  x,
  filtVal,
  filtTy = ">",
  filtCrit = NULL,
  displCrit = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	array (3-dim) of numeric data
filtVal	(numeric, length=1) for testing inferior/superor/equal condition
filtTy	(character, length=1) which type of testing to perform (may be 'eq', 'inf', 'infeq', 'sup', 'supeq', '>', '<', '>=', '<=', '==')
filtCrit	(character, length=1) which column-name consider when filtering filter with 'filtVal' and 'filtTy'
displCrit	(character) column-name(s) to display
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

and extract/display all col matching 'displCrit'.

Value

This function returns a list of filtered matrixes (by 3rd dim)

See Also

[filterList](#); [filterLiColDeList](#);

Examples

```
arr1 <- array(11:34, dim=c(4,3,2), dimnames=list(c(LETTERS[1:4]),
  paste("col",1:3,sep=""), c("ch1","ch2")))
filt3dimArr(arr1,displCrit=c("col1","col2"),filtCrit="col2",filtVal=7)
```

filterLiColDeList *Filter lines(rows) and/or columns from all suitable elements of list*

Description

Filter all elements of list (or S3-object) according to criteria designed to one selected reference-element of the list. All simple vectors, matrix, data.frames and 3-dimensional arrays will be checked if matching number of rows and/or columns to decide if they should be filtered the same way. If the reference element has same number of rows and columns simple (1-dimensional) vectors won't be filtered since it not clear if this should be done to lines or columns.

Usage

```
filterLiColDeList(
  lst,
  useLines,
  useCols = NULL,
  ref = 1,
  silent = FALSE,
  callFrom = NULL,
  debug = FALSE
)
```

Arguments

lst	(list or S3 object) main input
useLines	(integer, logical or character) vector to assign lines to keep when filtering along lines; set to NULL for no filtering; if 'allNA' all lines composed uniquely of NA values will be removed.
useCols	(integer, logical or character) vector for filtering columns; set to NULL for no filtering; if 'allNA' all columns uniquely NA values will be removed
ref	(integer) index for designing the element of 'lst' to take as reference for checking which other list-elements have suitable number of rows or columns
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced
debug	(logical) additional messages for debugging

Details

This function is used eg in package wrProteo to simultaneously filter raw and transformed data.

Value

This function returns the correct(ed) input (object of same class, of same length)

See Also

[moderTest2grp](#) for single comparisons, [lmFit](#)

Examples

```
lst1 <- list(m1=matrix(11:18,ncol=2), m2=matrix(21:30,ncol=2), indR=31:34,
            m3=matrix(c(21:23,NA,25:27,NA),ncol=2))
## here $m2 has more lines than $m1, and thus will be ignored when ref=1
filterLiColDeList(lst1, useLines=2:3)
filterLiColDeList(lst1, useLines="allNA", ref=4)
```

filterList

Filter for unique elements

Description

This function aims to apply a given filter-criterium, a matrix or vector of FALSE/TRUE which is typically combined with a second layer which filters for a min content of filer-passing values per line for the first/main criterium. Then all lines concerned will be removed. This will be done for all list-elements (of appropriate size) of the input-list (while maintaining the list-structure in the output) not matching the filtering criteria.

Usage

```
filterList(lst, filt, minLineRatio = 0.5, silent = FALSE, callFrom = NULL)
```

Arguments

lst	(list) main input, each vector, matrix or data.frame in this list will be filtered if its length or number of lines fits to filt
filt	(logical) vector of FALSE/TRUE to use for filtering. If this a matrix is given, the value of minLineRatio will be applied as threshod of min content of TRUE for each line of filt
minLineRatio	(numeric) in case filt is a matrix of FALSE/TRUE, this value will be used as threshold of min content of TRUE for each line of filt
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of message(s) produced

Value

filtered list

See Also

[correctToUnique](#), [unique](#), [duplicated](#), [extrColsDeX](#)

Examples

```
set.seed(2020); dat1 <- round(runif(80),2)
list1 <- list(m1=matrix(dat1[1:40],ncol=8), m2=matrix(dat1[41:80],ncol=8), other=letters[1:8])
rownames(list1$m1) <- rownames(list1$m2) <- paste0("line",1:5)
filterList(list1, list1$m1[,1] >0.4)
filterList(list1, list1$m1 >0.4)
```

filterNetw

Filter nodes & edges for extracting networks This function allows extracting and filtering network-data based on fixed threshold (limInt) and add sandwich-nodes (nodes inter-connecting initial nodes) out of node-based queries.

Description

Filter nodes & edges for extracting networks

This function allows extracting and filtering network-data based on fixed threshold (limInt) and add sandwich-nodes (nodes inter-connecting initial nodes) out of node-based queries.

Usage

```
filterNetw(
  lst,
  filtCol = 3,
  limInt = 5000,
  sandwLim = 5000,
  filterAsInf = TRUE,
  outFormat = "matrix",
  remOrphans = TRUE,
  remRevPairs = TRUE,
  elemNa = "genes",
  silent = FALSE,
  callFrom = NULL,
  debug = FALSE
)
```

Arguments

lst	(list, composed of multiple matrix or data.frames) main input (each list-element should have same number of columns)
filtCol	(integer, length=1) which column of lst should be used to filter using thresholds limInt and sandwLim
limInt	(numeric, length=1) filter main edge-scores according to filterAsInf
sandwLim	(numeric, length=1) filter sandwich connection edge-scores according to filterAsInf
filterAsInf	(logical) filter as 'inferior or equal' or 'superior or equal'
outFormat	(character) may be 'matrix' for tabular output, 'all' as list with matrix and list of node-names
remOrphans	(logical) remove networks consisting only of 2 connected edges
remRevPairs	(logical) remove duplicate edges due to reverse massping (eg A - B and B - A); NOTE : use only when edges don't have orientation !
elemNa	(character) used only for messages
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of message(s) produced
debug	(logical) display additional messages for debugging

Value

This function returns a matrix or data.frame

See Also

in [cbind](#)

Examples

```
lst2 <- list('121'=data.frame(ID=as.character(c(141,221,228,229,449)),11:15),
            '131'=data.frame(ID=as.character(c(228,331,332,333,339)),11:15),
            '141'=data.frame(ID=as.character(c(121,151,229,339,441,442,449)),c(11:17)),
            '151'=data.frame(ID=as.character(c(449,141,551,552)),11:14),
            '161'=data.frame(ID=as.character(171),11), '171'=data.frame(ID=as.character(161),11),
            '181'=data.frame(ID=as.character(881:882),11:12) )

lst2 <- list('121'=data.frame(ID=as.character(c(141,221,228,229,449)),11:15, 21:25),
            '131'=data.frame(ID=as.character(c(228,331,332,333,339)),11:15, 21:25),
            '141'=data.frame(ID=as.character(c(121,151,229,339,441,442,449)), c(11:17), 21:27),
            '151'=data.frame(ID=as.character(c(449,141,551,552)), 11:14, 21:24),
            '161'=data.frame(ID=as.character(171), 11,21), '171'=data.frame(ID=as.character(161), 11,21),
            '181'=data.frame(ID=as.character(881:882), 11:12,21:22) )

(te1 <- filterNetw(lst2, limInt=90, remOrphans=FALSE))
(te2 <- filterNetw(lst2, limInt=90, remOrphans=TRUE))

(te3 <- filterNetw(lst2, limInt=13, remOrphans=FALSE))
(te4 <- filterNetw(lst2, limInt=13, remOrphans=TRUE))
```

 filtSizeUniq

Filter For UniqueElements

Description

This function aims to identify and remove duplicated elements in a list and maintain the list-structure in the output. `filtSizeUniq` filters 'lst' (list of character-vectors or character-vector) for elements being unique (to 'ref' or if NULL to all 'lst') and of character length. In addition, the min- and max- character length may be filtered, too. Eg, in proteomics this helps removing peptide sequences which would not be measured/detected any way.

Usage

```

filtSizeUniq(
  lst,
  ref = NULL,
  minSize = 6,
  maxSize = 36,
  filtUnique = TRUE,
  byProt = TRUE,
  inclEmpty = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)

```

Arguments

<code>lst</code>	list of character-vectors or character-vector
<code>ref</code>	(character) optional alternative 'reference', if not NULL used in addition to 'lst' for considering elements of 'lst' as unique
<code>minSize</code>	(integer) minimum number of characters, if NULL set to 0
<code>maxSize</code>	(integer) maximum number of characters
<code>filtUnique</code>	(logical) if TRUE return unique-only character-strings
<code>byProt</code>	(logical) if TRUE organize output as list (by names of input, eg protein-names) - if 'lst' was named list
<code>inclEmpty</code>	(logical) optional including empty list-elements when all elements have been filtered away - if 'lst' was named list
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

list of filtered input

See Also

[correctToUnique](#), [unique](#), [duplicated](#)

Examples

```
filtSizeUniq(list(A="a",B=c("b","bb","c"),D=c("dd","d","ddd","c")),filtUn=TRUE,minSi=NULL)
# input: c and dd are repeated
filtSizeUniq(list(A="a",B=c("b","bb","c"),D=c("dd","d","ddd","c")),ref=c(letters[c(1:26,1:3)]),
  "dd","dd","bb","ddd"),filtUn=TRUE,minSi=NULL) # a,b,c,dd repeated
```

findCloseMatch

Find Close Numeric Values Between Two Vectors

Description

findCloseMatch finds close matches (similar values) between two numeric vectors ('x','y') based on method 'compTy' and threshold 'limit'. Return list with close matches of 'x' to given 'y', the numeric value depends on 'sortMatch' (if FALSE then always value of 'y' otherwise of longest of x&y). Note: Speed & memory improvement if 'sortMatch'=TRUE (but result might be inversed!): adopt search of x->y or y->x to searching matches of each longest to each shorter (ie flip x &y). Otherwise, if length of 'x' & 'y' are very different, it may be advantageous to use a long(er) 'x' and short(er) 'y' (with 'sortMatch'=FALSE). Note: Names of 'x' & 'y' or (if no names) prefix letters 'x' & 'y' are always added as names to results.

Usage

```
findCloseMatch(
  x,
  y,
  compTy = "ppm",
  limit = 5,
  asIndex = FALSE,
  maxFitShort = 100,
  sortMatch = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	numeric vector for comparison
y	numeric vector for comparison
compTy	(character) may be 'diff' or 'ppm', will be used with threshold from argument 'limit'
limit	(numeric) threshold value for retaining values, used with distace-type specified in argument 'compTy'
asIndex	(logical) optionally rather report index of retained values
maxFitShort	(numeric) limit output to max number of elements (avoid returning high number of results if filtering was not enough stringent)
sortMatch	(logical) if TRUE than matching will be preformed as 'match longer (of x & y) to closer', this may process slightly faster (eg 'x' longer: list for each 'y' all 'x' that are close, otherwise list of each 'x'),
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a list with close matches of 'x' to given 'y', the numeric value depends on 'sortMatch' (if FALSE then always value of 'y' otherwise of longest of x&y)

See Also

[checkSimValueInSer](#) and (from this package) `.compareByDiff`, for convient output [countCloseToLimits](#)

Examples

```
aa <- 11:14 ; bb <- c(13.1,11.5,14.3,20:21)
findCloseMatch(aa,bb,com="diff",lim=0.6)
findCloseMatch(c(a=5,b=11,c=12,d=18),c(G=2,H=11,I=12,J=13)+0.5, comp="diff", lim=2)
findCloseMatch(c(4,5,11,12,18),c(2,11,12,13,33)+0.5, comp="diff", lim=2)
findCloseMatch(c(4,5,11,12,18),c(2,11,12,13,33)+0.5, comp="diff", lim=2, sort=FALSE)
.compareByDiff(list(c(a=10,b=11,c=12,d=13),c(H=11,I=12,J=13,K=33)+0.5),limit=1) #' return matrix

a2 <- c(11:20); names(a2) <- letters[11:20]
b2 <- c(25:5)+c(rep(0,5),(1:10)/50000,rep(0,6)); names(b2) <- LETTERS[25:5]
which(abs(b2-a2[8]) < a2[8]*1e-6*5) #' find R=18 : no10
findCloseMatch(a2, b2, com="ppm", lim=5) #' find Q,R,S,T
findCloseMatch(a2, b2, com="ppm", lim=5,asI=TRUE) #' find Q,R,S,T
findCloseMatch(b2, a2, com="ppm", lim=5,asI=TRUE,sort=FALSE)
findCloseMatch(a2, b2, com="ratio", lim=1.000005) #' find Q,R,S,T
findCloseMatch(a2, b2, com="diff", lim=0.00005) #' find S,T
```

findHeadAndTail *Find Group-Names In Pairwise Combined And Isolate Separator*

Description

This function allows mapping which group-names are occurring either as head or as tail in pairwise combined terms (by checking from tails).

Usage

```
findHeadAndTail(
  grpNa,
  pairwNa,
  reportAs = "list",
  sortGrp = TRUE,
  rmAmbig = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

grpNa	(character) the names of the groups of replicates (ie conditions) used to test
pairwNa	(character) the names of pairwise-testing (ie 'concatenated' sampNa
reportAs	(character) default 'reportAs=list' to return list, otherwise a character vector with separator(s) found will be returned
sortGrp	(logical) by default groups will be sorted (as levels of a factor appear sorted)
rmAmbig	(logical) remove all ambiguous
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

This function aims identifying the separator used to create pairwise comparison labels by looking for given group-names at head and tail of combined labels. If labels occur inside other ones (eg 'AB' in 'ABC') it will always privilege the longest one. After stripping off all group-names the remaining characters are considered as the separator used. The function will also check if all pairwise labels returned the same separator and in case of multiple separators found the most frequent may be retained.

Value

This function returns a list containing \$sep a character vector of the separator(s) identified

See Also

(for running multiple pair-wise test) [moderTestXgrp](#), used underneath [grep](#)

Examples

```
findHeadAndTail(LETTERS[4:2], c("D-X", "D-C"))

grp1 <- c("C", "ACC", "CC", "B.B", "B.BA", "B", "CA")
pwNa1 <- "B.B-CC"
findHeadAndTail(grp1, pwNa1)

pwNa2 <- c("B.B-CC", "CA-ACC")
findHeadAndTail(grp1, pwNa2)
```

findRepeated	<i>Find repeated elements</i>
--------------	-------------------------------

Description

`findRepeated` gets index of repeated items/values in vector 'x' (will be treated as character). Return (named) list of indexes for each of the repeated values, or NULL if all values are unique. This approach is similar but more basic compared to [get1stOfRepeatedByCol](#).

Usage

```
findRepeated(x, nonRepeated = FALSE, silent = FALSE, callFrom = NULL)
```

Arguments

x	character vector
nonRepeated	(logical) if =TRUE, return list with elements \$rep and \$nonrep
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of message(s) produced

Value

(named) list of indexes for each of the repeated values, or NULL if all values unique

See Also

similar approach but more basic than [get1stOfRepeatedByCol](#)

Examples

```
aa <- c(11:16,14:12,14); findRepeated(aa)
```

findSimilFrom2sets *Find similar numeric values from two vectors/matrixes*

Description

findSimilFrom2sets compares two vectors or matrixes and returns combined view including only all close (by [findCloseMatch](#)). Return matrix (predMatr) with add'l columns for index to and 'grp' (group of similar values (1-to-many)), 'nGrp' (n of grp), 'isBest' or 'nBest', 'disToMeas' (distance/difference between pair) & 'ppmToPred' (distance in ppm). Note: too wide 'limitComp' will result in large window and many 'good' hits will compete (and be mutually excluded) if selection 'bestOnly' is selected

Usage

```
findSimilFrom2sets(
  predMatr,
  measMatr,
  colMeas = 1,
  colPre = 1,
  compareTy = "diff",
  limitComp = 0.5,
  bestOnly = FALSE,
  silent = FALSE,
  callFrom = NULL,
  debug = FALSE
)
```

Arguments

predMatr	(matrix or numeric vector) dataset number 1, referred to as 'predicted', the column speified in argument colPre points to the data to be used
measMatr	(matrix or numeric vector) dataset number 2, referred to as 'measured', the column speified in argument colMeas points to the data to be used
colMeas	(integer) which column number of 'measMatr' to consider
colPre	(integer) which column number of 'predMatr' to consider
compareTy	(character) 'diff' (difference) 'ppm' (relative difference)
limitComp	(numeric) limit used by 'compareTy'
bestOnly	(logical) allows to filter only hits with min distance (defined by 'compareTy'), 3rd last col will be 'nBest' - otherwise 3rd last col 'isBest'
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced
debug	(logical) for bug-tracking: more/enhanced messages

Value

This function returns a matrix (predMatr) with add'l columns for index to and 'grp' (group of similar values (1-to-many)), 'nGrp' (n of grp), 'isBest' or 'nBest', 'disToMeas' (distance/difference between pair) & 'ppmToPred' (distance in ppm)

See Also

[checkSimValueInSer](#) [findCloseMatch](#) [closeMatchMatrix](#)

Examples

```
aA <- c(11:17); bB <- c(12.001,13.999); cC <- c(16.2,8,9,12.5,12.6,15.9,14.1)
aZ <- matrix(c(aA,aA+20),ncol=2,dimnames=list(letters[1:length(aA)],c("aa","aZ")))
cZ <- matrix(c(cC,cC+20),ncol=2,dimnames=list(letters[1:length(cC)],c("cc","cZ")))
findCloseMatch(cC,aA,com="diff",lim=0.5,sor=FALSE)
findSimilFrom2sets(aA,cC)
findSimilFrom2sets(cC,aA)
findSimilFrom2sets(aA,cC,best=FALSE)
findSimilFrom2sets(aA,cC,comp="ppm",lim=5e4,deb=TRUE)
findSimilFrom2sets(aA,cC,comp="ppm",lim=9e4,best0=FALSE)
# below: find fewer 'best matches' since search window larger (ie more good hits compete !)
findSimilFrom2sets(aA,cC,comp="ppm",lim=9e4,best0=TRUE)
```

findUsableGroupRange *Select Groups Within Given Range*

Description

This function aims to help finding stretches/segments of data with a given maximum number of NA-instances.

Usage

```
findUsableGroupRange(
  dat,
  grp,
  maxNA = 1,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	(matrix or data.frame) main input
grp	(factor) information which column of 'dat' is replicate of whom
maxNA	(integer) max number of tolerated NAs

silent (logical) suppress messages
 debug (logical) additional messages for debugging
 callFrom (character) allow easier tracking of messages produced

Details

To find groups within a specific range, this function searches independently each line of the input-matrix 'dat' for stretches with a given maximum of NA-instances ('maxNA'). This function is used to inspect/filter each lines of 'dat' for a subset with sufficient presence/absence of NA values (ie limit number of NAs per level of 'grp'). Note : optimal performance with n.lines » n.groups

Value

This function returns a matrix with boundaries of 1st and last usable column (NA if there were no suitable groups found)

Examples

```

dat1 <- matrix(1:56, ncol=7)
dat1[c(2,3,4,5,6,10,12,18,19,20,22,23,26,27,28,30,31,34,38,39,50,54)] <- NA
rownames(dat1) <- letters[1:nrow(dat1)]
findUsableGroupRange(dat1, gl(3,3)[-3:4])

```

firstLineOfDat *Filter matrix to keep only first of repeated lines*

Description

This function aims to reduce the complexity of a matrix (or data.frame) in case column 'refCol' has multiple lines with same value. In this case, it reduces the input-data to 1st line of redundant entries and returns a matrix (or data.frame) without lines identified as redundant entries for 'refCol'. In sum, this functions works like using unique on a given column, and propagates the same treatment to all other columns.

Usage

```
firstLineOfDat(dat, refCol = 2, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

dat (matrix or data.frame) main input
 refCol (integer) column number of reference-column
 silent (logical) suppress messages
 debug (logical) additional messages for debugging
 callFrom (character) allow easier tracking of messages produced

Value

matrix (same number of columns as input)

See Also

[firstOfRepeated](#), [unique](#), [duplicated](#)

Examples

```
(mat1 <- matrix(c(1:6,rep(1:3,1:3)),ncol=2,dimnames=list(letters[1:6],LETTERS[1:2])))
firstLineOfDat(mat1)
```

firstOfRepeated	<i>Find first of repeated elements</i>
-----------------	--

Description

This function works similar to `unique`, but provides additional information about which elements of original input 'x' are repeated by providing indexes relative to the input. `firstOfRepeated` makes list with 3 elements: `$indRepeated..` index for first of repeated 'x', `$indUniq..` index of all unique + first of repeated, `$indRedund..` index of all redundant entries, ie non-unique (wo 1st). Used for reducing data to non-redundant status, however, for large numeric input the function `nonAmbiguousNum()` may perform better/faster. NAs won't be considered (NAs do not appear in reported index of results), see also `firstOfRepLines()`.

Usage

```
firstOfRepeated(x, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

x	(character or numeric) main input
silent	(logical) suppress messages
debug	(logical) display additional messages for debugging
callFrom	(character) allow easier tracking of message(s) produced

Value

list with indices: `$indRepeated`, `$indUniq`, `$indRedund`

See Also

[duplicated](#), [nonAmbiguousNum](#), [firstOfRepLines](#) gives less detail in output (lines/elements/indexes of omitted not directly accessible) and works faster

Examples

```
x <- c(letters[c(3,2:4,8,NA,3:1,NA,5:4)]); names(x) <- 100+(1:length(x))
firstOfRepeated(x)
x[firstOfRepeated(x)$indUniq]          # only unique with names
```

firstOfRepLines

Reduce To First Occurance Of Repeated Lines

Description

This function concatenates all columns of input-matrix and then searches like unique for unique elements, optionally the indexes of unique elements may get returned. Note: This function treats input as character (thus won't understand $10==10.0$). Returns simplified/non-redundant vector/matrix (ie fewer lines), or respective index. faster than [firstOfRepeated](#)

Usage

```
firstOfRepLines(
  mat,
  outTy = "ind",
  useCol = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

mat	initial matrix to treat
outTy	for output type: 'ind'.. index to 1st occurrence (non-red),'orig'..non-red lines of mat, 'conc'.. non-red concatenated values, 'num'.. index to which group/category the lines belong
useCol	(integer) custom choice of which columns to paste/concatenate
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a simplified/non-redundant vector/matrix (ie fewer lines for matrix), or respective index

See Also

[unique](#), [nonAmbiguousNum](#), faster than [firstOfRepeated](#) which gives more detail in output (lines/elements/indexes of omitted)

Examples

```
mat <- matrix(c("e", "n", "a", "n", "z", "z", "n", "z", "z", "b",
               "", "n", "c", "n", "", "", "n", "", "", "z"), ncol=2)
firstOfRepLines(mat, out="conc")
```

fuseAnnotMatr

Fuse annotation matrix to initial matrix

Description

In a number of instances experimental measurements and additional information (annotation) are provided by separate objects (matrixes) as they may not be generated the same time. The aim of this function is provide help when matching appropriate lines for 2 sets of data (experimental measures in `iniTab` and annotation from `annotTab`) for fusing. `fuseAnnotMatr` adds supplemental columns/annotation to an initial matrix `iniTab` : using column `'refIniT'` as key (in `iniTab`) to compare with key `'refAnnotT'` (from `'annotTab'`). The columns to be added from `annotTab` must be chosen explicitly. Note: if non-unique IDs in `iniTab` : runs slow (but save) due to use of loop for each unique ID.

Usage

```
fuseAnnotMatr(
  iniTab,
  annotTab,
  refIniT = "Uniprot",
  refAnnotT = "combName",
  addCol = c("ensembl_gene_id", "description", "geneName", "combName"),
  debug = TRUE,
  silent = FALSE,
  callFrom = NULL
)
```

Arguments

<code>iniTab</code>	(matrix), that may have lines with multiple (=repeated) key entries
<code>annotTab</code>	(matrix) containing reference annotation
<code>refIniT</code>	(character) type of reference (eg 'Uniprot')
<code>refAnnotT</code>	(character) column name to use for reference-annotation
<code>addCol</code>	(character) column-namess of 'annotTab' to use/extract (if no matches found, use all)
<code>debug</code>	(logical) for bug-tracking: more/enhanced messages
<code>silent</code>	(logical) suppress messages
<code>callFrom</code>	(character) allow easier tracking of message(s) produced

Value

This function returns a combined matrix (elements not found in 'annotTab' are displayed as NA)

See Also

[merge](#)

Examples

```
tab0 <- matrix(rep(letters[1:25],8),ncol=10)
tab1 <- cbind(Uniprot=paste(tab0[,1],tab0[,2]),col1=paste(tab0[,3],
  tab0[,4],tab0[,5]," ",tab0[,7],tab0[,6]))
tab2 <- cbind(combName=paste(tab0[,1],tab0[,2]),col2=paste(tab0[,8],tab0[,9],tab0[,10]))
fuseAnnotMatr(tab1,tab2[c(20:11,2:5),],refIni="Uniprot",refAnnotT="combName",addCol="col2")
fuseAnnotMatr(tab2[c(20:11,2:5),],tab1,refAnnotT="Uniprot",refIni="combName",addCol="col1")
```

fuseCommonListElem *Fuse content of list-elements with redundant (duplicated) names*

Description

This function fuses (character or numeric) elements of list re-occurring under same name, so that resultant list has unique names. Note : Will not work with list of matrixes

Usage

```
fuseCommonListElem(
  lst,
  initOrd = TRUE,
  removeDuplicates = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

lst	(list) main input, list of numeric vectors
initOrd	(logical) preserve initial order in output (if TRUE) or otherwise sort alphabetically
removeDuplicates	(logical) allow to remove duplicate entries (if vector contains names, both the name and the value need to be identical to be removed; note: all names must have names with more than 0 characters to be considered as names)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a fused list (same names as elements of input)

See Also

[unlist](#)

Examples

```
val1 <- 10 +1:26
names(val1) <- letters
lst1 <- list(c=val1[3:6],a=val1[1:3],b=val1[2:3],a=val1[12],c=val1[13])
fuseCommonListElem(lst1)
```

fusePairs

Fuse pairs to generate cluster-names

Description

Fuse previously identified pairs to 'clusters', return vector with cluster-numbers.

Usage

```
fusePairs(
  datPair,
  refDatNames = NULL,
  inclRepLst = FALSE,
  maxFuse = NULL,
  debug = FALSE,
  silent = TRUE,
  callFrom = NULL
)
```

Arguments

datPair	2-column matrix where each line represents 1 pair
refDatNames	(NULL or character) allows placing selected pairs in context of larger data-set (names to match those of 'datPair')
inclRepLst	(logical) if TRUE, return list with 'clu' (clu-numbers, default output) and 'refLst' (list of clustered elements, only n>1)
maxFuse	(integer, default NULL) maximal number of groups/clusters
debug	(logical) display additional messages for debugging
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of message(s) produced

Value

This function returns a vector with cluster-numbers

Examples

```
daPa <- matrix(c(1:5,8,2:6,9), ncol=2)
fusePairs(daPa, maxFuse=4)
```

get1stOfRepeatedByCol *Get First Of Repeated By Column*

Description

get1stOfRepeatedByCol sorts matrix 'mat' and extracts only 1st occurrence of values in column 'sortBy'. Returns then non-redundant matrix (ie for column 'sortBy', if 'markIfAmbig' specifies existing col, mark ambig there). Note : problem when sortSupl or sortBy not present (or not intended for use)

Usage

```
get1stOfRepeatedByCol(
  mat,
  sortBy = "seq",
  sortSupl = "ty",
  asFirstLast = c("full", "inter"),
  markIfAmbig = c("ambig", "seqNa"),
  asList = FALSE,
  abmiPref = "_",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

mat	(matrix or data.frame) numeric vector to be tested
sortBy	(character) column name for which elements should be made unique, numeric or character column; 'sortSupl' .. add'l colname to always select specific 1st)
sortSupl	(character) default="ty"
asFirstLast	(character,length=2) to force specific strings from colun 'sortSupl' as first and last when selecting 1st of repeated terms, default=c("full","inter")
markIfAmbig	(character,length=2) 1st will be set to 'TRUE' if ambiguous/repeated, 2nd will get (heading) prefix, default=c("ambig","seqNa")
asList	(logical) to return list with non-redundant ('unique') and removed lines ('repeats')

abmiPref (character) prefix to note ambiguous entries/terms, default="_"
 silent (logical) suppress messages
 debug (logical) additional messages for debugging
 callFrom (character) allow easier tracking of messages produced

Value

This function returns depending on argument 'asList' either list with non-redundant ('unique') and removed lines ('repeats')

See Also

[firstOfRepeated](#) for (more basic) treatment of simple vector, [nonAmbiguousNum](#) for numeric use (much faster !!!)

Examples

```
aa <- cbind(no=as.character(1:20), seq=sample(LETTERS[1:15], 20, repl=TRUE),
            ty=sample(c("full", "Nter", "inter"), 20, repl=TRUE), ambig=rep(NA, 20), seqNa=1:20)
get1stOfRepeatedByCol(aa)
```

getPairwiseSetup *Extract Pairwise Testing Setup*

Description

This function allows extracting, checking and combining elements defining labels for pairwise comparisons.

Usage

```
getPairwiseSetup(
  pwGrpNa,
  grpNa = NULL,
  sep = NULL,
  combPwSep = "combine1",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<code>pwGrpNa</code>	(character) the names of pairwise-testing (ie 'concatenated' <code>pwGrpNa</code> using the separator <code>sep</code>)
<code>grpNa</code>	(character) the names of the groups of replicates (ie conditions) used to test
<code>sep</code>	(NULL or character, length=1) if not NULL the character-vector (of length=1) given will be used to split <code>grpNa</code> using <code>stringsplit()</code>
<code>combPwSep</code>	(character) sequence of separators for building combined names; may be <code>combPwSep='combine1'</code> or <code>'combine2'</code> ; will be used in <code>pwSeparatorList()</code>
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Details

This function was designed to support functions exploiting pairwise testing results like plotting functions for Volcano-Plots etc.

Initially the function will check if the object given as argument `pwGrpNa` is an `MAarrayLM`-objects object and/or was created using `moderTestXgrp`. If yes, the function will try to extract names of groups, pairwise combinations and separator used from `$setup`, if present. If no `$setup` found this function will check through several elements in `MAarrayLM`-objects to gather all elements needed.

2) The separator `sep` is given and exact matches at both sides will be searched. However, if the character(s) from `sep` do appear inside `pwGrpNa` no matches will be found.

If some `pwGrpNa` are not found in `grpNa` this will be marked as NA.

Finally, if no testing result is given as input, basic parameters group-names, pairwise names and the separator to be used can be combined into a list.

Value

This function returns a list with `$ind` with matrix of indexes to (sorted) `pwGrpNa` for each pairwise comparison; `$pwGrpNames` with matrix of `pwGrpNa` for each pairwise comparison; `$sep` for the separator found ; `$pwGrpNa` which recapitulates (sorted) `pwGrpNa` as factor

See Also

(for running multiple pair-wise test) [moderTestXgrp](#), [convPairwiseSetup](#), [presenceFilt](#), [getPWseparator](#), [indexGroupsFromPW](#), (used underneath:) [grep](#), [strsplit](#)

Examples

```
grp3 <- factor(rep(LETTERS[c(3,1,4)],c(2,3,3)))
set.seed(2017); t8 <- matrix(round(rnorm(208*8,10,0.4),2), ncol=8,
  dimnames=list(paste(letters[],rep(1:8,each=26),sep=""), paste0(grp3, c(1:2,1:3,1:3))))
test1 <- moderTestXgrp(t8, grp3)
getPairwiseSetup(test1)
```

getPWseparator	<i>Identify Separator In Pairwise Group-Names Or Find Separator For Use With Pairwise Group-Names This function allows identifying separator used when pairwise groups are presented.</i>
----------------	---

Description

Identify Separator In Pairwise Group-Names Or Find Separator For Use With Pairwise Group-Names

This function allows identifying separator used when pairwise groups are presented.

Usage

```
getPWseparator(
  compNames = NULL,
  grp = NULL,
  potSep = c("-", "---", "_", "___", ".", "-vs-", "_vs_", "--vs--", "__vs__", " ", " ",
    "--", "__"),
  includeGrp = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

compNames	(character or integer) names of pairwise combined group-names
grp	(character or factor) optional groups (may include group-names that do not occur in compNames)
potSep	(character) potential separators to be checked if occurring in useComp; the first fitting will used
includeGrp	(logical) if includeGrp=TRUE a list including also the group-names is returned
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

Note : Potential separators potSep must be at least 1 character long

The character '.' may used as separator (argument potSep), it will be protected internally for obtaining correct results when using grep(). Note : The indexing is relative to the levels of grp, thus to sorted group-names !

Cases of usage : 1) Identify separator used in concatenated labels, ie concatenated group-names are given, (only argument compNames is obligatory)

2) Suggests/Find suitable separator for given group-labels (ie a separator not occurring in any of the group-labels) when names of grp given (thus argument grp is obligatory), the first instance of potSep fitting will be chosen

Value

This function returns a character vector (length=1) of the (first) separator fitting to all data, or a list with \$sep and \$grpNa if includeGrp=TRUE

See Also

[indexGroupsFromPW](#), [getPWseparator](#), colnames of testing results from [moderTestXgrp](#), used by [replacePWseparator](#)

Examples

```
## Suggest separator
getPWseparator(grp=LETTERS[1:3])
getPWseparator(grp=c("B-C", "D", "E"))
getPWseparator(grp=c("B-C", "D", "E"), includeGrp=TRUE)

## Identify separator used
getPWseparator(compNames=c("B-C", "B-D", "C-D"))
getPWseparator(compNames=c("B-C", "B-D", "C-D"), includeGrp=TRUE)
```

getValuesByUnique *Print matrix-content as plot*

Description

When data have repeated elements (defined by names inside the vector), it may be advantageous to run some operations only on a unique set of the initial data, or sometimes all repeated occurrences need to be replaced by a common (summarizing) value. This function allows to re-introduce new values from on second vector with unique names, to return a final vector of initial input-length and order of names (elements) like initial, too. Normally the user would provide 'datUniq' (without repeated names) containing new values which will be expanded to structure of 'dat', if 'datUniq' is not provided a vector with unique names will be made using the first occurrence of repeated value(s). For more complex cases the indexing relative to 'datUniq' can be returned (setting asIndex=TRUE). Note: If not all names of 'dat' are found in 'datUniq' the missing spots will be returned as NA.

Usage

```
getValuesByUnique(
  dat,
  datUniq = NULL,
  asIndex = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	(numeric or character) main long input, must have names
datUniq	(numeric or character) will be used to impose values on dat, must have names that should match names (at least partially) from dat
asIndex	(logical) if TRUE index values will be returned instead of replacing values
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

vector of length dat with imposed values, or index values if asIndex=TRUE

See Also

[unique](#), [findRepeated](#), [correctToUnique](#), [treatTxtDuplicates](#)

Examples

```
dat <- 11:19
names(dat) <- letters[c(6:3,2:4,8,3)]
## let's make a 'datUniq' with the mean of repeated values :
datUniq <- round(tapply(dat,names(dat),mean),1)
## now propagate the mean values to the full vector
getValuesByUnique(dat,datUniq)
cbind(ini=dat,firstOfRep=getValuesByUnique(dat,datUniq),
      indexUniq=getValuesByUnique(dat,datUniq,asIn=TRUE))
```

gitDataUrl

Convert GitHub Url-Name For Reading In Raw-Mode

Description

This functions converts a given urlName so that (tabular) data from GitHub (<https://github.com/>) can data be read correctly as tabular data.

Usage

```
gitDataUrl(
  urlName,
  replTxt = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

urlName	(character) main url-address
replTxt	(NULL or matrix) adjust/ custom-modify search- and replacement items; default settings will exchange the beginning of the site to 'raw.githubusercontent.com' and then exchange 'blob' to 'refs/head' otherwise should be matrix with 2 columns, the 1st column entries will be used as 'search-for' and the 2nd as 'replace by' for each row
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

Thus, this will exchange the beginning of the site to 'raw.githubusercontent.com' and then exchange 'blob' to 'refs/head' . Alternatively, the user may custom define all terms to get exchanged (as matrix with 2 columns 'old' and 'new').

Note : The default separator from [read.delim](#) may suit better for reading the data.

Value

corrected urlName

See Also

[sub](#); [read.delim](#)

Examples

```
url1 <- paste0("https://github.com/bigbio/proteomics-metadata-standard/blob/",
              "main/datasets/PXD001819/PXD001819.sdrf.tsv")
rbind(ini=url1, new=gitDataUrl(url1))
```

htmlSpecCharConv

Html Special Character Conversion

Description

Converts 'txt' so that (the most common) special characters (like 'beta', 'micro', 'square' etc) will be displayed correctly when used for display in html (eg at mouse-over). Note : The package [stringi](#) is required for the conversions (the input will get returned if [stringi](#) is not available). Currently only the 16 most common special characters are implemented.

Usage

```
htmlSpecCharConv(txt, silent = FALSE, callFrom = NULL, debug = FALSE)
```

Arguments

txt	character vector, including special characters
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced
debug	(logical) additional messages for debugging

Value

This function returns a corrected character vector adopted for html display

See Also

tables on <https://www.htmlhelp.com/reference/html40/entities/latin1.html>, <https://www.degraeve.com/reference/specialcharacters.php>, or <https://ascii.cl/htmlcodes.htm>

Examples

```
## we'll use the package stringi to generate text including the 'micro'-symbol as input
x <- if(requireNamespace("stringi", quietly=TRUE)) {
  stringi::stri_unescape_unicode("\u00b5\u003d\u0061\u0062")} else "\"x=axb\""
htmlSpecCharConv(x)
```

indexGroupsFromPW	<i>Index Names Of Groups From Vector Of Concatenated Pairwise Group-Names</i>
-------------------	---

Description

This function allows matching which groups are cited in a pairwise concatenated manner. This function can also be used to split concatenated group-names (while automatically determining a suitable separator) and display as matrix when includeGrp=TRUE. Replaces matchSampToPairw() ???

Usage

```
indexGroupsFromPW(
  compNames,
  grp = NULL,
  potSep = pwSeparatorList("combine1"),
  includeGrp = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

compNames	(vector of character or integer, or matrix) names of pairwise combined group-names; if matrix the rownames of compNames will be used
grp	(character or factor) optional groups (may include group-names that do not occur in compNames)
potSep	(character) potential separators to be checked if occurring in useComp; the first fitting will be used
includeGrp	(logical) instead of matrix, rather return list with \$pwInd, \$pwGrpNames (group-names corresponding to index), \$sep (separator used to split) and \$grpNa
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a numeric matrix with indexes corresponding to (sorted) group-names as they appear in compNames; or if includeGrp=TRUE a list with \$ind (matrix indexes for each compNames), \$grpNames (group-names corresponding to index), \$sep (separator used to split) and \$grpNa (sorted names of types of groups)

See Also

[moderTestXgrp](#) (colnames of testing results from this function may be used); [replacePWseparator](#); used internally [getPWseparator](#), [pwSeparatorList](#), [.getPWseparator](#)

Examples

```
indexGroupsFromPW(c("C-B", "B-D", "C-D"))
indexGroupsFromPW(c("C-B", "B-D", "C-D"), grp=rep(LETTERS[1:6],2), includeGrp=TRUE)
```

keepCommonText

Extract Longest Common Text Out Of Character Vector

Description

This function allows recovering the single longest common text-fragments (from center, head or tail) out of character vector txt. Only the first of all of the longest solutions will be returned.

Usage

```
keepCommonText(
  txt,
  minNchar = 1,
  side = "center",
  hiResol = TRUE,
```

```

    silent = TRUE,
    callFrom = NULL,
    debug = FALSE
)

```

Arguments

txt	character vector to be treated
minNchar	(integer) minimum number of characters that must remain
side	(character) may be either 'center', 'any', 'terminal', 'left' or 'right'; only with side='center' or 'any' internal text-segments may be found
hiResol	(logical) find best solution, but at much higher computational cost (eg 3x slower, however hiResol=FALSE rather finds anchor which may need to get extended)
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced
debug	(logical) display additional messages for debugging

Details

Please note, that finding common parts between chains of characters is not a completely trivial task. This topic still has ongoing research for the application of sequence-alignments, where chains of characters to be compared get very long. This function uses a k-mer inspired approach. The initial aim with this function was allowing to treat smaller chains of characters (and finding shorter stretches of common text), like eg with column-names.

Important : This function identifies only the first best hit, ie other shared/common character-chains of the same length will not be found !

Using the argument hiResol=FALSE it is possible to accelerate the search approx 3x (with larger character-vectors), however, frequently the very best solution may not be found. This means, that in this case the result should rather be considered a 'seed', allowing check if further extension may improve the result, ie for identifying a (slightly) longer chain of common characters.

With longer vectors and longer character chains this may get demanding on computational resources, the argument hiResol=FALSE allows reducing this at the price of missing the best solution. With this argument single common/matching characters will not be searched if all text-elements are longer than 500 characters, an empty character vector will be returned.

When argument side is either left, right or terminal only terminal common text may be found (a potentially even longer internal text will be lost). Of course, choosing this option makes searches much faster.

This function does not return the position of the shared/common characters within the text, you may use grexpr or regex to locate them.

Value

This function returns a character vector of length=1, ie only one (normally the longest) common sequence of characters is identified. If nothing is found common/shared an empty character-vector is returned

See Also

Use `gregexpr` or `regexec` in [grep](#) for locating the identified common characters in the initial query.

Inverse : Trim redundant text (from either side) to keep only variable part using [trimRedundText](#); you may also look for related functions in package [stringr](#)

Examples

```
txt1 <- c("abcd_abc_kjh", "bcd_abc123", "cd_abc_po")
keepCommonText(txt1, side="center")      # trim from right

txt2 <- c("ddd_ab", "ddd_bcd", "ddd_cde")
trimRedundText(txt2, side="left")        #
keepCommonText(txt2, side="center")      #
```

levIndex

*Transform (factor) levels into index***Description**

This function helps transforming a numeric or character vector into indexes of levels (of its original values). By default indexes are assigned by order of occurrence, ie, the first value of `x` will be get the index of 1. Using the argument `byOccurance=FALSE` the resultant indexes will follow the sorted values.

Usage

```
levIndex(
  dat,
  byOccurance = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<code>dat</code>	(numeric or character vector or factor) main input
<code>byOccurance</code>	(logical) toggle if lowest index should be based on alphabetical order or on order of input
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

matrix with mean values

See Also

[rowSds, colSums](#)

Examples

```
x1 <- letters[rep(c(5,2:3),1:3)]
levIndex(x1)
levIndex(x1, byOccurance=FALSE)
## with factor
fa1 <- factor(letters[rep(c(5,2:3),1:3)], levels=letters[1:6])
levIndex(fa1)
levIndex(fa1, byOccurance=FALSE)
```

linModelSelect	<i>Test Multiple Starting Levels For Linear Regression Model, Select Best And Plot</i>
----------------	--

Description

The aim of this function is to select the data suiting set of levels on the main input data to construct a linear regression model.

Usage

```
linModelSelect(
  rowNa,
  dat,
  expect,
  logExpect = FALSE,
  startLev = NULL,
  lisNa = c(raw = "raw", annot = "annot", datImp = "datImp"),
  plotGraph = TRUE,
  tit = NULL,
  pch = c(1, 3),
  cexLeg = 0.95,
  cexSub = 0.85,
  xLab = NULL,
  yLab = NULL,
  cexXAxis = 0.85,
  cexYAxis = 0.9,
  xLabLas = 1,
  cexLab = 1.1,
  suppressWarnings = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

rowNa	(character or numeric, length=1) if character rowname for line to be extracted from dat, if numeric used as line-number of dat
dat	(matrix, list or MArrayLM-object from limma) main input of which columns should get re-ordered, may be output from <code>moderTestXgrp</code> or <code>moderTest2grp</code> .
expect	(numeric or character) the expected levels; if character, constant unit-characters will be stripped away to extract the numeric content
logExpect	(logical) toggle to TRUE if the main data are logarithmic but expect is linear
startLev	(integer) specify all starting levels to test for omitting here (multiple start sites for modelling linear regression may be specified to finally pick the best model)
lisNa	(character) in case dat is list or MArrayLM-type object, the list-elements with these names will be used as \$raw (for indicating initial NA-values, \$datImp (the main quantitation data to use) and \$annot for displaying the corresponding value from the "Accession"-column.
plotGraph	(logical) display figure
tit	(character) optional custom title
pch	(integer) symbols to use n optional plot; 1st for regular values, 2nd for values not used in regression
cexLeg	(numeric) size of text in legend
cexSub	(numeric) text-size for line (as subtitle) giving regression details of best linear model)
xLab	(character) custom x-axis label
yLab	(character) custom y-axis label
cexXAxis	(character) cex-type for size of text for x-axis labels
cexYAxis	(character) cex-type for size of text for y-axis labels
xLabLas	(integer) las-type orientation of x-axis labels (set to 2 for vertical axis-labels)
cexLab	(numeric) cex-type for size of text in x & y axis labels (will be passed to <code>cex.lab</code> in <code>plot()</code>)
suppressWarnings	(logical) suppress warnings from <code>lm()</code> that may appear when NAs get introduced
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

In real world measurements one may be confronted to the case of very low level analytes below the detection limit (LOD) and resulting read-outs fluctuate around around a common baseline (instead of NA). With such data it may be preferable to omit the read-outs for the lowest concentrations/levels of analytes if they are spread around a base-line value. This function allows trying to omit all starting levels designed in `startLev`, then the resulting p-values for the linear regression slopes will be

checked and the best p-value chosen. The input may also be a MArrayLM-type object from package `limma` or from `moderTestXgrp` or `moderTest2grp`. In the graphical representation all points associated to levels omitted are shown in light green. For the graphical display additional information can be used : If the `dat` is list or MArrayLM-type object, the list-elements `$raw` (according to argument `lisNa` will be used to display points initially given as NA and imputed later on in grey. Logarithmic (ie log-linear) data can be treated by setting argument `logExpect=TRUE`. Then the levels will be taken as exponent of 2 for the regression, while the original values will be displayed in the figure.

Value

This function returns a list with `$coef` (coefficients), `$name` (as/from input `rowNa`), `$startLev` the best starting level)

See Also

`moderTestXgrp` for single comparisons, `order`

Examples

```
## Construct data
li1 <- rep(c(4,3,3:6),each=3) + round(runif(18)/5,2)
names(li1) <- paste0(rep(letters[1:5], each=3), rep(1:3,6))
li2 <- rep(c(6,3:7), each=3) + round(runif(18)/5, 2)
dat2 <- rbind(P1=li1, P2=li2)
exp2 <- rep(c(11:16), each=3)

## Check & plot for linear model
linModelSelect("P2", dat2, expect=exp2)

## Log-Linear data
## Suppose dat2 is result of measures in log2, but exp4 is not
exp4 <- rep(c(3,10,30,100,300,1000), each=3)
linModelSelect("P2", dat2, expect=exp4, logE=FALSE) # bad
linModelSelect("P2", dat2, expect=exp4, logE=TRUE)
```

linRegrParamAndPVal *Fit linear regression, return parameters and p-values*

Description

This function fits a linear regression and returns the parameters, including p-values from Anova. Here the vector 'y' (scalar response or dependent variable, ie the value that should get estimated) will be estimated according to 'dep' (explanatory or independent variable). Alternatively, 'dep' may me a matrix where 1st column will be used as 'dep' and the 2nd column as 'y'.

Usage

```
linRegrParamAndPVal(
  dep,
  y = NULL,
  asVect = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dep	(numeric vector, matrix or data.frame) explanatory or dependent variable, if matrix or data.frame the 1st column will be used, if 'y'=NULL the 2nd column will be used as 'y'
y	(numeric vector) independent variable (the value that should get estimated based on 'dep')
asVect	(logical) return numeric vector (Intercept, slope, p.intercept, p.slope) or matrix or results
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

numeric vector (Intercept, slope, p.intercept, p.slope), or if asVect==TRUE as matrix (p.values in 2nd column)

See Also

[lm](#)

Examples

```
linRegrParamAndPVal(c(5,5.1,8,8.2),gl(2,2))
```

listBatchReplace

Replacements in list

Description

listBatchReplace replaces in list lst all entries with value searchValue by replaceBy

Usage

```
listBatchReplace(
  lst,
  searchValue,
  replaceBy,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

lst	input-list to be used for replacing
searchValue	(character, length=1)
replaceBy	(character, length=1)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a corrected list

See Also

basic replacement sub in [grep](#)

Examples

```
lst1 <- list(aa=1:4, bb=c("abc", "efg", "abhh", "effge"), cc=c("abdc", "efg"))
listBatchReplace(lst1, search="efg", repl="EFG", sil=FALSE)
```

listGroupsByNames *Organize Values Into List And Sort By Names*

Description

Sort values of 'x' by its names and organize as list by common names, the names until 'sep' are used for (re)grouping. Note that typical spearators occuring the initial names may need protection by '\` (this is automatically taken care of for the case of the dot ('.') separator).

Usage

```
listGroupsByNames(x, sep = ".", silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

x	(list) main input
sep	(character) separator (note that typical separators may need to be protected, only automatically added for '.')
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a matrix or data.frame

See Also

rbind in [cbind](#)

Examples

```
listGroupsByNames((1:10)/5)
ser1 <- 1:6; names(ser1) <- c("AA", "BB", "AA.1", "CC", "AA.b", "BB.e")
listGroupsByNames(ser1)
```

 lmSelClu

Run lm on segmented data (from clustering)

Description

lmSelClu runs linear regression on data segmented previously (eg by clustering). This function offers various types of (2-coefficient) linear regression on 2 columns of 'dat' (matrix with 3rd col named 'clu' or 'cluID', numeric elements for cluster-number). If argument 'clu' is (default) 'max', the column 'clu' will be inspected to take most frequent value of 'clu', otherwise a numeric entry specifying the cluster to extract is expected. Note: this function was initially made for use with results from diagCheck() Note: this function lacks means of judging goodness of fit of the regression performed & means for plotting

Usage

```
lmSelClu(
  dat,
  useCol = 1:2,
  clu = "max",
  regTy = "lin",
  filt1 = NULL,
  filt2 = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	matrix or data.frame
useCol	(integer or character) specify which 2 columns of 'dat' to use for linear regression
clu	(character) name of cluster to be extracted and treated
regTy	(character) change type used for linear regression : 'lin' for 1st col ~ 2nd col, 'res' for residue ~ 2nd col, 'norRes' for residue/2nd col ~ 2nd col or 'sqNorRes', 'inv' for 1st col ~ 1/(2nd col), 'invRes' for residue ~ 1/(2nd col)
filt1	(logical or numerical) filter criteria for 1st of 'useCol' , if numeric then select all lines of dat less than max of filt1
filt2	(logical or numerical) filter criteria for 2nd of 'useCol' , if numeric then select all lines of dat less than max of filt2
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

lm object (or NULL if no data left)

See Also

[lm](#)

Examples

```
set.seed(2016); ran1 <- runif(220)
mat1 <- round(rbind(matrix(c(1:100+ran1[1:100], rep(1, 50)), ncol=3),
  matrix(c(1:60, 68:9+ran1[101:160], rep(2, 60)), nc=3)), 1)
colnames(mat1) <- c("a", "BB", "clu")
lmSelClu(mat1)
plot(mat1[which(mat1[, 3]=="2"), 1:2], col=grey(0.6))
abline(lmSelClu(mat1), lty=2, lwd=2)
#
mat2 <- round(rbind(matrix(c(1:100+ran1[1:100], rep(1, 50)), ncol=3),
  matrix(c(1:60, (2:61+ran1[101:160])^2, rep(2, 60)), nc=3)), 1)
colnames(mat2) <- c("a", "BB", "clu")
(reg2 <- lmSelClu(mat2, regTy="sqNor"))
plot(function(x) coef(reg2)[2]+ (coef(reg2)[2]*x^2), xlim=c(1, 70))
points(mat2[which(mat2[, 3]=="2"), 1:2], col=2)
```

lrbind	<i>rbind on lists</i>
--------	-----------------------

Description

rbind-like function to append list-elements containing matrixes (or data.frames) and return one long table. All list-elements must have same number of columns (and same types of classes in case of data.frames. Simple vectors (as list-elements) will be considered as sigle lines for attaching.

Usage

```
lrbind(lst, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

lst	(list, composed of multiple matrix or data.frames or simple vectors) main input (each list-element should have same number of columns, numeric vectors will be converted to number of columns of other columns/elements)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns (depending on input) a matrix or data.frame

See Also

rbind in [cbind](#)

Examples

```
lst1 <- list(matrix(1:9, ncol=3, dimnames=list(letters[1:3],c("AA","BB","CC"))),  
            11:13, matrix(51:56, ncol=3))  
lrbind(lst1)
```

makeMAList	<i>Make MA-List Object</i>
------------	----------------------------

Description

makeMAList extracts sets of data-pairs (like R & G series) and makes MA objects as MA-List object (eg for ratio oriented analysis). The grouping of columns as sets of replicate-measurements is done according to argument MAfac. The output is fully compatible to functions of package [limma](#) (Bioconductor).

Usage

```
makeMAList(
  mat,
  MAfac,
  useF = c("R", "G"),
  isLog = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

mat	main input matrix
MAfac	(factor) factor organizing columns of 'mat' (if useF contains the default 'R' and 'G', they should also be part of MAfac)
useF	(character) two specific factor-levels of MAfac that will be used/extracted
isLog	(logical) tell if data is already log2 (will be considered when computing M and A values)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

This function requires Bioconductor package [limma](#) being installed.

Value

limma-type "MAList" containing M and A values

See Also

[test2factLimma](#), for creating RG-lists within limma: MA.RG in [normalizeWithinArrays](#)

Examples

```
set.seed(2017); t4 <- matrix(round(runif(40,1,9),2), ncol=4,
  dimnames=list(letters[c(1:5,3:4,6:4)], c("AA1","BB1","AA2","BB2")))
makeMAList(t4, gl(2,2,labels=c("R","G")))
```

makeNRedMatr

Make non-redundant matrix

Description

This function takes matrix or data.frame 'dat' to summarize redundant lines (column argument iniID) along method specified in summarizeRedAs to treat all lines with redundant iniID by same approach (ie for all columns the line where specified column is at eg max = 'maxOfRef'). If no name given, the function will take the last numeric (factors may be used - they will be read as levels).

Usage

```
makeNRedMatr(
  dat,
  summarizeRedAs,
  iniID = "iniID",
  retDataFrame = TRUE,
  nEqu = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	(matrix or data.frame) main input for making non-redundant
summarizeRedAs	(character) summarization method(s), typical choices 'median','mean','min' or 'maxOfRef'; basic usage like summarizeRedAs='mean' will pick independently the mean for each (numeric) column; it is also possible to specify different methods for each of columnw (length of summarizeRedAs should be equal number of numeric columns); special methods look at a single reference column to decide which line should be picked and their values reported (not compatible with specifying different methods for different columns),
iniID	(character) column-name used as reference for determining groups of redundant lines (default="iniID")
retDataFrame	(logical) if TRUE, check if text-columns may be converted to data.frame with numeric
nEqu	(logical) if TRUE, add additional column indicating the number of equal lines for choice (only with min or max)
silent	(logical) suppress messages

debug (logical) additional messages for debugging
 callFrom (character) allows easier tracking of messages produced

Details

When using for selection of single initial line give the character-string of argument `summarizeRedAs` a name (eg `summ=c(X1="minOfRef")`) so that the function will use **ONLY** the column specified via the name for determining which line should be used/kept.

It is possible to base the choice from 'redundant' lines on a single reference-column. For example, when `summarizeRedAs='maxOfRef'` summarizing of all (numeric) columns will be performed according to one single column (ie the line where the last numeric column is at its max). Otherwiser, a name can be assigned as reference column to be used (eg see last example using `summarizeRedAs=c(x1='maxOfRef')`)

Value

This function returns a (numeric) matrix or data.frame with summarized data and add'l col with number of initial redundant lines

See Also

simple/partial functionality in [summarizeCols](#), [checkSimValueInSer](#)

Examples

```
t3 <- data.frame(ref=rep(11:15,3),tx=letters[1:15],
  matrix(round(runif(30,-3,2),1),nc=2),stringsAsFactors=FALSE)
by(t3,t3[,1],function(x) x)
t(sapply(by(t3,t3[,1],function(x) x), summarizeCols, me="maxAbsOfRef"))
# calculate mean for lines concerened of all columns :
(xt3 <- makeNRedMatr(t3, summ="mean", iniID="ref"))
# choose lines based only on content of column 'X1' (here: max):
(xt3 <- makeNRedMatr(t3, summ=c(X1="maxOfRef"), iniID="ref"))
```

matchMatrixLinesToRef *Match All Lines of Matrix To Reference Note*

Description

This function allows adjusting the order of lines of a matrix `mat` to a reference character-vector `ref`, even when initial direct matching of character-strings using `match` is not possible/successful. In this case, various variants of using `grep` will be used to see if unambiguous matching is possible of characteristic parts of the text. All columns of `mat` will be tested an the column giving the bes results will be used.

Usage

```
matchMatrixLinesToRef(
  mat,
  ref,
  exclCol = NULL,
  addRef = TRUE,
  inclInfo = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

mat	(matrix or data.frame) main input, all columns of mat will be tested for (partial) matching of ref
ref	(character, length must match) reference for trying to match each of the columns of mat
exclCol	(character or integer) column-name or -index of column to ignore/exclude when looking for matches
addRef	(logical), if TRUE the content of ref will be added to mat as additional column
inclInfo	(logical) allows returning list with new matrix and additional information
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Details

This function tests all columns of mat to find perfect matching results to the reference ref. In case of multiple results the In case no direct matching is possible, grep will be used to find the best partial matching. The orderof the rows of input mat will be adjusted according to the matching results.

If addRef=TRUE, the reference will be included as additional column to the results, too.

Value

This function returns the input matrix in an adjusted order (plus an optional additional column showing the reference) or if inclInfo=TRUE a list with \$mat (adjusted matrix), \$byColumn, \$newOrder and \$method; the reference can be added as additional last column if addRef=TRUE

See Also

[match](#), [grep](#), [trimRedundText](#), [replicateStructure](#)

Examples

```
## Note : columns b and e allow non-ambiguous match, not all elements of e are present in a
mat0 <- cbind(a=c("mvvk","axxd","bxxd","vv"),b=c("iwwy","iyyu","kvvh","gxx"), c=rep(9,4),
  d=c("hgf","hgf","vxc","nvn"), e=c("_vv_","_ww_","_xx_","_yy_"))
matchMatrixLinesToRef(mat0[,1:4], ref=mat0[,5])
matchMatrixLinesToRef(mat0[,1:4], ref=mat0[1:3,5], inclInfo=TRUE)

matchMatrixLinesToRef(mat0[,-2], ref=mat0[,2], inclInfo=TRUE) # needs 'reverse grep'
```

```
matchNamesWithReverseParts
```

Value Matching with optional reversing of sub-parts of non-matching elements

Description

This function provides a variant to `match`, where initially non-matching elements of `x` will be tested by decomposing non-matching elements, reversing the parts in front and after the separator `sep` and re-matching. If separator `sep` does not occur, a warning will be issued, if it occurs more than once, the parts before and after the first separator will be used and a warning issued.

Usage

```
matchNamesWithReverseParts(
  x,
  y,
  sep = "-",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<code>x</code>	(character) first vector for match
<code>y</code>	(character) second vector for match
<code>sep</code>	(character) separator between elements
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

index for matching (integer) `x` to `y`

See Also[match](#)**Examples**

```
tx1 <- c("a-b", "a-c", "d-a", "d-b", "b-c", "d-c")
tmp <- triCoord(4)
tx2 <- paste(letters[tmp[,1]], letters[tmp[,2]], sep="-")
## Some matches won't be found, since 'a-d' got reversed to 'd-a', etc...
match(tx1, tx2)
matchNamesWithReverseParts(tx1, tx2)
```

matchSampToPairw

Match Names To Concatenated Pairs Of Names

Description

The column-names of multiple pairwise testing contain the names of the initial groups/conditions tested, plus there is a separator (eg '-' in `moderTestXgrp`). Thus function allows to map back which groups/conditions were used by returning the index of the respective groups used in pair-wise sets.

Usage

```
matchSampToPairw(
  grpNa,
  pairwNa,
  sep = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<code>grpNa</code>	(character) the names of the groups of replicates (ie conditions) used to test
<code>pairwNa</code>	(character) the names of pairwise-testing (ie 'concatenated' <code>sampNa</code>)
<code>sep</code>	(character) if not NULL the characters given will be used via <code>stringsplit</code>
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Details

There are two modes of operation : 1) Argument sep is set to NULL : The names of initial groups/conditions (grpNa) will be tested for exact pattern matching either at beginning or at end of pair-wise names (pairwNa). This approach has the advantage that it does not need to be known what character(s) were used as separator (or they may change), but the disadvantage that in case the perfect grpNa was not given, the longest best match of grpNa will be returned.

2) The separator sep is given and exact matches at both sides will be searched. However, if the character(s) from sep do appear inside grpNa no matches will be found.

If some grpNa are not found in pairwNa this will be marked as NA.

This function checks also if a double version of sep may fit better to grpNa and will adjust sep accordingly (eg adjust sep='-' to '-').

Value

This function returns a matrix of 2 columns with indices of sampNa with pairwNa as rows

See Also

(for running multiple pair-wise test) [moderTestXgrp](#), [grep](#), [strsplit](#)

Examples

```
pairwNa1 <- c("abc-efg", "abc-hij", "efg-hij")
grpNa1 <- c("hij", "abc", "abcc", "efg", "klm")
matchSampToPairw(grpNa1, pairwNa1)
```

```
pairwNa2 <- c("abc-efg", "abcc-hij", "abc-hij", "abc-hijj", "zz-zz", "efg-hij")
matchSampToPairw(grpNa1, pairwNa2)
```

matr2list

Transform columns of matrix to list of vectors

Description

convert matrix to list of vectors: each column of 'mat' as vector of list

Usage

```
matr2list(mat, concSym = ".", silent = FALSE, debug = TRUE, callFrom = NULL)
```

Arguments

mat	(matrix) main input
concSym	(character) symbol for concatenating: concatenation of named vectors in list names as colname(s)+'concSym'+rowname
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

matrix or array (1st dim is intraplate-position, 2nd .. plate-group/type, 3rd .. channels)

See Also

[convToNum](#)

Examples

```
mat1 <- matrix(1:12, ncol=3, dimnames=list(letters[1:4], LETTERS[1:3]))
mat2 <- matrix(LETTERS[11:22], ncol=3, dimnames=list(letters[1:4], LETTERS[1:3]))
matr2list(mat1); matr2list(mat2)
```

mergeMatrices

Merge Multiple Matrices

Description

This function allows merging of multiple matrix-like objects. The matrix-rownames will be used to align common elements, either by returning all common elements mode='intersect' or containing all elements mode='union' (the result may contain additional NAs).

Usage

```
mergeMatrices(
  ...,
  mode = "intersect",
  useColumn = 1,
  na.rm = TRUE,
  extrRowNames = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

...	(matrix or data.frame) multiple matrix or data.frame objects may be entered
mode	(character) allows choosing restricting to all common elements (mode='intersect') or union (mode='union')
useColumn	(integer, character or list) the column(s) to consider, may be 'all' to use all, integer to select specific indexes or list of indexes or colnames for custom-selection per matrix
na.rm	(logical) suppress NAs
extrRowNames	(logical) decide whether columns with all values different (ie no replicates or max divergency) should be excluded

silent (logical) suppress messages
 debug (logical) additional messages for debugging
 callFrom (character) allow easier tracking of messages produced

Details

Custom column-names can be given by entering matrices like named arguments (see examples below). The choice of columns to use may be adopted to each matrix entered, in this case the argument useColumn may be a list with matrix-names to use or a list of indexes (see examples below).

Note, that matrices may contain repeated rownames (see examples, mat3). In this case only the first of repeated rownames will be considered (and lines of repeated names ignored).

Value

This function returns a matrix containing all selected columns of the input matrices to fuse

See Also

[merge](#), [mergeMatrixList](#)

Examples

```
mat1 <- matrix(11:18, ncol=2, dimnames=list(letters[3:6],LETTERS[1:2]))
mat2 <- matrix(21:28, ncol=2, dimnames=list(letters[2:5],LETTERS[3:4]))
mat3 <- matrix(31:38, ncol=2, dimnames=list(letters[c(1,3:4,3)],LETTERS[4:5]))

mergeMatrices(mat1, mat2)
mergeMatrices(mat1, mat2, mat3, mode="union", useCol=2)
## custom names for matrix-origins
mergeMatrices(m1=mat1, m2=mat2, mat3, mode="union", useCol=2)
## flexible/custom selection of columns
mergeMatrices(m1=mat1, m2=mat2, mat3, mode="union", useCol=list(1,1:2,2))
```

mergeMatrixList

Merge Multiple Matrices from List

Description

This function allows merging of multiple matrix-like objects from an initial list. The matrix-rownames will be used to align common elements, either by returning all common elements mode= 'intersect' or containing all elements mode= 'union' (the result may contain additional NAs).

Usage

```
mergeMatrixList(  
  matLst,  
  mode = "intersect",  
  useColumn = 1,  
  na.rm = TRUE,  
  extrRowNames = FALSE,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

matLst	(list containing matrices or data.frames) main input (multiple matrix or data.frame objects)
mode	(character) allows choosing restricting to all common elements (mode='intersect') or union (mode='union')
useColumn	(integer, character or list) the column(s) to consider, may be 'all' to use all, integer to select specific indexes or list of indexes or colnames for custom-selection per matrix
na.rm	(logical) suppress NAs
extrRowNames	(logical) decide whether columns with all values different (ie no replicates or max divergency) should be excluded
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

Custom column-names can be given by entering matrices like named arguments (see examples below). The choice of columns to use may be adopted to each matrix entered, in this case the argument useColumn may be a list with matrix-names to use or a list of indexes (see examples below).

Note, that matrices may contain repeated rownames (see examples, mat3). In this case only the first of repeated rownames will be considered (and lines of repeated names ignored).

Value

This function returns a matrix containing all selected columns of the input matrices to fuse

See Also

[merge](#), [mergeMatrices](#) for separate entries

Examples

```

mat1 <- matrix(11:18, ncol=2, dimnames=list(letters[3:6],LETTERS[1:2]))
mat2 <- matrix(21:28, ncol=2, dimnames=list(letters[2:5],LETTERS[3:4]))
mat3 <- matrix(31:38, ncol=2, dimnames=list(letters[c(1,3:4,3)],LETTERS[4:5]))

mergeMatrixList(list(mat1, mat2))

mergeMatrixList(list(m1=mat1, m2=mat2, mat3), mode="union", useCol=2)

```

mergeSelCol

Merge selected columns out of 2 matrix or data.frames

Description

This function merges selected columns out of 2 matrix or data.frames. 'selCols' will be used to define columns to be used; optionally may be different for 'dat2' : define in 'supCols2'. Output-cols will get additions specified in newSuff (default '.x' and '.y')

Usage

```

mergeSelCol(
  dat1,
  dat2,
  selCols,
  supCols2 = NULL,
  byC = NULL,
  useAll = FALSE,
  setRownames = TRUE,
  newSuff = c(".x", ".y"),
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)

```

Arguments

dat1	matrix or data.frame for fusing
dat2	matrix or data.frame for fusing
selCols	will be used to define columns to be used; optionally may be different for 'dat2' : define in 'supCols2'
supCols2	if additional column-names should be extracted form dat2
byC	(character) 'by' value used in merge
useAll	(logical) use all lines (will produce NAs when given identifier not found un 2nd group of data)
setRownames	(logical) if TRUE, will use values of col used as 'by' as rownames instead of showing as add'l col in output

newSuff (character) prefix (argument 'suffixes' in merge)
 silent (logical) suppress messages
 debug (logical) display additional messages for debugging
 callFrom (character) allow easier tracking of messages produced

Value

This function returns a data.frame containing the merged columns

See Also

[merge](#), merge 3 data.frames using [mergeSelCol3](#)

Examples

```
mat1 <- matrix(c(1:7, letters[1:7], 11:17), ncol=3, dimnames=list(LETTERS[1:7], c("x1", "x2", "x3")))
mat2 <- matrix(c(1:6, c("b", "a", "e", "f", "g", "k"), 31:36),
              ncol=3, dimnames=list(LETTERS[11:16], c("y1", "x2", "x3")))
mergeSelCol(mat1, mat2, selC=c("x2", "x3"))
```

mergeSelCol3

mergeSelCol3

Description

successive merge of selected columns out of 3 matrix or data.frames. 'selCols' will be used to define columns to be used; optionally may be different for 'dat2' : define in 'supCols2'. Output-cols will get additions specified in newSuff (default '.x' and '.y')

Usage

```
mergeSelCol3(
  dat1,
  dat2,
  dat3,
  selCols,
  supCols2 = NULL,
  supCols3 = NULL,
  byC = NULL,
  useAll = FALSE,
  setRownames = TRUE,
  newSuff = c(".x", ".y", ".z"),
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat1	matrix or data.frame for fusing
dat2	matrix or data.frame for fusing
dat3	matrix or data.frame for fusing
selCols	will be used to define columns to be used; optionally may be different for 'dat2' : define in 'supCols2'
supCols2	if additional column-names should be extracted form dat2
supCols3	if additional column-names should be extracted form dat3
byC	(character) 'by' value used in merge
useAll	(logical) use all lines (will produce NAs when given identifier not found un 2nd group of data)
setRownames	if TRUE, will use values of col used as 'by' as rownames instead of showing as add'l col in output
newSuff	(character) prefix (argument 'suffixes' in merge)
silent	(logical) suppress messages
debug	(logical) display additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a data.frame containing the merged columns

See Also

[merge](#), [mergeSelCol](#)

Examples

```
mat1 <- matrix(c(1:7, letters[1:7]), 11:17, ncol=3, dimnames=list(LETTERS[1:7], c("x1", "x2", "x3")))
mat2 <- matrix(c(1:6, c("b", "a", "e", "f", "g", "k")), 31:36, ncol=3,
  dimnames=list(LETTERS[11:16], c("y1", "x2", "x3")))
mat3 <- matrix(c(1:6, c("c", "a", "e", "b", "g", "k")), 51:56, ncol=3,
  dimnames=list(LETTERS[11:16], c("z1", "x2", "x3")))
mergeSelCol3(mat1, mat2, mat3, selC=c("x2", "x3"))
```

mergeVectors

Merge Named Vectors

Description

This function allows merging for multiple named vectors (each element needs to be named). Basically, all elements carrying the same name across different input-vectors will be aligned in the same column of the output (input-vectors appear as lines). If vectors are not given using a name (see first example below), they will be names 'x.1' etc (see argument namePrefix).

Usage

```
mergeVectors(
  ...,
  namePrefix = "x.",
  NAto0 = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

...	all vectors that need to be merged
namePrefix	(character) prefix to numers used when vectors are not given with explicit names (second exaample)
NAto0	(logical) optional replacemet of NAs by 0
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

Note : The arguments 'namePrefix', 'NAto0', 'callFrom' and 'silent' must be given with full name to be recognized as such (and not get considered as vector for merging).

Value

This function returns a matrix of merged values

See Also

[merge](#) (for two data.frames)

Examples

```
x1 <- c(a=1, b=11, c=21)
x2 <- c(b=12, c=22, a=2)
x3 <- c(a=3, d=43)
mergeVectors(vect1=x1, vect2=x2, vect3=x3)
x4 <- 41:44 # no names - not conform for merging
mergeVectors(x1, x2, x3, x4)
```

mergeW2	<i>Extended version of merge for multiple objects (even without row-names)</i>
---------	--

Description

mergeW2 provides flexible merging out of 'MArrayLM'-object (if found, won't consider any other input-data) or of separate vectors or matrixes. The main idea was to have something not adding add'l lines as merge might do, but to stay within the frame of the 1st argument given, even when IDs are repeated, so the output follows the order of the 1st argument, non-redundant IDs are created (orig IDs as new column). If no 'MArrayLM'-object found: try to combine all elements of input '...', input-names must match predefined variants 'chInp'. IDs given in 1st argument and not found in later arguments will be displayed as NA in the output matrix of data.frame. Note : (non-data) arguments must be given with full name (so far no lazy evaluation, may conflict with names in 'inputNamesLst'). Note : special characters in colnames bound to give trouble. Note : when no names given, mergeW2 will presume order of elements (names) from 'inputNamesLst'. PROBLEM : error after xxMerg3 when several entries have matching (row)names but some entries match only partially (what to do : replace with NAs ??)

Usage

```
mergeW2(
  ...,
  nonRedundID = TRUE,
  convertDF = TRUE,
  selMerg = TRUE,
  inputNamesLst = NULL,
  noMatchPursue = TRUE,
  standColNa = FALSE,
  lastOfMultCols = c("p.value", "Lfdr"),
  duplTxtSep = "_",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

...	all data (vectors, matrixes or data.frames) intended for merge
nonRedundID	(logical) if TRUE, always add 1st column with non-redundant IDs (add anyway if non-redundant IDs found)
convertDF	(logical) allows converting output in data.frame, add new heading col with non-red rownames & check which cols should be numeric
selMerg	(logical) if FALSE toggle to classic merge() (will give more rows in output in case of redundant names)

inputNamesLst	(list) named list with character vectors (should be unique), search these names in input for extracting/merging elements use for 'lazy matching' when checking names of input, default : 7 groups ('Mvalue', 'Avalue', 'p.value', 'mouseInfo', 'Lfdr', 'link', 'filt') with common short versions
noMatchPursue	(logical) allows using entries where 0 names match (just as if no names given)
standColNa	(logical) if TRUE return standard colnames as defined in 'inputNamesLst' (ie 'chInp'), otherwise colnames as initially provided
lastOfMultCols	may specify input groups where only last col will be used/extracted
duplTxtSep	(character) separator for counting/denominating multiple occurances of same name
silent	(logical) suppress messages
debug	(logical) for bug-tracking: more/enhanced messages and intermediate objects written in global name-space
callFrom	(character) allows easier tracking of message(s) produced

Value

matrix or data.frame of fused data

See Also

[merge](#)

Examples

```
t1 <- 1:10; names(t1) <- letters[c(1:7,3:4,8)]
t2 <- 20:11; names(t2) <- letters[c(1:7,3:4,8)]
t3 <- 101:110; names(t3) <- letters[c(11:20)]
t4 <- matrix(100:81, ncol=2, dimnames=list(letters[1:10], c("co1", "co2")))
t5 <- cbind(t1=t1, t52=t1+20, t53=t1+30)
      t1; t2; t3; cbind(t1, t2)
mergeW2(Mval=t1, p.value=t2, debug=FALSE)
```

minDiff

Minimum distance/difference between values

Description

This function aims to find the min distance (ie closest point) to any other x (numeric value), ie intra 'x' and returns matrix with 'index', 'value', 'dif', 'ppm', 'ncur', 'nbest', 'best'. At equal distance to lower & upper neighbour point, the upper (following) point is chosen (as single best). In case of multiple ex-aequo distance returns 1st of multiple, may be different at various repeats.

Usage

```
minDiff(
  x,
  digSig = 3,
  ppm = TRUE,
  initOrder = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	(numeric) vector to search minimum difference
digSig	number of significant digits, used for ratio or ppm column
ppm	(logical) display distance as ppm ($1e6 * \text{diff} / \text{refValue}$, ie normalized difference eg as used in mass spectrometry), otherwise the ratio is given as : value(from 'x') / closestValue (from 'x')
initOrder	(logical) return matrix so that 'x' matches exactly 2nd col of output
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a matrix

See Also

[diff](#)

Examples

```
set.seed(2017); aa <- 100*c(0.1 +round(runif(20),2),0.53,0.53)
minDiff(aa);
minDiff(aa,init0=TRUE,ppm=FALSE); .minDif(unique(aa))
```

moderTest2grp

Moderated Pairwise t-test From Limma

Description

This function runs moderated t-test from package `limma` on each line of data. Note: This function requires the package `limma` from bioconductor being installed. The `limma` contrast-matrix has to be read by column, the lines in the contrast-matrix containing '+1' will be compared to the '-1' lines, eg `grpA-grpB`. Local false discovery rates (l_{fdr}) estimations will be made using the CRAN-package `fdrtool` (if available).

Usage

```
moderTest2grp(
  dat,
  grp,
  limmaOutput = TRUE,
  addResults = c("lfd", "FDR", "Mval", "means"),
  testOrientation = "=",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	matrix or data.frame with rows for multiple (independent) tests, use ONLY with 2 groups; assumed as log2-data
grp	(factor) describes column-relationship of 'dat' (1st factor is considered as reference -> orientation of M-values !!)
limmaOutput	(logical) return full (or extended) MArrayLM-object from limma or 'FALSE' for only the (uncorrected) p.values
addResults	(character) types of results to add besides basic limma-output, data are assumed to be log2 ! (eg "lfd" using fdrtool-package, "FDR" or "BH" for BH-FDR, "BY" for BY-FDR, "bonferroni" for Bonferroni-correction, "qValue" for lfd by qvalue, "Mval", "means" or "nonMod" for non-moderated test and the equivalent all (other) multiple testing corrections chosen here)
testOrientation	(character) for one-sided test (">","greater" or "<","less"), NOTE : 2nd grp is considered control/reference, '<' will identify grp1 < grp2
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a limma-type object of class MArrayLM (which can be handled like a list)

See Also

[lmFit](#) and the eBayes-family of functions in package [limma](#), [p.adjust](#)

Examples

```
set.seed(2017); t8 <- matrix(round(rnorm(1520,10,0.4),2), ncol=8,
  dimnames=list(paste("l",1:190),c("AA1","BB1","CC1","DD1","AA2","BB2","CC2","DD2")))
t8[3:6,1:2] <- t8[3:6,1:2] +3      # augment lines 3:6 for AA1&BB1
t8[5:8,5:6] <- t8[5:8,5:6] +3    # augment lines 5:8 for AA2&BB2 (c,d,g,h should be found)
t4 <- log2(t8[,1:4]/t8[,5:8])
```

```
## Two-sided testing
fit4 <- moderTest2grp(t4,gl(2,2))
# If you have limma installed we can now see further
if(requireNamespace("limma")) {
  limma::topTable(fit4, coef=1, n=5) # effect for 3,4,7,8

## One-sided testing
fit4in <- moderTest2grp(t4,gl(2,2), test0="<")
# If you have limma installed we can now see further
if(requireNamespace("limma")) {
  limma::topTable(fit4in, coef=1, n=5) }
```

moderTestXgrp

Multiple Moderated Pairwise t-tests From limma

Description

This function runs (selected or all) pairwise combinations of moderated t-tests from package 'limma' on each line of data against. Note: This function requires the package **limma** from bioconductor. The limma contrast-matrix has to be read by column, the lines in the contrast-matrix containing '+1' will be compared to the '-1' lines, eg grpA-grpB .

Usage

```
moderTestXgrp(
  dat,
  grp,
  useComparison = NULL,
  limmaOutput = TRUE,
  addResults = c("lfd", "FDR", "Mval", "means"),
  testOrientation = "=",
  sep = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	matrix or data.frame with rows for multiple (independent) tests, use ONLY with 2 groups; assumed as log2-data !!!
grp	(factor) describes column-relationship of 'dat' (1st factor is considered as reference -> orientation of M-values !!)
useComparison	(numeric, character or matrix) optional way to indicate which pairwise comparisons should be performed : if useComparison="all" all pairwise comparisons possible will be performed, otherwise pairwise comparisons may be chosen using indexes (the ith instance of all possible pairwise comparisons); a character

vector citing the concatenated levels of argument grp; may be used (in this case it may be necessary to specify the separator used in argument argument sep ; please note, it is important to check that a custom selected separator sep does not occur inside the groups from grp); finally, the argument useComparison may be or as matrix of 2 columns where each row specifies a different comparison, the matrix mat contain the names of the levels of argument grp or an index relative to the levels of argument grp; In all cases where 2 groups are specified this will be read as 'sample-reference' - thus, the 2nd entity will be taken as reference; Of course this separator should not occur in 'grp' (if present it will be automatically repaced by '___' in 'grp').

limmaOutput	(logical) return full (or extended) MArrayLM-object from limma or 'FALSE' for only the (uncorrected) p.values
addResults	(character) types of results to add besides basic limma-output, data are assumed to be log2 ! (eg "lfd" using fdrtool-package, "FDR" or "BH" for BH-FDR, "BY" for BY-FDR, "bonferroni" for Bonferroni-correction, "qValue" for lfd by qvalue, "Mval", "means" or "nonMod" for non-moderated test and he equivalent all (other) multiple testing corrections chosen here)
testOrientation	(character) for one-sided test (">","greater" or "<","less"), NOTE : 2nd grp is considered control/reference, '<' will identify grp1 < grp2
sep	(NULL] or character of length=1) optional custom choice for separator for column-names of pairwise comparisons, otherwise determined as character(-set) not occurring in grp
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

When multiple pairwise comparisons will be run, first a global linear model will be estimated and the particular pairwise comparisons will then be performed using a contrast-matrix. This process is described with the bioconductor package [limma](#) which is used underneath.

By default (useComparison=NULL), the first of all possible pairwise comparisons will be run. If you would like to run all comparisons, please set useComparison="all". Besides, it is also possible to custom choose which comparisons should be run (and which order of sample/reference) via the argument useComparison using the character vector '-' as separator for the two groups of samples (referring to argument grp) to be compared. This will be interpreted as 'sample-reference' (additional space around the separator, if present, will be removed), thus the second element will be used as reference. Furthermore, the argument useComparison may be a matrix of 2 columns (for sample and reference) where each line represents a pairwise comparison that should be run.

As effort for compatibility to previous versions and compatibility to standard writing in limma the group-separator '-' in useComparison has limited support : This (single character) separator will be internally converted to ' - ' and in absence of ' - ' in argument grp, output will have the initial (single character) separator '-'.

Concerning the separator used when reporting results for pairwise comparisons : If argument grp contains any '-', comparisons of groups will always (!) get reported using ' - ' as separator to avoid

any confusion. In case useComparison is a matrix, the reported comparisons will have '-' if grp does not contain as well any '-', otherwise '-' will be used (to support compatibility with results from limma).

Please note, that in the output of this function the Benjamini-Hochberg (BH) adjusted p-values are called 'FDR' (see argument addResults).

the output contains a list-element named setup summarizing the global setup as captured (names of groups of samples), including the names of the pairwise combinations that were tested.

Value

This function returns a limma-type MA-object (which can be handled like a list), or when problems are encountered NULL

See Also

[moderTest2grp](#) for simplified single comparisons (with fewer options/flexibility), [lmFit](#) and the eBayes-family of functions in package [limma](#)

Examples

```
grp3 <- factor(rep(LETTERS[c(3,1,4)],c(2,3,3)))
set.seed(2017); t8 <- matrix(round(rnorm(208*8,10,0.4),2), ncol=8,
  dimnames=list(paste(letters[],rep(1:8,each=26),sep=""), paste0(grp3, c(1:2,1:3,1:3))))
t8[3:6,1:2] <- t8[3:6,1:2] +3 # augment lines 3:6 (c-f)
t8[5:8,c(1:2,6:8)] <- t8[5:8,c(1:2,6:8)] -1.5 # lower lines
t8[6:7,3:5] <- t8[6:7,3:5] +2.2 # augment lines
## expect to find C/A in c,d,g, (h)
## expect to find C/D in c,d,e,f
## expect to find A/D in f,g,(h)
test8 <- moderTestXgrp(t8, grp3)

## Custom choice of what to compare
test8b <- moderTestXgrp(t8, grp3, useComparison=c("D-A","C-A"))
head(test8b$FDR)
head(test8b$Mval)

## Custom choice as matrix
comp4 <- matrix(LETTERS[c(4,3,3,1)], ncol=2)
test4 <- moderTestXgrp(t8, grp3, useComparison=comp4)

## Names of pairwise comparisons performed
test4$setup$concat

## One can also use functions from package limma to see more
library(limma)
topTable(test8b, n=5)
```

multiCharReplace	<i>Multiple replacement of entire character elements in simple vector, matrix or data.frame</i>
------------------	---

Description

This functions allows multiple types of replacements of entire character elements in simple vector, matrix or data.frame. In addition, the result may be optionally directly transformed to logical or numeric

Usage

```
multiCharReplace(
  mat,
  repl,
  convTo = NULL,
  silent = FALSE,
  debug = TRUE,
  callFrom = NULL
)
```

Arguments

mat	(character vector, matrix or data.frame) main data
repl	(matrix or list) tells what to replace by what: If matrix the 1st oolumn will be considered as 'old' and the 2nd as 'replaceBy'; if named list, the names of the list-elements will be considered as 'replaceBy'
convTo	(character) optional conversion of content to 'numeric' or 'logical'
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns an object of same dimension as input (with replaced content)

See Also

[grep](#)

Examples

```
x1 <- c("ab", "bc", "cd", "efg", "ghj")
multiCharReplace(x1, cbind(old=c("bc", "efg"), new=c("BBCC", "EF")))

x2 <- c("High", "n/a", "High", "High", "Low")
```

```
multiCharReplace(x2, cbind(old=c("n/a", "Low", "High"), new=c(NA, FALSE, TRUE)), convTo="logical")

# works also to replace numeric content :
x3 <- matrix(11:16, ncol=2)
multiCharReplace(x3, cbind(12:13, 112:113))
```

multiMatch

Simple Multi-to-Multi Matching of (Concatenated) Terms

Description

This function allows convenient matching of multi-to-multi relationships between two objects/vectors. It was designed for finding common elements in multiple to multiple matching situations (eg when comparing c("aa; bb", "cc") to c("bb; ab", "dd"), ie to find 'bb' as matching between both objects).

Usage

```
multiMatch(
  x,
  y,
  sep = "; ",
  sep2 = NULL,
  method = "byX",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	(vector or list) first object to compare; if vector, the (partially) concatenated identifiers (will be split using separator sep), or list of items to be matched (ie already split)
y	(vector or list) second object to compare; if vector, the (partially) concatenated identifiers (will be split using separator sep), or list of items to be matched (ie already split)
sep	(character, length=1) separator used to split concatenated identifiers (if x or y is vector)
sep2	(character, length=1) optional separator used when method="matched" to concatenate all indexes of y for column y.allInd
method	(character) mode of operation: 'asIndex' to return index of y (those who have matches) with names of x (which x are the corresponding match)
silent	(logical) suppress messages
debug	(logical) display additional messages for debugging
callFrom	(character) allow easier tracking of message(s) produced

Details

method='byX' .. returns data.frame with view oriented towards entries of x: character column x for entire content of x; integer column x.Ind for index of x; character column TagBest for most frequent matching isolated tag/ID; integer column y.IndBest index of most frequent matching y; character column y.IndAll index for all y matching any of the tags; character column y.Match for entire content of best matching y; character column y.Adj for y adjusted to best matching y for easier subsequent perfect matching.

method=c("byX", "filter") .. combined argument to keep only lines with any matches

method='byTag' .. returns matrix (of integers) from view of isolated tags from x (a separate line for each tag from x matching to y);

method=c("byTag", "filter") ..if combined as arguments, this will return a data.frame for all unique tags with any matches between x and y, with additional columns x.AllInd for all matching x-indexes, y.IndBest best matching y index; x.n for number of different x containing this tag; y.AllInd for all matching y-indexes

method='adjustXtoY' .. returns vector with x adjusted to y, ie those elements of x matching are replace by the exact corresponding term of y.

method=NULL .. If no term matching the options shown above is given, another version of 'asIndex' is returned, but indexes to y _after_ splitting by sep. Again, this method can be filtered by using method="filter" to focus on the best matches to x.

Value

matrix, data.frame or list with matching results depending on method chosen

See Also

[match](#); [strsplit](#)

Examples

```
aa <- c("m","k", "j; aa", "m; aa; bb; o; ee", "n; dd; cc", "aa", "cc")
bb <- c("dd; r", "aa", "ee; bb; q; cc", "p; cc")
(match1 <- multiMatch(aa, bb, method=NULL))      # match bb to aa
(match2 <- multiMatch(aa, bb, method="byX"))     # match bb to aa
(match3 <- multiMatch(aa, bb, method="byTag"))   # match bb to aa
(match4 <- multiMatch(aa, bb, method=c("byTag","filter")) # match bb to aa
```

Description

This function removes NAs from input vector, in contrast to `na.omit` this function has no slot for removed elements.

Usage

```
naOmit(x, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

x (vector or matrix) data to check & remove NAs
 silent (logical) suppress messages if TRUE
 debug (logical) additional messages for debugging
 callFrom (character) allows easier tracking of messages produced

Details

Resulting objects from naOmit are smaller in size and subsequent code execution (on large vectors) may be faster (in particular if many NAs get encountered). Note : This function behaves differently to na.omit with input other than plain vectors. Will not work with data.frames !

Value

This function returns a vector without NAs (matrix input will be transformed to vector). Returns NULL if input consists only of NAs.

See Also

[na.fail](#), [na.omit](#)

Examples

```
aA <- c(11:13,NA,10,NA);
naOmit(aA)
```

nFragments	<i>Number Of Fragments After Cut At Specific Character(s) Within Size-range</i>
------------	---

Description

This function determines number of fragments /entry within range of 'sizeRa' (numeric,length=2) when cutting after 'cutAt'

Usage

```
nFragments(
  protSeq,
  cutAt,
  sizeRa,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

protSeq	(character) text to be cut
cutAt	(character) position to cut
sizeRa	(numeric,length=2) min and max size to consider
silent	(logical) suppress messages if TRUE
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a numeric vector with number of fragments for each entry 'protSeq' (names are 'protSeq')

See Also

[cutAtMultSites](#), simple version {nFragments0} (no size-range)

Examples

```
tmp <- "MSVSREDSCELDLVYVTERIIAVSFPSTANEENFRSNLREVAQMLKSKHGGNYLLFNLSERRPDITKLHAKVLEFGWPDLHTPALEKI"
nFragments(c(tmp,"ojioRij"),c("R","K"),c(4,31))
```

nFragments0	<i>Number Of Fragments After Cut At Specific Character(s)</i>
-------------	---

Description

This function tells the number of fragments/entry when cutting after 'cutAt'

Usage

```
nFragments0(protSeq, cutAt, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

protSeq	(character) text to be cut
cutAt	(integer) position to cut
silent	(logical) suppress messages if TRUE
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a numeric vector with number of fragments for each entry 'protSeq' (names are 'protSeq')

See Also

more elaborate {nFragments}; [cutAtMultSites](#)

Examples

```
tmp <- "MSVSRTMEDSCELDLVYVTERIIAVSFPSTANEENFRSNLREVAQMLKSKHGGNYLLFNLSERRPDITKLHAKVLEFGWPDHLHTPALEKI"
nFragments0(c(tmp,"ojioRij"),c("R","K"))
```

nNonNumChar	<i>Count number of non-numeric characters</i>
-------------	---

Description

nNonNumChar counts number of non-numeric characters. Made for positive non-scientific values (eg won't count neg-sign, neither Euro comma ',')

Usage

```
nNonNumChar(txt)
```

Arguments

txt character vector to be treated

Value

This function returns a numeric vector with numer of non-numeric characters (ie not '.' or 0-9)

See Also

[nchar](#)

Examples

```
nNonNumChar("a1b "); sapply(c("aa","12ab","a1b2","12","0.5"), nNonNumChar)
```

nonAmbiguousMat	<i>Transform matrix to non-ambiguous matrix (in respect to given column)</i>
-----------------	--

Description

nonAmbiguousMat makes values of matrix 'mat' in col 'byCol' unique.

Usage

```
nonAmbiguousMat(
  mat,
  byCol,
  uniqOnly = FALSE,
  asList = FALSE,
  nameMod = "amb_",
  silent = TRUE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

mat	numeric or character matrix (or data.frame), column specified by 'byCol' must be/will be used as.numeric, 1st column of 'mat' will be considered like index & used for adding prefix 'nameMod' (unless byCol=1, then 2nd col will be used)
byCol	(character or integer-index) column by which ambiguity will be tested
uniqOnly	(logical) if =TRUE return unique only, if =FALSE return unique and single representative of non-unique values (with " added to name), selection of representative of repeated: first (of sorted) or middle if >2 instances
asList	(logical) return result as list
nameMod	(character) prefix added to 1st column of 'mat' (expect 'by') for indicating non-unique/ambiguous values
silent	(logical) suppress messages
debug	(logical) for bug-tracking: more/enhanced messages and intermediate objects written in global name-space
callFrom	(character) allows easier tracking of message(s) produced

Value

sorted non-ambiguous numeric vector (or list if 'asList'=TRUE and 'uniqOnly'=FALSE)

See Also

for non-numeric use [firstOfRepeated](#) - but 1000x much slower !; [get1stOfRepeatedByCol](#)

Examples

```
set.seed(2017); mat2 <- matrix(c(1:100,round(rnorm(200),2)),ncol=3,
  dimnames=list(1:100,LETTERS[1:3]));
head(mat2U <- nonAmbiguousMat(mat2,by="B",na="_",uniq0=FALSE),n=15)
head(get1stOfRepeatedByCol(mat2,sortB="B",sortS="B"))
```

nonAmbiguousNum	<i>Make numeric vector non-ambiguous (ie unique)</i>
-----------------	--

Description

This function transforms a vector of (named) numeric values *x* into unique. Note: for non-numeric use the function [firstOfRepeated](#) - but 1000x slower ! Return sorted non-ambiguous numeric vector (or list if 'asList'=TRUE and 'uniqOnly'=FALSE)

Usage

```
nonAmbiguousNum(
  x,
  uniqOnly = FALSE,
  asList = FALSE,
  nameMod = "amb_",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<i>x</i>	(numeric) main input
<i>uniqOnly</i>	(logical) if=TRUE return unique only, if =FALSE return unique and single representative of non-unique values (with " added to name), selection of representative of repeated: first (of sorted) or middle if >2 instances
<i>asList</i>	(logical) return list
<i>nameMod</i>	(character) text to add in case on ambiguous values, default="amb_"
<i>silent</i>	(logical) suppress messages
<i>debug</i>	(logical) additional messages for debugging
<i>callFrom</i>	(character) allows easier tracking of messages produced

Value

sorted non-ambiguous numeric vector (or list if 'asList'=TRUE and 'uniqOnly'=FALSE)

See Also

[firstOfRepeated](#) for non-numeric use (much slower !!!), [duplicated](#)

Examples

```
set.seed(2017); aa <- round(rnorm(100),2); names(aa) <- 1:length(aa)
str(nonAmbiguousNum(aa))
str(nonAmbiguousNum(aa,uniq=FALSE,asLi=TRUE))
```

nonredDataFrame *Filter for unique elements*

Description

nonredDataFrame filters 'x' (list of char-vectors or char-vector) for elements unique (to 'ref' or if NULL to all 'x') and of character length. May be used for different 'accession' for same pep sequence (same 'peptide_id'). Note : made for treating data.frames, may be slightly slower than matrix equivalent

Usage

```
nonredDataFrame(
  dataFr,
  useCol = c(pepID = "peptide_id", protID = "accession", seq = "sequence", mod =
    "modifications"),
  sepCollapse = "//",
  callFrom = NULL
)
```

Arguments

dataFr	(data.frame) main input
useCol	(character,length=2) column names of 'dataFr' to use : 1st value designates where redundant values should be gathered; 2nd value designates column of which information should be concatenated
sepCollapse	(character) concatenation symbol
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a data.frame of filtered (fewer lines) with additional 2 columns 'nSamePep' (number of redundant entries) and 'concID' (concatenated content)

See Also

[combineRedBasedOnCol](#), [correctToUnique](#), [unique](#)

Examples

```
df1 <- data.frame(cbind(xA=letters[1:5], xB=c("h","h","f","e","f"), xC=LETTERS[1:5]))
nonredDataFrame(df1, useCol=c("xB","xC"))
```

nonRedundLines	<i>Non-Redundant Lines Of Matrix</i>
----------------	--------------------------------------

Description

This function reduces complexity of matrix (or data.frame) if multiple consecutive (!) lines with same values. Return matrix (or data.frame) without repeated lines (keep 1st occurrence)

Usage

```
nonRedundLines(dat, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

dat	(matrix or data.frame) main input
silent	(logical) suppress messages if TRUE
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a matrix (or data.frame) without repeated lines (keep 1st occurrence)..

See Also

[firstLineOfDat](#), [firstOfRepLines](#), [findRepeated](#), [firstOfRepeated](#), [get1stOfRepeatedByCol](#), [combineRedBasedOnCol](#), [correctToUnique](#)

Examples

```
mat2 <- matrix(rep(c(1,1:3,3,1),2),ncol=2,dimnames=list(letters[1:6],LETTERS[1:2]))
nonRedundLines(mat2)
```

normalizeThis	<i>Normalize Data In Various Modes</i>
---------------	--

Description

Generic normalization of 'dat' (by columns), multiple methods may be applied. The choice of normalization procedures must be done with care, plotting the data before and after normalization may be critical to understanding the initial data structure and the effect of the procedure applied. Inappropriate methods chosen may render interpretation of (further) results incorrect.

Usage

```
normalizeThis(
  dat,
  method = c("mean", "average", "median", "trimMean", "rowNormalize", "standardize",
    "slope", "twoPointSlope", "exponent", "vsn", "none", "NULL"),
  refLines = NULL,
  refGrp = NULL,
  mode = c("proportional", "additive", "linear", "lin", "logarithmic", "log"),
  trimFa = NULL,
  minQuant = NULL,
  sparseLim = 0.4,
  nCombin = 3,
  omitNonAlignable = FALSE,
  maxFact = 10,
  quantFa = NULL,
  expFa = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	matrix or data.frame of data to get normalized
method	(character) may be "mean","median","NULL","none", "trimMean", "rowNormalize", "slope", "exponent", "twoPointSlope", "vsn"; When NULL or 'none' is chosen the input will be returned
refLines	(NULL or numeric) allows to consider only specific lines of 'dat' when determining normalization factors (all data will be normalized)
refGrp	Only the columns indicated will be used as reference, default all columns (integer or colnames)
mode	(character) may be "proportional", "additive" (for log2 data); decide if normalization factors will be applied as multiplicative (proportional) or additive; for log2-omics data mode="additive" is suggested besides 'log' or 'logarithmic' may be used instead of 'additive'; and 'lin' or 'linear' may be used instead of 'proportional'
trimFa	(numeric, length=1) additional parameters for trimmed mean
minQuant	(numeric) only used with method='rowNormalize': optional filter to set all values below given value as NA; see also rowNormalize
sparseLim	(integer) only used with method='rowNormalize': decide at which min content of NA values the function should go in sparse-mode; see also rowNormalize
nCombin	(NULL or integer) only used with method='rowNormalize': used only in sparse-mode (ie if content of NAs higher than content of sparseLim): Number of groups of smaller matrixes with this number of columns to be inspected initially; low values (small groups have higher chances of more common elements); see also rowNormalize

omitNonAlignable	(logical) only used with method='rowNormalize': allow omitting all columns which can't get aligned due to sparseness; see also rowNormalize
maxFact	(numeric, length=2) only used with method='rowNormalize': max normalization factor; see also rowNormalize
quantFa	(numeric, length=2) additional parameters for quantiles to use with method='slope'
expFa	(numeric, length=1) additional parameters for method='exponent'
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Details

In most cases of treating 'Omics'-data one works with the hypothesis that there are no global changes in the structure of all data/columns Under this hypothesis it is very common to assume the the median (via the argument method) of all samples (ie columns) should remain constant. For examples samples/columns with less signal will be considered as having received 'accidentally' less material (eg due to the imprecision when transferring very small amounts of liquid samples). In consequence, a sample having received only 95 Thus, all measures will be multiplied by 1/0.95 (apr 1.053) to compensate for supposed lack of staring material.

LOG-SCALE : With the analysis of 'Omics'-data it is very common to work with data on log-scale. In this case the argument mode should be set to additive (or log or logarithmic). At normalization a constant factor will be added (or subtracted) using this mode. This corresponds to a multiplicative factor on regular scale. Please note that (at this point) the methods 'slope', 'exponent', 'twoPointSlope' and 'vsn' don't distinguish between additive and proportional modes, but take the data 'as is' (you may look at the original documentation for more details, see [exponNormalize](#), [scaleXY](#) or [adjBy2ptReg](#), [justvsn](#)).

Normalization using method="rowNormalize" runs [rowNormalize](#) from this package. In this case, the working hypothesis is, that all values in each row are expected to be the same. This method could be applied when all series of values (ie columns) are replicate measurements of the same sample. There is also an option for treating sparse data (see argument sparseLim), which may, however, consume much more computational resources, in particular, when the value nCombin is low (compared to the number of samples/columns).

Normalization using method="standardize" runs [scale](#) resulting in a matrix where column-means are set to 0 (or very close to 0) and sd et 1, standardization by columns. With this method additive or proportional mode give the same output. Results from this method should be interpreted with caution, since the absolute values are not any more considered. Therefor this approach is rather oriented for comparing profiles (no matter how important changes are on an absolute scale)

Normalization using method="vsn" runs [justvsn](#) from [vsn](#) (this requires a minimum of 42 rows of input-data and having the Bioconductor package vsn installed). Note : Depending on the procedure chosen, the normalized data may appear on a different scale.

Value

This function returns a matrix of normalized data (same dimensions as input)

See Also

[rowNormalize](#), [exponNormalize](#), [scaleXY](#), [adjBy2ptReg](#), [justvsn](#)

Examples

```
set.seed(2015); rand1 <- round(runif(300)+rnorm(300,0,2),3)
dat1 <- cbind(ser1=round(100:1+rand1[1:100]), ser2=round(1.2*(100:1+rand1[101:200])-2),
  ser3=round((100:1 +rand1[201:300])^1.2-3))
dat1 <- cbind(dat1, ser4=round(dat1[,1]^seq(2,5,length.out=100)+rand1[11:110],1))
dat1[dat1 <1] <- NA
summary(dat1)
dat1[c(1:5,50:54,95:100),]
no1 <- normalizeThis(dat1, refGrp=1:3, meth="mean")
no2 <- normalizeThis(dat1, refGrp=1:3, meth="trimMean", trim=0.4)
no3 <- normalizeThis(dat1, refGrp=1:3, meth="median")
no4 <- normalizeThis(dat1, refGrp=1:3, meth="slope", quantFa=c(0.2,0.8))
dat1[c(1:10,91:100),]
cor(dat1[,3],rowMeans(dat1[,1:2],na.rm=TRUE), use="complete.obs") # high
cor(dat1[,4],rowMeans(dat1[,1:2],na.rm=TRUE), use="complete.obs") # bad
cor(dat1[c(1:10,91:100),4],rowMeans(dat1[c(1:10,91:100),1:2],na.rm=TRUE),use="complete.obs")
cor(dat1[,3],rowMeans(dat1[,1:2],na.rm=TRUE)^(1/seq(2,5,length.out=100)),use="complete.obs")
```

numPairDeColNames	<i>Extract pair of numeric values from vector or column-names</i>
-------------------	---

Description

This function extracts a pair of numeric values out of a vector or colnames (from a matrix). This is useful when pairwise comparisons are concatenated like '10c-100c', return matrix with 'index'=selComp, log2rat and both numeric. Additional white space or character text can be removed via the argument stripTxt. Of course, the separator sep needs to be specified and should not be included to 'stripTxt'.

Usage

```
numPairDeColNames(
  dat,
  selComp = NULL,
  stripTxt = NULL,
  sep = "-",
  columLabel = "conc",
  sortByAbsRatio = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	(matrix or data.frame) main input
selComp	(character) the column index selected
stripTxt	(character, max length=2) text to ignore, if NULL heading letter and punctuation characters will be removed; default will remove all letters (and following spaces)
sep	(character, length=1) separator between pair of numeric values to extract
columnLabel	(character) column labels in output
sortByAbsRatio	(logical) optional sorting of output by (absolute) log-ratios (most extreme ratios on top)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a matrix

See Also

[strsplit](#) and help on regex

Examples

```
## composed column names
mat1 <- matrix(1:8, nrow=2, dimnames=list(NULL, paste0(1:4,"-",6:9)))
numPairDeColNames(mat1)
numPairDeColNames(colnames(mat1))
## works also with simple numeric column names
mat2 <- matrix(1:8, nrow=2, dimnames=list(NULL, paste0("a",6:9)))
numPairDeColNames(mat2)
```

orderMatrToRef

Order Lines of Matrix According to Reference (Character) Vector

Description

This function orders lines of matrix `mat` according to a (character) reference vector `ref`. To do so, all columns of `mat` will be considered to use the first column from left with the best (partial) matching results. This function first looks for unambiguous perfect matches, and if not found successive rounds of more elaborate partial matching will be engaged: In case of no perfect matches found, `grep` of `ref` on all columns of `mat` and/or `grep` of all columns of `mat` on `ref` (ie 'reverse `grep`') will be applied (finally a 'two way `grep`' approach). Until a perfect match is found each element of `ref` will be tested on `mat` and inversely (for each column) each element of `mat` will be tested on `ref`. The approach with the best number of (unique) matches will be chosen. In case of one-to-many matches, it will be tried to use most complete lines (see also last example).

Usage

```
orderMatrToRef(
  mat,
  ref,
  addRef = TRUE,
  listReturn = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

mat	(matrix, data.frame) main input of which rows should get re-ordered according to a (character) reference vector ref
ref	(character) reference imposing new order
addRef	(logical) add ref to output as new column
listReturn	(logical) allows retrieving more information in form of list
silent	(logical) suppress messages
debug	(logical) display additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns, depending on `listReturn`, either the input-matrix in new order or a list with `$mat` (the input matrix in new order), `$grep` (matched matrix) and `$col` indicating the column of `mat` finally used

See Also

for basic ordering see [match](#); [checkGrpOrder](#) for testing each line for expected order, [checkStrictOrder](#) to check for strict (ascending or descending) order

Examples

```
mat1 <- matrix(paste0("__", letters[rep(c(1,1,2,2,3),3) + rep(0:2, each=5)]), rep(1:5)), ncol=3)
orderMatrToRef(mat1, paste0(letters[c(3,4,5,3,4)], c(1,3,5,2,4)))

mat2 <- matrix(paste0("__", letters[rep(c(1,1,2,2,3),3) + rep(0:2, each=5)]),
  c(rep(1:5,2), 1,1,3:5 )), ncol=3)
orderMatrToRef(mat2, paste0(letters[c(3,4,5,3,4)], c(1,3,5,1,4)))

mat3 <- matrix(paste0(letters[rep(c(1,1,2,2,3),3) + rep(0:2, each=5)]),
  c(rep(1:5,2), 1,1,3,3,5 )), ncol=3)
orderMatrToRef(mat3, paste0("__", letters[c(3,4,5,3,4)], c(1,3,5,1,3)))
```

organizeAsListOfRepl *(re)organize data of (3-dim) array as list of replicates*

Description

Organize array of all data ('arrIn', long table) into list of (replicate-)arrays (of similar type/layout) based on dimension number 'byDim' of 'arrIn' (eg 2nd or 3rd dim). Argument inspNChar defines the number of characters to consider, so if the beginning of names is the same they will be separated as list of multiple arrays. Default will search for '_' separator or trim from end if not found in the relevant dimnames

Usage

```
organizeAsListOfRepl(
  arrIn,
  inspNChar = 0,
  byDim = 3,
  silent = TRUE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

arrIn	(array) main input
inspNChar	(integer) if inspNChar=0 the array-names (2nd dim of 'arrIn') will be cut before last '_'
byDim	(integer, length=1) dimension number along which data will be split in separate elements (considering the first inspNChar characters)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a list of arrays (typically 1st and 2nd dim for specific genes/objects, 3rd for different measures associated with)

See Also

[array](#)

Examples

```
arr1 <- array(1:24,dim=c(4,3,2),dimnames=list(c(LETTERS[1:4]),
  paste("col",1:3,sep=""), c("ch1","ch2")))
organizeAsListOfRepl(arr1)
```

packageDownloadStat *Simple Package Download Statistics From CRAN*

Description

This function allows accessing the most recent counts of package downloads available on <http://www.datasciencemeta.com/> obtaining rank quantiles and to compare (multiple) given packages to the bulk data, optionally a plot can be drawn.

Usage

```
packageDownloadStat(  
  queryPackages = c("wrMisc", "wrProteo", "cif", "bcv", "FinCovRegularization"),  
  countUrl = "http://www.datasciencemeta.com/rpackages",  
  refQuant = (1:10)/10,  
  options = c("naOmit", "sort"),  
  figure = TRUE,  
  log = "",  
  silent = FALSE,  
  callFrom = NULL,  
  debug = FALSE  
)
```

Arguments

queryPackages	(character or integer) package names of interest, if integer, n random packages will be picked by random
countUrl	(character) the url where the daily counts are available
refQuant	(numeric) add reference quantile values to output matrix
options	(character) additional settings : use 'naOmit' to remove NA-lines from output (package-names not found in 'countUrl'); 'sort' for sorting output by number of downloads
figure	(logical) decide if figure should be printed
log	(character) set count-axis of figure to linear or log-scale (by setting log="y")
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced
debug	(logical) additional messages for debugging

Details

Detailed articles on this subject have been published on R-Hub (<https://blog.r-hub.io/2020/05/11/packagerank-intro/>) and on R-bloggers (<https://www.r-bloggers.com/2020/10/a-cran-downloads-experiment/>). The task of checking the number of downloads for a given package has also been addressed by several other packages (eg dlstats, cranlogs, adjustedcranlogs).

This function only allows accessing counts as listed on the website of www.datasciencemeta.com which get updated daily. Please note, that reading all lines from the website may take a few seconds !! To get a better understanding of the counts read, reference quantiles for download-counts get added by default (see argument `refQuant`). The (optional) figure can be drawn in linear scale (default, with minor zoom to lower number of counts) or in log (necessary for proper display of the entire range of counts), by setting the argument `log="y"`.

The number of downloads counted by RStudio may not be a perfect measure for the actual usage/popularity of a given package, the articles cited above discuss this in more detail. For example, multiple downloads from the same IP or subsequent downloads of multiple (older) versions of the same package seem to get counted, too.

Value

This function returns a matrix with download counts (or NULL if the web-site can't be accessed or the query-packages are not found there)

See Also

packages [cranlogs](#) and [packageRank](#)

Examples

```
## Let's try a microscopic test-file (NOT representative for true up-to-date counts !!)
pack1 <- c("cif", "bcv", "FinCovRegularization", "wrMisc", "wrProteo")
testFi <- file.path(system.file("extdata", package="wrMisc"), "rpackagesMicro.html")
packageDownloadStat(pack1, countUrl=testFi, log="y", figure=FALSE)
## For real online counting simply use the argument countUrl in default setting
```

`pairsAsPropensMatr` *Convert Pairs of Node-Names to Non-Oriented Propensity Matrix*

Description

Numerous network query tools produce a listing of pairs of nodes (with one pair of nodes per line). Using this function such a matrix (or `data.frame`) can be combined to this more comprehensive view as propensity-matrix.

Usage

```
pairsAsPropensMatr(mat, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

<code>mat</code>	(matrix) main input, matrix of interaction partners with each line as a separate pair of nodes; the first two columns should contain identifiers of the nodes
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Details

Note, this has been primarily developed for undirected interaction networks, the resulting propensity-matrix does not show any orientation any more. In a number of applications (eg in protein-protein interaction networks, PPI) the resulting matrix may be rather sparse.

Value

This function returns matrix or data.frame

See Also

uses typically input from [filterNetw](#)

Examples

```
pairs3L <- matrix(LETTERS[c(1,3,3, 2,2,1)], ncol=2) # loop of 3
(netw13pr <- pairsAsPropensMatr(pairs3L))         # as prop matr
```

partialDist	<i>Partial distance matrix (focus on closest)</i>
-------------	---

Description

partialDist calculates distance matrix like dist for 1- or 2-dim data, but only partially, ie only cases of small distances. This function was made for treating very large data-sets where only very close distances to a given point need to be found, it allows to overcome memory-problems with larger data (and faster execution with > 50 rows of 'dat').

Usage

```
partialDist(
  dat,
  groups,
  overLap = TRUE,
  method = "euclidean",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	(matrix of numeric values) main input
groups	(factor) to split using cut or specific custom grouping (length of dat)
overLap	(logical) if TRUE make groups overlapping by 1 value (ie maintain some context-information)

method	'character' name of method passed to dist
silent	(logical) suppress messages
debug	(logical) display additional messages for debugging
callFrom	(character) allow easier tracking of message(s) produced

Value

This function returns a matrix with partial distances (not of class 'dist' object)

See Also

[dist](#)

Examples

```
set.seed(2016); mat3 <- matrix(runif(300),nr=30)
round(dist(mat3), 1)
round(partialDist(mat3, gr=3), 1)
```

partUnlist	<i>Partial unlist of lists of lists</i>
------------	---

Description

partUnlist does partial unlist for treating list of lists : New (returned) list has one level less of hierarchy (Highest level list will be appended). In case of conflicting (non-null) listnames a prefix will be added. Behaviour different to [unlist](#) when unlisting list of matrixes.

Usage

```
partUnlist(lst, sep = "_", silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

lst	(list) main input, list to be partially unlisted
sep	(character, length=1) separator for names
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a list with partially reduced nested structure

See Also

[unlist](#), [asSepList](#)

Examples

```
partUnlist(list(list(a=11:12,b=21:24), list(c=101:101,d=201:204)))
li4 <- list(c=1:3, M2=matrix(1:4,ncol=2), L3=list(L1=11:12, M3=matrix(21:26,ncol=2)))
partUnlist(li4)
unlist(li4, rec=FALSE)
```

 pasteC

Advanced paste-collapse

Description

This function is a variant of [paste](#) for convenient use of paste-collapse and separation of last element to paste (via 'lastCol'). This function was made for more human like enumerating in output and messages. If multiple arguments are given without names they will all be concatenated, if they contain names lazy evaluation for names will be tried (with preference to longest match to argument names). Note that some special characters (like backslash) may need to be protected when used with 'collapse' or 'quoteC'. Returns character vector of length 1 (everything pasted together)

Usage

```
pasteC(..., collapse = ", ", lastCol = " and ", quoteC = "")
```

Arguments

...	(character) main input to be collapsed
collapse	(character,length=1) element to use for collapsing
lastCol	(character) text to use before last item enumerated element
quoteC	character to use for citing with quotations (default "")

Value

This function returns a character vector of truncated versions of input txt

See Also

[paste](#) for basic paste

Examples

```
pasteC(1:4)
```

 presenceFilt

Filter Lines Of Matrix For Max Number Of NAs

Description

This function produces a logical matrix to be used as filter for lines of 'dat' for sufficient presence of non-NA values (ie limit number of NAs per line). Filter abundance/expression data for min number and/or ratio of non-NA values in at east 1 of multiple groups. This type of procedure is common in proteomics and tanscriptomics, where a NA can many times be assocoaued with quantitation below detetction limit.

Usage

```
presenceFilt(
  dat,
  grp,
  useComparison = NULL,
  maxGrpMiss = 1,
  ratMaxNA = 0.8,
  minVal = NULL,
  sep = NULL,
  experSetup = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	matrix or data.frame (abundance or expression-values which may contain some NAs).
grp	factor of min 2 levels describing which column of 'dat' belongs to which group (levels 1 & 2 will be used)
useComparison	(character or matrix) optional argument allowing to specify which pairwise comparisons could be performed, default useComparison=NULL will run all pairwise comparisons; may be character combining two group-names (from argument grp) separated by a '-' (eg 'A-B') or matrix where the rownames design the elements to be compared as pairwise; Note : the names of the groups may not contain any '-' to avoid confucing them with pairwise separators !
maxGrpMiss	(numeric) at least 1 group has not more than this number of NAs (otherwise marke line as bad)
ratMaxNA	(numeric) at least 1 group below this content of NA values
minVal	(default NULL or numeric), any value below will be treated like NA
sep	(character) in case useCompar ison is not given all pairwise comparisons will be done, the separator to be used when combining names of groups can be given using this argument

experSetup (list) optional experimental setup
 silent (logical) suppress messages
 debug (logical) additional messages for debugging
 callFrom (character) allow easier tracking of messages produced

Value

This function returns a logical matrix (with separate col for each pairwise combination of 'grp' levels) indicating if line of 'dat' acceptable based on NAs (and values minVal)

See Also

[presenceGrpFilt](#), there are also other packages on CRAN and Bioconductor dedicated to filtering

Examples

```

mat <- matrix(rep(8,150), ncol=15, dimnames=list(NULL,
  paste0(rep(LETTERS[4:2],each=6),1:6)[c(1:5,7:16)]))
mat[lower.tri(mat)] <- NA
mat[,15] <- NA
mat[c(2:3,9),14:15] <- NA
mat[c(1,10),13:15] <- NA
mat
# default : at least 1 group with max 1 NA and one group below 80% NA
presenceFilt(mat, substr(colnames(mat),1,1))
# custom 2 groups
presenceFilt(mat, rep(1:2,c(9,6)))          # D1- C4, C5 - B4

# one more example
dat1 <- matrix(1:56, ncol=7)
dat1[c(2:6,10,12,18,19,20,22,23,26:28,30,31,34,38,39,50,54)] <- NA
grp3 <- letters[c(3,3,2,2,1,1,1)]
colnames(dat1) <- correctToUnique(grp3, sep="")
dat1
## At least one group wo any NAs
presenceFilt(dat1, grp3, maxGr=0)
presenceFilt(dat1, gr=gl(2,4)[-1], maxGr=1, ratM=0.1)
presenceFilt(dat1, gr=gl(2,4)[-1], maxGr=2, rat=0.5)

```

presenceGrpFilt

Filter For Each Group Of Columns For Sufficient Data As Non-NA

Description

The aim of this function is to filter for each group of columns for sufficient data as non-NA.

Usage

```
presenceGrpFilt(
  dat,
  grp,
  presThr = 0.75,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	matrix or data.frame (abundance or expression-values which may contain some NAs).
grp	factor of min 2 levels describing which column of 'dat' belongs to which group (levels 1 & 2 will be used)
presThr	(numeric) min ratio of non- NA values (per group) for returning a given line & group as TRUE
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

This function allows to identify lines with an NA-content above the threshold `presThr` per group as defined by the levels of factor `grp`. With different types of projects/questions different threshold `presThr` levels may be useful. For example, if one would like to keep the degree of threshold `presThrs` per group rather low, one could use a value of 0.75 (ie ≥ 75)

Value

logical matrix (with one column for each level of `grp`)

See Also

[presenceFilt](#), there are also other packages totally dedicated to filtering on CRAN and Bioconductor

Examples

```
mat <- matrix(NA, nrow=11, ncol=6)
mat[lower.tri(mat)] <- 1
mat <- cbind(mat, mat[,1:4])
colnames(mat) <- c(paste0("re",1:6), paste0("x",1:4))
mat[6:8,7:10] <- mat[1:3,7:10] # ref
mat[9:11,1:6] <- mat[2:4,1:6]

## accept 1 NA out of 4, 2 NA out of 6 (ie certainly present)
```

```
(filt0a <- presenceGrpFilt(mat, rep(1:2, c(6,4)), pres=0.66))
## accept 2 NA out of 4, 2 NA out of 6 (ie min 50% present)
(filt0b <- presenceGrpFilt(mat, rep(1:2, c(6,4)), pres=0.5))
## accept 3 NA out of 4, 4 NA out of 6 (ie possibly present)
(filt0c <- presenceGrpFilt(mat, rep(1:2, c(6,4)), pres=0.19))
```

protectSpecChar *Protect Special Characters*

Description

Some characters do have a special meaning when used with regular expressions. This concerns characters like a point, parenthesis, backslash etc. Thus, when using `grep` or any related command, such special characters must get protected in order to get considered as they are.

Usage

```
protectSpecChar(
  x,
  prot = c(".", "\\\"", "|", "(", ")", "[", "{", "^", "$", "*", "+", "?"),
  silent = TRUE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<code>x</code>	character vector to be prepared for use in regular expressions
<code>prot</code>	(character) collection of characters that need to be protected
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

This function returns a modified character vector

Examples

```
aa <- c("abc", "abcde", "ab.c", "ab.c.e", "ab*c", "ab\\d")
grepl("b.", aa)                    # all TRUE
grepl("b\\. ", aa)                # manual protection
grepl(protectSpecChar("b."), aa)
```

pVal2lfdr

*Convert p-values to lfdr***Description**

This function takes a numeric vector of p-values and returns a vector of lfdr-values (local false discovery) using the package `fdrtool`. Multiple testing correction should be performed with caution, short series of p-values typically pose problems for transforming to lfdr. The transformation to lfdr values may give warning messages, in this case the resultant lfdr values may be invalid !

Usage

```
pVal2lfdr(x, silent = TRUE, debug = FALSE, callFrom = NULL)
```

Arguments

<code>x</code>	(numeric) vector of p.values
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

This function returns a (numeric) vector of lfdr values (or NULL if data insufficient to run the function 'fdrtool')

See Also

lfdr from `fdrtool`, other p-adjustments (multiple test correction, eg FDR) in `p.adjust`

Examples

```
## Note that this example is too small for estimating really meaningful fdr values
## In consequence, a warning will be issued.
set.seed(2017); t8 <- matrix(round(rnorm(160,10,0.4),2), ncol=8,
  dimnames=list(letters[1:20], c("AA1","BB1","CC1","DD1","AA2","BB2","CC2","DD2")))
t8[3:6,1:2] <- t8[3:6,1:2]+3 # augment lines 3:6 (c-f) for AA1&BB1
t8[5:8,5:6] <- t8[5:8,5:6]+3 # augment lines 5:8 (e-h) for AA2&BB2 (c,d,g,h should be found)
head(pVal2lfdr(apply(t8, 1, function(x) t.test(x[1:4], x[5:8])$p.value)))
```

pwSeparatorList *Suggestions Of Collections Of Classical Separators For Pairwise Combinations*

Description

This function provides collections of typical separators used for combined names in pair-wise testing for later choice of the most suited.

Usage

```
pwSeparatorList(
  type = "split1",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

type	(character) allows selecting of different types of collections of separators
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

Depending if one rather looks for separators for cutting existing names or for suggesting separators for fresh concatenation, two different sets of collections are available via the argument type.

Using type="split" will default to type="split1", similarly type="combine" will be used as type="combine1".

The option type="split1" has a default collection of shorter/compact separators for splitting. The option type="split2" allows more extensive search for 38 separators (ie combinations with ' ; ' and ' _ '), but extensive checking may cost CPU time. The option type="split3" has a shorter collection of 12 basic commonly used separators. The option type="split4" to type="split9" default to 'split1'.

The option type="combine1" does not suggest '-' (neither ' __ ') since if '-' may not be chosen in the first place, using '-' as separator next to '-' occurring inside group-names may not enhance visibility. The option type="combine2" contains a collection of separators using 'vs' or 'versus'. The option type="combine3" is designed for explicit terms (starts with ' - versus - ', for suggesting compact terms rather use type="combine1". The option type="combine4" to type="combine9" default to 'combine1'.

Value

This function returns a character vector with proposed separators for later choosing the most suited.

See Also

(for running multiple pair-wise test) [moderTestXgrp](#), [convPairwiseSetup](#), [presenceFilt](#), [getPWseparator](#), [indexGroupsFromPW](#), (used underneath:) [grep](#), [strsplit](#)

Examples

```
pwSeparatorList(type="split1")
```

randIndFx	<i>Distance of categorical data (Jaccard, Rand and adjusted Rand index)</i>
-----------	---

Description

randIndFx calculates distance of categorical data (as Rand Index, Adjusted Rand Index or Jaccard Index). Note: uses/requires package [flexclust](#) Methods so far available (via flexclust): "ARI" .. adjusted Rand Index, "RI" .. Rand index, "J" .. Jaccard, "FM" .. Fowlkes-Mallows.

Usage

```
randIndFx(
  ma,
  method = "ARI",
  adjSense = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

ma	(matrix) main input for distance calculation
method	(character) name of distance method (eg "ARI","RI","J","FM")
adjSense	(logical) allows introducing correlation/anticorrelation (interpret neg distance results as anti)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a distance matrix

See Also

comPart in [randIndex](#)

Examples

```
set.seed(2016); tab2 <- matrix(sample(1:2, size=42, replace=TRUE), ncol=7)
if(requireNamespace("flexclust")) { flexclust::comPart(tab2[1,], tab2[2,])
  flexclust::comPart(tab2[1,], tab2[3,])
  flexclust::comPart(tab2[1,], tab2[4,]) }
## via randIndFx():
randIndFx(tab2, adjSense=FALSE)
cor(t(tab2))
randIndFx(tab2, adjSense=TRUE)
```

rankToContigTab

*Contingency tables for fit of ranking***Description**

Count the number of instances where the corresponding columns of 'dat' have a value matching the group number as specified by 'grp'. Counting will be performed/repeated independently for each line of 'dat'. Returns array (1st dim is rows of dat, 2nd is unique(grp), 3rd dim is ok/bad), these results may be tested using eg [fisher.test](#). This function was made for preparing to test the ranking of multiple features (lines in 'mat') including replicates (levels of 'grp').

Usage

```
rankToContigTab(dat, grp)
```

Arguments

dat	(matrix or data.frame of integer values) ranking of multiple features (lines), equal ranks may occur
grp	(integer) expected ranking

Value

array (1st dim is rows of dat, 2nd is unique(grp), 3rd dim is ok/bad)

See Also

[lm](#)

Examples

```
# Let's create a matrix with ranks (equal ranks do occur)
ma0 <- matrix(rep(1:3,each=6), ncol=6, dimnames=list(
  c("li1", "li2", "ref"), letters[1:6]))
ma0[1,6] <- 1 # create item not matching correctly
ma0[2,] <- c(3:1,2,1,3) # create items not matching correctly
gr0 <- gl(3,2) # the expected ranking (as duplicates)
(count0 <- rankToContigTab(ma0,gr0))
```

```
cTab <- t(apply(count0, c(1,3) ,sum))
# Now we can compare the ranking of line1 to ref ...
fisher.test(cTab[,c(3,1)])      # test li1 against ref
fisher.test(cTab[,c(3,2)])      # test li2 against ref
```

ratioAllComb	<i>Calculate all ratios between x and y</i>
--------------	---

Description

This function calculates all possible pairwise ratios between all individual values of x and y, or samples up to a maximum number of combinations.

Usage

```
ratioAllComb(
  x,
  y,
  maxLim = 10000,
  isLog = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	(numeric) vector, numerator for constructing ratios
y	(numeric) vector, denominator for constructing ratios
maxLim	(integer) allows reducing complexity by drawing for very long x or y
isLog	(logical) adjust ratio calculation to log-data
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Examples

```
set.seed(2014); ra1 <- c(rnorm(9,2,1),runif(8,1,2))
ratioAllComb(ra1[1:9],ra1[10:17])
boxplot(list(norm=ra1[1:9], unif=ra1[10:17], rat=ratioAllComb(ra1[1:9],ra1[10:17])))
```

ratioToPpm	<i>Convert ratio to ppm</i>
------------	-----------------------------

Description

This function transforms ratio 'x' to ppm (parts per million). If 'y' not given (or different length as 'x'), then 'x' is assumed as ratio otherwise ratios are constructed as x/y is used lateron. Does additional checking : negative values not expected - will be made absolute !

Usage

```
ratioToPpm(  
  x,  
  y = NULL,  
  nSign = NULL,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

x	(numeric) main input
y	(numeric) optional value to construct ratios (x/y). If NULL (or different length as 'x'), then 'x' will be considered as ratio.
nSign	(numeric) number of significant digits
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a numeric vector of ppm values

See Also

[XYToDiffPpm](#) for ppm of difference as used in mass spectrometrie

Examples

```
set.seed(2017); aa <- c(1.000001,0.999999,1+rnorm(10,0,0.001))  
cbind(x=aa,ppm=ratioToPpm(aa,nSign=4))
```

readCsvBatch *Read batch of csv-files*

Description

This function was designed to read screening data split in parts (with common structure) and saved to multiple files, to extract the numeric columns and to compile all (numeric) data to a single array (or list). Some screening platforms save results while progressing through a pile of microtiter-plates separately. The organization of the resultant files is structured through file-names and all files have exactly the same organization of lines and columns/ European or US-formatted csv files can be read, if argument `fileFormat` is NULL both types will be tested, otherwise it allows to specify a given format. The presence of headers (to be used as column-names) may be tested using `checkFormat`.

Usage

```
readCsvBatch(
  fileNames = NULL,
  path = ".",
  fileFormat = "Eur",
  checkFormat = TRUE,
  returnArray = TRUE,
  columns = c("Plate", "Well", "StainA"),
  excludeFiles = "All infected plates",
  simpleNames = TRUE,
  minNamesLe = 4,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<code>fileNames</code>	(character) names of files to be read, if NULL all files fitting 'fileFormat'
<code>path</code>	(character) where files should be read (folders should be written in R-style)
<code>fileFormat</code>	(character) may be NULL (both US and European formats will be tried), 'Eur' or 'US'
<code>checkFormat</code>	(logical) if TRUE: check header, remove empty columns, 1st line if all empty, set output format for each file to matrix, if rownames are increasing integers try to use 2nd of 'columns' as rownames
<code>returnArray</code>	(logical) allows switching from array to list-output
<code>columns</code>	(NULL or character) column-headers to be extracted (if specified), 2nd value may be column with rownames (if rownames are encountered as increasing rownames)
<code>excludeFiles</code>	(character) names of files to exclude (only used when reading all files of given directory)

simpleNames	(logical) allows truncating names (from beginning) to get to variable part (using <code>.trimLeft()</code>), but keeping 'minNamesLe'
minNamesLe	(integer) min length of column-names if simpleNames=TRUE
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns an array (or list if `returnArray=FALSE`) of all numeric data read (numerical columns only) from individual files

See Also

[read.table](#), [writeCsv](#), [readXlsxBatch](#)

Examples

```
path1 <- system.file("extdata", package="wrMisc")
fiNa <- c("pl01_1.csv", "pl01_2.csv", "pl02_1.csv", "pl02_2.csv")
datAll <- readCsvBatch(fiNa, path1)
str(datAll)
## batch reading of all csv files in specified path :
datAll2 <- readCsvBatch(fileNames=NULL, path=path1, silent=TRUE)
```

readTabulatedBatch *Batch Reading Of Tabulated Text-Files*

Description

This function allows batch reading of multiple tabulated text files n batch. The files can be designed specifically, or, alternatively all files from a given directory can be read. If package `data.table` is available, faster reading of files will be performed using the function [fread](#).

Usage

```
readTabulatedBatch(
  query,
  path = NULL,
  dec = ".",
  header = "auto",
  strip.white = FALSE,
  blank.lines.skip = TRUE,
  fill = FALSE,
  filtCol = 2,
  filterAsInf = TRUE,
  filtVal = 5000,
```

```

    silent = FALSE,
    callFrom = NULL,
    debug = FALSE
  )

```

Arguments

query	(character) vector of file-names to be read, if "." all files will be read (no matter what their extension might be)
path	(character) path for reading files, if NULL or NA the current directory will be used
dec	(character, length=1) decimals to use, will be passed to fread or read.delim
header	(character, length=1) path for reading files, if NULL or NA the current directory will be used, will be passed to fread or read.delim
strip.white	(logical, length=1) Strips leading and trailing whitespaces of unquoted fields, will be passed to fread or read.delim
blank.lines.skip	(logical, length=1) If TRUE blank lines in the input are ignored. will be passed to fread or read.delim
fill	(logical, length=1) If TRUE then in case the rows have unequal length, blank fields are implicitly filled, will be passed to fread or read.delim
filtCol	(integer, length=1) which columns should be used for filtering, if NULL or NA all data will be returned
filterAsInf	(logical, length=1) filter as inferior or equal (TRUE) or superior or equal threshold <code>filtVal</code>
filtVal	(numeric, length=1) which numeric threshold should be used for filtering, if NULL or NA all data will be returned
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced
debug	(logical) display additional messages for debugging

Details

If you want to provide a flexible pattern of file-names, this has to be done before calling this function, eg using `grep` to provide an explicit collection of files. However, it is possible to read different files from different locations/directories, the length of path must match the length of query

Value

This function returns a list of data.frames

See Also

[fread](#), [read.delim](#), for reading batch of csv files : [readCsvBatch](#)

Examples

```
path1 <- system.file("extdata", package="wrMisc")
fiNa <- c("a1.txt", "a2.txt")
allTxt <- readTabulatedBatch(fiNa, path1)
str(allTxt)
```

readVarColumns

*Read Tabular Content Of Files With Variable Number Of Columns***Description**

Reading the content of files where the number of separators (eg tabulation) is variable poses problems with traditional methods for reading files, like [read.table](#). This function reads each line independently and then parses all separators therein. The first line is assumed to be column-headers. Finally, all data will be returned in a matrix adopted to the line with most separators and if the number of column-headers is insufficient, new (unique) column-headers will be generated. Thus, the lines may contain different number of elements, empty elements (ie tabular fields) will always get added to right of data read and their content will be as defined by argument `emptyFields` (default NA).

Usage

```
readVarColumns(
  fiName,
  path = NULL,
  sep = "\t",
  header = TRUE,
  emptyFields = NA,
  refCo = NULL,
  supNa = NULL,
  silent = FALSE,
  callFrom = NULL
)
```

Arguments

<code>fiName</code>	(character) file-name
<code>path</code>	(character) optional path
<code>sep</code>	(character) separator (between columns)
<code>header</code>	(logical) indicating whether the file contains the names of the variables as its first line.
<code>emptyFields</code>	(NA or character) missing headers will be replaced by the content of 'emptyFields', if NA the last column-name will be re-used and a counter added
<code>refCo</code>	(integer) for custom choice of column to be used as row-names (default will use 1st text-column)

supNa (character) base for constructing name for columns wo names (+counter starting at 2), default column-name to left of 1st col wo colname

silent (logical) suppress messages

callFrom (character) allow easier tracking of messages produced

Details

Note, this functions assumes one line of header and at least one line of data ! Note, for numeric data the comma is assumed to be US-Style (as '.'). Note, that it is assumed, that any missing fields for the complete tabular view are missing on the right (ie at the end of line) !

Value

This function returns a matrix (character or numeric)

See Also

for regular 'complete' data [read.table](#) and its argument flush

Examples

```
path1 <- system.file("extdata",package="wrMisc")
fiNa <- "Names1.tsv"
datAll <- readVarColumns(fiName=file.path(path1,fiNa))
str(datAll)
```

readXlsxBatch

Read Batch of Excel xlsx-Files

Description

readXlsxBatch reads data out of multiple xlsx files, the sheet indicated by 'sheetInd' will be considered. All files must have the same organization of data, as this is typically the case when high-throughput measurements are automatically saved while experiments progress. In particular, the first file read is used to structure the output.

Usage

```
readXlsxBatch(
  fileNames = NULL,
  path = ".",
  fileExtension = "xlsx",
  excludeFiles = NULL,
  sheetInd = 1,
  checkFormat = TRUE,
  returnArray = TRUE,
  columns = c("Plate", "Well", "StainA"),
```

```

    simpleNames = 3,
    silent = FALSE,
    debug = FALSE,
    callFrom = NULL
  )

```

Arguments

fileNames	(character) provide either explicit list of file-names to be read or leave NULL for reading all files ending with 'xlsx' in path specified with argument path
path	(character) there may be a different path for each file
fileExtension	(character) extension of files (default='xlsx')
excludeFiles	(character) names of files to exclude (only used when reading all files of given directory)
sheetInd	(character or integer) specify which sheet to extract (as exact name of sheet or sheet-number, eg sheetInd=2 will extract always the 2nd sheet (no matter the name); if given as sheet-name but not present in file an empty list-element will be returned)
checkFormat	(logical) if TRUE: check header, remove empty columns, if rownames are increasing integers it will search for first column with different entries to use as rownames
returnArray	(logical) allows switching from array to list-output
columns	(NULL or character) column-headers to be extracted (if specified, otherwise all columns will be extracted)
simpleNames	(integer), if NULL all characters of fileNames will be maintained, otherwise allows truncating names (from beginning) to get to variable part (using <code>.trimLeft()</code>), but keeping at least the number of characters indicated by this argument
silent	(logical) suppress messages
debug	(logical) display additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Details

By default all columns with text-content may be eliminated to keep the numeric part only, which may then get organized to a 3-dim numeric array (where the additional files will be used as 2nd dimension and multiple columns per file shown as 3rd dimension).

NOTE : (starting from version `wrMisc-1.5.5`) requires packages `readxl` and `Rcpp` being installed ! (This allows much faster and memory efficient processing than previous use of package 'xlsx')

Value

This function returns a list of data.frames

See Also

[read_excel](#); for simple reading of (older) xls-files under 32-bit R one may also see the package [RODBC](#)

Examples

```

path1 <- system.file("extdata", package="wrMisc")
fiNa <- c("pl01_1.xlsx", "pl01_2.xlsx", "pl02_1.xlsx", "pl02_2.xlsx")
datAll <- readXlsxBatch(fiNa, path1)
str(datAll)
## Now let's read all xlsx files of directory
datAll2 <- readXlsxBatch(path=path1, silent=TRUE)
identical(datAll, datAll2)

```

reduceTable

Reduce table by aggregating smaller groups

Description

reduceTable treats/reduces results from [table](#) to 'nGrp' groups, optional indiv resolution of 'separFirst' (numeric or NULL). Mainly made for reducing the number of classes for better plots with [pie](#)

Usage

```
reduceTable(tab, separFirst = 4, nGrp = 15)
```

Arguments

tab	output of table
separFirst	(integer or NULL) optional separation of n 'separFirst' groups (value <2 or NULL will privilege more uniform size of groups, higher values will cause small initial and larger tailing groups)
nGrp	(integer) number of groups expected

Value

This function returns a numeric vector with number of counts and class-borders as names (like [table](#)).

See Also

[table](#)

Examples

```

set.seed(2018); dat <- sample(11:60, 200, repl=TRUE)
pie(table(dat))
pie(reduceTable(table(dat), sep=NULL))
pie(reduceTable(table(dat), sep=NULL), init.angle=90,
  clockwise=TRUE, col=rainbow(20)[1:15], cex=0.8)

```

regrBy1or2point *Rescaling According To Reference Data Using Linear Regression.*

Description

This function does rescaling: linear transform simple vector 'inDat' that (mean of) elements of names cited in 'refLst' will end up as values 'regrTo'. Regress single vector according to 'refLst' (describing names of inDat). If 'refLst' contains 2 groups, the 1st group will be set to the 1st value of 'regrTo' (and the 2nd group of 'refLst' to the 2nd 'regrTo')

Usage

```
regrBy1or2point(
  inDat,
  refLst,
  regrTo = c(1, 0.5),
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

inDat	(matrix or data.frame) data to rescaled
refLst	list of names existing in inDat (one group of names for each value in 'regrTo'), to be transformed in values precised in 'regrTo'; if no matches to names of 'inDat' found, the 2 lowest and/or highest values will be chosen
regrTo	(numeric,length=2) range (at scale 0-1) of target-values for mean of elements cited in 'refLst'
silent	(logical) suppress messages if TRUE
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a normalized matrix

See Also

[adjBy2ptReg](#), [regrMultBy1or2point](#)

Examples

```
set.seed(2016); dat1 <- 1:50 +(1:50)*round(runif(50),1)
names(dat1) <- 1:length(dat1)
reg1 <- regrBy1or2point(dat1, refLst=c("2","49"))
plot(reg1, dat1)
```

regrMultBy1or2point *Rescaling Of Multiple Data-Sets According To Reference Data Using Regression*

Description

This function regresses each col of matrix according to 'refLst'(describing rownames of inDat). If 'refLst' conatins 2 groups, the 1st group will be set to the 1st value of 'regrTo' (and the 2nd group of 'refLst' to the 2nd 'regrTo')

Usage

```
regrMultBy1or2point(
  inDat,
  refLst,
  regrTo = c(1, 0.5),
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

inDat	(matrix or data.frame) data to be rescaled
refLst	list of names existing in inDat (one group of names for each value in 'regrTo'), to be transformed in values precised in 'regTo'; if no matches to names of 'inDat' found, the 2 lowest and/or highest highest values will be chosen
regrTo	(numeric,length=2) range (at scale 0-1) of target-values for mean of elements cited in 'refLst'
silent	(logical) suppress messages if TRUE
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a normalized matrix

See Also

[adjBy2ptReg](#), [regrBy1or2point](#)

Examples

```
set.seed(2016); dat2 <- round(cbind(1:50 +(1:50)*runif(50),2.2*(1:50) +rnorm(50,0,3)),1)
rownames(dat2) <- 1:nrow(dat2)
reg1 <- regrBy1or2point(dat2[,1],refLst=list(as.character(5:7),as.character(44:45)))
reg2 <- regrMultBy1or2point(dat2,refLst=list(as.character(5:7),as.character(44:45)))
plot(dat2[,1],reg2[,1])
identical(reg1,reg2[,1])
identical(dat2[,1],reg2[,1])
```

renameColumns	<i>Rename columns</i>
---------------	-----------------------

Description

This function renames columns of 'refMatr' using 2-column matrix (or data.frame) indicating old and new names (for replacement).

Usage

```
renameColumns(refMatr, newName, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

refMatr	matrix (or data.frame) where column-names should be changed
newName	(matrix of character) giving correspondence of old to new names (number of lines must match number of columns of 'refMatr')
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a matrix (or data.frame) with renamed columns

Examples

```
ma <- matrix(1:8,ncol=4,dimnames=list(1:2,LETTERS[1:4]))
replBy1 <- cbind(new=c("dd","bb","z_"),old=c("D","B","zz"))
replBy2 <- matrix(c("D","B","zz","dd","bb","z_"),ncol=2)
replBy3 <- matrix(c("X","Y","zz","xx","yy","z_"),ncol=2)
renameColumns(ma,replBy1)
renameColumns(ma,replBy2)
renameColumns(ma,replBy3)
```

reorgByCluNo

*Reorganize matrix according to clustering-output***Description**

Reorganize input matrix as sorted by cluster numbers (and geometric mean) according to vector with cluster names, and index for sorting per cluster and per geometric mean. In case mat is an array, the 3rd dimension will be considered as 'column' with arguments useColumn (and cluNo, if it designs a 'column' of mat).

Usage

```
reorgByCluNo(
  mat,
  cluNo,
  useColumn = NULL,
  meanCol = NULL,
  addInfo = TRUE,
  retList = FALSE,
  silent = FALSE,
  callFrom = NULL,
  debug = FALSE
)
```

Arguments

mat	(matrix or data.frame) main input
cluNo	(positive integer, length to match nrow(dat) initial cluster numbers for each line of 'mat' (obtained by separate clustering or other segmentation) or may design column of mat to use as cluster-numbers
useColumn	(character or integer) the columns to use from mat as main data (default will use all, except cluCol and/or meanCol if they design columns)
meanCol	(character or integer) alternative summarizing data for intra-cluster sorting (instead of geometric mean)
addInfo	(logical) allows of columns 'index', 'geoMean' and 'cluNo' (or array if FALSE)
retList	(logical) return as list of matrixes (or array if FALSE)
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced
debug	(logical) additional messages for debugging

Value

This function returns a list or array (as 2- or 3 dim) with possible number of occurrences for each of the 3 elements in nMax. Read results vertical : out[[1]] or out[,1] .. (multiplicative) table for 1st element of nMax; out[,2] .. for 2nd

Value

This function returns a character vector with group-wise substituted separators (or NULL if conflicts appear)

See Also

[indexGroupsFromPW](#), [getPWseparator](#), [.getPWseparator](#)

Examples

```
replacePWseparator(compNames=c("B-C", "B-D", "C-D"), newSep="-vs-")
```

replicateStructure *Search and Select Groups of Replicates*

Description

This function was designed for mining annotation information organized in multiple columns to identify the (potential) grouping of multiple samples, ie to determine factor levels. The argument method allows further finetuning if high or low number of groups should be preferred, if multiple columns may be combined, or to choose a particular custom column for designating factor levels.

Usage

```
replicateStructure(  
  x,  
  method = "median",  
  sep = "__",  
  exclNoRepl = TRUE,  
  trimNames = FALSE,  
  includeOther = FALSE,  
  silent = FALSE,  
  callFrom = NULL,  
  debug = FALSE  
)
```

Arguments

x	(matrix or data.frame) the annotation to inspect; each column is supposed to describe another set of annoation/metadata for the rows of x (min 1 row and 1 column),
method	(character, length=1) the procedure to choose column(s) with properties of information, may be highest or max (max number of levels) lowest or min (min number of levels), median (median of all options for number of levels), combAll (combine all columns of x) or combNonOrth (combine only non-orthogonal columns of x, to avoid avoid n lines with n levels); lazy evluation of the argument is possible

sep	(character) separator used when a method combining multiple columns (eg combAll, combNonOrth) is chosen (should not appear anywhere in x)
exclNoRepl	(logical) decide whether columns with all values different (ie no replicates or max divergency) should be excluded
trimNames	(logical) optional trimming of names in x by removing redundant heading and tailing text
includeOther	(logical) include \$allCols with pattern of (all) other columns
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced
debug	(logical) additional messages for debugging

Details

Statistical tests require specifying which samples should be considered as replicates of whom. In some cases, like the Sdrf-format, automatic mining of such annotation to identify an experiment's underlying structure of replicates may be challenging, since the key information may not always be found in the same column. For this reason this function allows inspecting all columns of a matrix of data.frame to identify which columns may serve describing groups of replicates.

The argument `exclNoRepl=TRUE` allows excluding all columns with different content for each line (like line-numbers), ie information without any replicates. It is set by default to TRUE to exclude such columns, since statistical tests usually do require some replicates.

When using as `method="combAll"`, there is risk all lines (samples) will be considered different and no replicates remain. To avoid this situation the argument can be set to `method="combNonOrth"`. Using this mode it will be checked if more columns will lead to complete loss of replicates, and -if so- concerned columns omitted.

Value

This function returns a list with \$col (column index relativ to x), \$lev (abstract labels of level), \$meth (note of method finally used) and \$allCols with general replicate structure of all columns of x

See Also

[duplicated](#), uses [trimRedundText](#); for choosing single most likely column describing sample-names and groups of replicates [chooseGroupNames](#)

Examples

```
## a is all different, b is groups of 2,
## c & d are groups of 2 but NOT 'same general' pattern as b
strX <- data.frame(a=letters[18:11], b=letters[rep(c(3:1,4), each=2)],
  c=letters[rep(c(5,8:6), each=2)], d=letters[c(1:2,1:3,3:4,4)],
  e=letters[rep(c(4,8,4,7),each=2)], f=rep("z",8) )
strX
replicateStructure(strX[,1:2])
replicateStructure(strX[,1:4], method="combAll")
replicateStructure(strX[,1:4], method="combAll", exclNoRepl=FALSE)
```

```

replicateStructure(strX[,1:4], method="combNonOrth", exc1NoRepl=TRUE)
replicateStructure(strX, method="lowest")
replicateStructure(strX, method=3, includeOther=TRUE) # custom choice of 3rd column

```

replNAbyLow

Replace NAs by low values

Description

With several screening techniques used in high-throughput biology values at/below detection limit are returned as NA. However, the resultant NA-values may be difficult to analyse properly, simply ignoring NA-values may not be a good choice. When (technical) replicate measurements are available, one can look for cases where one gave an NA while the other did not with the aim of investigating such 'NA-neighbours'. replNAbyLow locates and replaces NA values by (random) values from same line & same group 'grp'. The origin of NAs should be predominantly absence of measure (quantitation) due to signal below limit of detection and not saturation at upper detection limit or other technical problems. Note, this approach may be not optimal if the number of NA-neighbours is very low. Replacement is done -depending on argument 'unif'- by Gaussian random model based on neighbour values (within same group), using their means and sd, or a uniform random model (min and max of neighbour values). Then numeric matrix (same dim as 'x') with NA replaced is returned.

Usage

```

replNAbyLow(
  x,
  grp,
  quant = 0.8,
  signific = 3,
  unif = TRUE,
  absOnly = FALSE,
  seed = NULL,
  silent = FALSE,
  callFrom = NULL
)

```

Arguments

x	(numeric matrix or data.frame) main input
grp	(factor) to organize replicate columns of (x)
quant	(numeric) quantile form 'neighbour' values to use as upper limit for random values
signific	number of signif digits for random values

unif	(logical) toggle between uniform and Gaussian random values
absOnly	(logical) if TRUE, make negative NA-replacement values positive as absolute values
seed	(integer) for use with set.seed for reproducible output
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of message(s) produced

Value

numeric matrix (same dim as 'x') with NA replaced

See Also

[naOmit](#), [na.fail](#)

Examples

```
dat <- matrix(round(rnorm(30),2),ncol=6); grD <- gl(2,3)
dat[sort(sample(1:30,9,repl=FALSE))] <- NA
dat; replNAbyLow(dat,gr=grD)
```

replPlateCV	<i>CV of replicate plates (list of matrixes)</i>
-------------	--

Description

This function calculates CVs of replicates from list of 2 or 3-dim arrays (where 2nd dim is replicates, 3rd dim may be channel). Note : all list-elements of must **MUST** have SAME dimensions ! When treating data from microtiter plates (eg 8x12) data are typically spread over multiple plates, ie initial matrixes that are the organized into arrays. Returns matrix or array (1st dim is intraplate-position, 2nd .. plate-group/type, 3rd .. channels)

Usage

```
replPlateCV(lst, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

lst	list of matrixes : suppose lines are independent elements, columns are replicates of the 1st column. All matrixes must have same dimensions
silent	(logical) suppress messages if TRUE
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a matrix or array (1st dim is intraplate-position, 2nd .. plate-group/type, 3rd .. channels)

See Also

[rowCVs](#), [@seealso arrayCV](#)

Examples

```
set.seed(2016); ra1 <- matrix(rnorm(3*96),nrow=8)
pla1 <- list(ra1[,1:12],ra1[,13:24],ra1[,25:36])
replPlateCV(pla1)
arrL1 <- list(a=array(as.numeric(ra1)[1:192],dim=c(8,12,2)),
             b=array(as.numeric(ra1)[97:288],dim=c(8,12,2)))
replPlateCV(arrL1)
```

rmDupl2colMatr	<i>Remove Lines Of Matrix Redundant /Duplicated For 1st And 2nd Column</i>
----------------	--

Description

This function removes lines of matrix that are redundant /duplicated for 1st and 2nd column (irrespective of content of their columns). The first occurrence of redundant /duplicated elements is kept.

Usage

```
rmDupl2colMatr(
  mat,
  useCol = c(1, 2),
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

mat	(matrix or data.frame) main input
useCol	(integer, length=2) columns to consider/use when looking for duplicated entries
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a matrix where duplicated lines are removed

See Also

[unlist](#)

Examples

```
mat <- matrix(1:12,ncol=3)
mat[3,1:2] <- mat[1,1:2]
rmDup12colMatr(mat)
```

rmEnumeratorName	<i>Remove or rename enumerator tag/name (or remove entire enumerator) from tailing enumerators</i>
------------------	--

Description

This function allows identifying, removing or renaming enumerator tag/name (or remove entire enumerator) from tailing enumerators (eg 'abc_No1' to 'abc_1'). A panel of potential candidates as combination of separator-symbols and separator text/words will be tested to find if one matches all data. In case the main input is a matrix, all columns will be tested independently to find the first column where one specific combination of separator-symbols and separator text/words is found. Several options exist for the output, the combination of separator-symbols and separator text/words may be included, too.

Usage

```
rmEnumeratorName(
  dat,
  nameEnum = c("Number", "No", "#", "Replicate", "Sample"),
  sepEnum = c(" ", "-", "_", "/"),
  newSep = "",
  incl = c("anyCase", "trim2"),
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	(character vector or matrix) main input
nameEnum	(character) potential enumerator-names
sepEnum	(character) potential separators for enumerator-names
newSep	(character) potential enumerator-names

<code>incl</code>	(character) options to include further variants of the enumerator-names, use "rmEnum" for completely removing enumerator tag/name and digits for different options of trimming names/tags from nameEnum; or one may use anyCase, trim3 (trimming down to max 3 letters), trim2 (trimming to max 2 letters) or trim1 (trimming down to single letter); trim0 works like trim1 but also includes ' ', ie no enumerator tag/name in front of the digit(s)
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) display additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Details

In case only digit-enumerators are present (ie, without repetitive text), one has to use `incl="rmEnum"` to remove terminal enumerators. This will work, only when all items do contain terminal digits.

Please note, that checking a variety of different separator text-word and separator-symbols may give an important number of combinations to check. In particular, when automatic trimming of separator text-words is added (eg `incl="trim2"`), the complexity of associated searches increases quickly. Thus, with large data-sets restricting the content of the arguments `nameEnum`, `sepEnum` and (in particular) `newSep` to the most probable terms/options is suggested to help reducing demands on memory and CPU.

In case the input `dat` is a matrix and multiple different numerator-types are found, only the first column (from the left) will be treated. If you wish to remove/substitute multiple types of enumerators the function `rmEnumeratorName` must be run independently, see last example below.

Value

This function returns a corrected vector (or matrix), or a list if `incl="rmEnumL"` containing `$dat` (corrected data), `$pattern` (the combination of separator-symbols and separator text/words found), and if input is matrix `$column` (which column of the input was identified and treated)

See Also

when the exact pattern is known [grep](#) and `sub` may allow direct manipulations much faster

Examples

```
xv <- c("hg_1", "hjRe2_2", "hk-33")
rmEnumeratorName(xv)
rmEnumeratorName(xv, incl="rmEnum")

xx <- c("hg_Re1", "hjRe2_Re2", "hk-Re3_Re33")
rmEnumeratorName(xx)
rmEnumeratorName(xx, newSep="--")
rmEnumeratorName(xx, incl="anyCase")

xy <- cbind(a=11:13, b=c("11#11", "2_No2", "333_samp333"), c=xx)
rmEnumeratorName(xy)
rmEnumeratorName(xy, incl=c("anyCase", "trim2", "rmEnumL"))
```

```
xz <- cbind(a=11:13, b=c("23#11", "4#2", "567#333"), c=xx)
apply(xz, 2, rmEnumeratorName, sepEnum=c("", "_"), newSep="_", silent=TRUE)
```

 rmOrphans

Remove or Reassign Orphan Indexes

Description

This function allows detecting terminal orphans of a vector of (cluster-) indexes and removing (ie marking as NA) or re-assigning them to the neighbour class towards the center.

Usage

```
rmOrphans(
  ind,
  minN = 1,
  reassign = FALSE,
  side = "both",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

ind	(integer) main input of (cluster-) indexes
minN	(numeric, length=1) the min frequency to consider as orphans, if less than 1 it will be interpreted as ratio compared to length of index
reassign	(logical) if TRUE orphan indexes will be replaced by neighbour class indexes (towards the center)
side	(character) may be 'both', 'b', 'upper', 'u', 'lower' or 'l' to decide if lower and/or upper end indexes should be treated.
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Details

All input of `ind` is supposed to be integer values as (cluster-) indexes. This function will look if the lowest and/or highest (cluster-) indexes appear at very low frequency so that they may be considered orphans. The argument `minN` assigns the threshold of when the frequency of terminal values may be considered as 'orphan', either as absolute threshold or if less than 1 as ratio (0.1 => 10)

The argument `side` may be 'both', 'b', 'upper', 'u', 'lower' or 'l', to decide if lower and/or upper end indexes should be treated.

Value

This function returns an integer vector of adjusted indexes

See Also

[table](#)

Examples

```
x=c(3:1,3:4,4:6,5:3); rmOrphans(x)
rmOrphans(x, minN=0.2)
## reassign orphans to neighbour center class
cbind(x, x=x, def=rmOrphans(x, reassign=TRUE),
      minN=rmOrphans(x, minN=0.2, reassign=TRUE) )
```

 rmSharedWords

Trim/Remove Redundant Words

Description

This function allows removing shared words, ie trimming to non-redundant words.

Usage

```
rmSharedWords(
  x,
  sep = c("_", " ", "."),
  anySep = TRUE,
  newSep = NULL,
  minLe = 2,
  na.omit = FALSE,
  fixed = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	(character) main input for making non-redundant
sep	(character) separator(s) to be used
anySep	(logical) if TRUE, will consider all separators at one time (), thus combinations with different separators won't be distinguished
newSep	(character) new (uniform) separator between words, if NULL the first value/separator of if sep will be used
minLe	(integer) minimum length for allowing being recognised as 'word'

na.omit	(logical) if TRUE NAs will be removed from output
fixed	(logical) will be transmitted to argument fixed of strsplit(); if TRUE regular expressions are allowed/used
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Details

Heading separators will be removed in any case (even if not followed by a 'word').

Special characters will be automatically protected. When looking for repeated words, the order of such words does NOT matter, multiple repeats will be removed, too.

#'

Value

This function returns character vector of same length (unless na.omit=TRUE), simply with modified text-content

See Also

[trimRedundText](#)

Examples

```
x1 <- c("aa_A1 yy_zz.txt", NA, "B2 yy_aa_aa_zz.txt")
rmSharedWords(x1)
```

rnormW	<i>Normal random number generation with close fit to expected mean and sd</i>
--------	---

Description

This function allows creating a vector of random values similar to rnorm, but resulting value get recorrected to fit to expected mean and sd. When the number of random values to generate is low, the mean and sd of the resultant values may deviate from the expected mean and sd when using the standard rnorm function. In such cases the function rnormW helps getting much closer to the expected mean and sd.

Usage

```
rnormW(  
  n,  
  mean = 0,  
  sd = 1,  
  seed = NULL,  
  digits = 8,  
  silent = FALSE,  
  callFrom = NULL  
)
```

Arguments

n	(integer, length=1) number of observations. If length(n) > 1, the length is taken to be the number required.
mean	(numeric, length=1) expected mean
sd	(numeric, length=1) expected sd
seed	(integer, length=1) seed for generating random numbers
digits	(integer, length=1 or NULL) number of significant digits for output, set to NULL to get all digits
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced

Details

For making result reproducible, a seed for generating random numbers can be set via the argument seed. However, with n=2 the resulting values are 'fixed' since no random component is possible at n < 3.

Value

This function returns a numeric vector of random values

See Also

[Normal](#)

Examples

```
x1 <- (11:16)[-5]  
mean(x1); sd(x1)  
## the standard way  
ra1 <- rnorm(n=length(x1), mean=mean(x1), sd=sd(x1))  
## typically the random values deviate (slightly) from expected mean and sd  
mean(ra1) -mean(x1)  
sd(ra1) -sd(x1)  
## random numbers with close fit to expected mean and sd :  
ra2 <- rnormW(length(x1), mean(x1), sd(x1))
```

```

mean(ra2) -mean(x1)
sd(ra2) -sd(x1)      # much closer to expected value

```

rowCVs

rowCVs

Description

This function returns CV for values in each row (using speed optimized standard deviation). Note : NaN values get replaced by NA.

Usage

```
rowCVs(dat, autoconvert = NULL, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

dat	(numeric) matix
autoconvert	(NULL or character) allows converting simple vectors in matrix of 1 row (autoconvert="row")
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a (numeric) vector with CVs for each row of 'dat'

See Also

[colSums](#), [rowSds](#), [rowGrpCV](#), [colCVs](#)

Examples

```

set.seed(2016); dat1 <- matrix(c(runif(200) +rep(1:10,20)), ncol=10)
head(rowCVs(dat1))

```

rowGrpCV	<i>Row group CV</i>
----------	---------------------

Description

This function calculates CVs for matrix with multiple groups of data, ie one CV for each group of data. Groups are specified as columns of 'x' in 'grp' (so length of grp should match number of columns of 'x', NAs are allowed)

Usage

```
rowGrpCV(x, grp, means = NULL, listOutp = FALSE)
```

Arguments

x	numeric matrix where replicates are organized into separate columns
grp	(factor) defining which columns should be grouped (considered as replicates)
means	(numeric) alternative values instead of means by .rowGrpMeans()
listOutp	(logical) if TRUE, provide output as list with \$CV, \$mean and \$n

Value

This function returns a matrix of CV values

See Also

[rowCVs](#), [arrayCV](#), [replPlateCV](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
head(rowGrpCV(dat1, gr=g1(4,3,labels=LETTERS[1:4])[2:11]))
```

rowGrpMeans	<i>Row-Means With Distinction Of Groups (Of Columns, eg Groups Of Replicates)</i>
-------------	---

Description

Thus function calculates column-means for matrix with multiple groups of data, ie similar to rowMeans but one mean for each group of data. Groups are specified as columns of 'x' in 'grp' (so length of grp should match number of columns of 'x', NAs are allowed).

Usage

```
rowGrpMeans(  
  x,  
  grp,  
  na.rm = TRUE,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

x	(numeric matrix or data.frame) main input
grp	(character or factor) defining which columns should be grouped (considered as replicates)
na.rm	(logical) a logical value indicating whether NA-values should be stripped before the computation proceeds.
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) This function allows easier tracking of messages produced

Value

This function returns a matrix with mean values

See Also

[rowSds](#), [colSums](#) which also shows [colMeans](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200) + rep(1:10,20)), ncol=10)  
head(rowGrpMeans(dat1, gr=gl(4, 3, labels=LETTERS[1:4])[2:11]))
```

rowGrpNA

Count Number Of NAs Per Row And Group Of Columns

Description

This functions allows easy counting of the number of NAs per row in data organized in multiple sub-groups as columns.

Usage

```
rowGrpNA(
  mat,
  grp = NULL,
  initColOrder = TRUE,
  mode = "simple",
  digits = 2,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

mat	(matrix, data.frame, list or 'MArrayLM') data to count the number of NAs; in case of furnishing a list or MArrayLM-class a list-element called 'isNA' will be used as mat or all NA positions of list-element called 'raw'
grp	(character or factor) defining which columns should be grouped (considered as replicates). If grp is not provided and mat is list or 'MArrayLM'-class containing a list-element 'setup' (as produced with testing from package wrProteo) the group-association will be taken from there
initColOrder	(logical) if FALSE the columns may be in (alphabetically) sorted order
mode	(character) switch between different types of output : - mode="simple" will return simply the number of NAs per line and group as integer - mode="simpleCollapse" will collapse all columns into single chain of characters with the number of NAs per line and group (as character) - mode="complete" will return number of NAs per line and group accompanied by the number of columns associated with the very group (as character) - mode="completeCollapse" will collapse all columns into single chain of characters with the number of NAs per line and group accompanied by the number of columns associated with the very group (as character) - mode="ratio" will return the ratio of NAs per line and group (as numeric) - mode="ratioCollapse" will collapse all columns into single chain of characters with the ratio of NAs per line and group(as character)
digits	(integer, length=1) number of decimal digits from rounding (when ratios are calculated)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Details

First of all, this function allows counting the number of NAs per line and sub-group of columns as defined by argument `grp`. Furthermore, the counting can be expressed relative to the size of the sub-groups, either as ratio or by giving the NA-count using `mode="ratio"` and the size of the sub-group using `mode="complete"`. Finally, all results may get collapsed in as single (character) vector, however, the names of the groups do not get conserved.

Value

This function returns typically a matrix (or numeric vector if all grouping falls in a single class or character-vector if all groups get collapsed in single chain of characters) with number of NAs per group

See Also

[rowGrpMeans](#), [rowSds](#), [colSums](#)

Examples

```
mat2 <- matrix(1, nrow=200, ncol=40)
mat2[sample.int(prod(dim(mat2)), nrow(mat2), replace=FALSE)] <- NA
grp2 <- as.factor(sample.int(n=8, size=ncol(mat2), replace=TRUE))
  table(grp2)
## overall number of NAs per row
rowSums(is.na(mat2))

## number of NAs per row and group
head(rowGrpNA(mat2, grp2))
head(rowGrpNA(mat2, grp2, mode="simple"))
head(rowGrpNA(mat2, grp2, mode="complete"))

## mimick output from testing from package wrProteo
dat1 <- list(isNA =mat2, setup=list(grp=grp2))
head(rowGrpNA(dat1, mode="simple"))
head(rowGrpNA(dat1, mode="complete"))
head(rowGrpNA(dat1, mode="ratioCollapse"))
```

rowGrpSds

Per line and per group sd-values

Description

rowGrpSds calculate Sd (standard-deviation) for matrix with multiple groups of data, ie one sd for each group of data. Groups are specified as columns of 'x' in 'grp' (so length of grp should match number of columns of 'x', NAs are allowed).

Usage

```
rowGrpSds(x, grp)
```

Arguments

x	matrix where replicates are organized into seprate columns
grp	(character or factor) defining which columns should be grouped (considered as replicates)

Value

This function returns a matrix of sd values

See Also

[rowGrpMeans](#), [rowCVs](#), [rowSEMs](#), [sd](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200) + rep(1:10,20)), ncol=10)
head(rowGrpSds(dat1, gr=gl(4,3,labels=LETTERS[1:4])[2:11]))
```

rowGrpSums	<i>rowSums with distinction of groups (of columns, eg groups of replicates)</i>
------------	---

Description

This function calculates row-sums for matrix with multiple groups of data, ie similar to `rowSums` but one summed value for each line and group of data. Groups are specified as columns of 'x' in 'grp' (so length of grp should match number of columns of 'x', NAs are allowed).

Usage

```
rowGrpSums(x, grp, na.rm = TRUE)
```

Arguments

x	matrix or data.frame
grp	(character or factor) defining which columns should be grouped (considered as replicates)
na.rm	(logical) a logical value indicating whether NA-values should be stripped before the computation proceeds.

Value

This function a matrix with row/group sum values

See Also

[rowGrpMeans](#), [rowGrpSds](#), [rowSds](#), [colSums](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200) + rep(1:10,20)), ncol=10)
head(rowGrpMeans(dat1, gr=gl(4, 3, labels=LETTERS[1:4])[2:11]))
```

rowMedSds	<i>Estimate sd Of Median For Each Row By Bootstrap</i>
-----------	--

Description

This function determines the stand error (sd) of the median for each row by bootstraping each row of 'dat'. Note: requires package [boot](#)

Usage

```
rowMedSds(dat, nBoot = 99, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

dat	(numeric) matix, main input
nBoot	(integer) number if iterations for bootstrap
silent	(logical) suppress messages
debug	(logical) display additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This functions returns a (numeric) vector with estimated sd values

See Also

For a more flexible version able to handle lists please look at [colMedSds](#) , based on [boot](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)), ncol=10)
rowMedSds(dat1) ; plot(rowSds(dat1), rowMedSds(dat1))
```

rowNormalize	<i>Row Normalize</i>
--------------	----------------------

Description

This function was designed for normalizing data that is supposed to be particularly similar, like a collection of technical replicates. Thus, initially for each row an independent normalization factor is calculated and the median or mean across all factors will be finally applied to the data. This function has a special mode of operation with higher content of NA values (which may pose problems with other normalization approaches). If the NA-content is higher than the threshold set in `sparseLim`, a special procedure for sparse data will be applied (iteratively trating subsets of `nCombin` columns that will be combined in a later step).

Usage

```

rowNormalize(
  dat,
  method = "median",
  refLines = NULL,
  refGrp = NULL,
  proportMode = TRUE,
  minQuant = NULL,
  sparseLim = 0.4,
  nCombin = 3,
  omitNonAlignable = FALSE,
  maxFact = 10,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)

```

Arguments

<code>dat</code>	matrix or data.frame of data to get normalized
<code>method</code>	(character) may be "mean", "median" (plus "NULL", "none"); When NULL or 'none' is chosen the input will be returned as is
<code>refLines</code>	(NULL or numeric) allows to consider only specific lines of 'dat' when determining normalization factors (all data will be normalized)
<code>refGrp</code>	(integer) Only the columns indicated will be used as reference, default all columns (integer or colnames)
<code>proportMode</code>	(logical) decide if normalization should be done by multiplicative or additive factor
<code>minQuant</code>	(numeric) optional filter to set all values below given value as NA
<code>sparseLim</code>	(integer) decide at which min content of NA values the function should go in sparse-mode
<code>nCombin</code>	(NULL or integer) used only in sparse-mode (ie if content of NAs higher than content of sparseLim): Number of groups of smller matrixes with this number of columns to be inspected initailly; low values (small groups have higher chances of more common elements)
<code>omitNonAlignable</code>	(logical) allow omitting all columns which can't get aligned due to sparseness
<code>maxFact</code>	(numeric, length=2) max normalization factor
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allows easier tracking of messages produced

Details

Arguments were kept similar with function `normalizeThis` as much as possible. In most cases data get normalized by proportional factors. In case of log2-data (very common in omics-data) normalizing by an additive factor is equivalent to a proportional factor.

This function has a special mode of operation for sparse data (ie containing a high content of NA values). 0-values by themselves will be primarily considered as true measurement outcomes and not as missing. However, by using the argument `minQuant` all values below a given threshold will be set as NA and this may possibly trigger the sparse mode of normalizing.

Note : Using a small value of `nCombin` will give the highest chances of finding sufficient complete combination of columns with sparse data. However, this will also increase (very much) the computational efforts and time required to produce an output.

When using default proportional mode a potential division by 0 could occur, when the initial normalization factor turns out as 0. In this case a small value (default the maximum value of `dat / 10`) will be added to all data before normalizing. If this also creates 0-values in the data this factor will be multiplied by 0.03.

Value

This function returns a matrix of normalized data

See Also

[normalizeThis](#), [exponNormalize](#), [adjBy2ptReg](#), [justvsn](#)

Examples

```
## sparse matrix normalization
set.seed(2); AA <- matrix(rbinom(110,10,0.05), nrow=10)
AA[,4:5] <- AA[,4:5] *rep(4:3, each=nrow(AA))
AA[2,c(2,6,7)] <- 1; AA[3,8] <- 1;

(AA1 <- rowNormalize(AA))
(AA2 <- rowNormalize(AA, minQuant=1)) # set all 0 as NAs
(AA3 <- rowNormalize(AA, refLines=1:6, omitNonAlignable=FALSE, minQuant=1))
```

rowSds

sd for each row (fast execution)

Description

This function is speed optimized `sd` per row of a matrix or data.frame and treats each row as independent set of data for `sd` (equiv to `apply(dat, 1, sd)`). NAs are ignored from data unless entire line NA). Speed improvements may be seen at more than 100 lines. Note: NaN instances will be transformed to NA

Usage

```
rowSds(dat, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

dat	matrix (or data.frame) with numeric values (may contain NAs which will be ignored)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

numeric vector of sd values

See Also

[sd](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
rowSds(dat1)
```

rowSEMs

SEM for each row

Description

This function speed optimized SEM (standard error of the mean) for each row. The function takes a matrix or data.frame and treats each row as set of data for SEM; NAs are ignored from data. Note: NaN instances will be transformed to NA

Usage

```
rowSEMs(dat)
```

Arguments

dat	matrix or data.frame
-----	----------------------

Value

This function returns a numeric vector with SEM values

See Also

[rowSds](#), [colSds](#), [colSums](#)

Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
head(rowSEMs(dat1))
```

sampNoDeMArrayLM	<i>Locate Sample Index From Index Or Name Of Pair-Wise Comparisons In List Or MArrayLM-Object</i>
------------------	---

Description

When multiple series of data are tested simultaneously (eg using `moderTestXgrp`), multiple pairwise comparisons get performed. This function helps locating the groups of samples, eg respective mean-columns, corresponding to specific pairwise comparisons.

Usage

```
sampNoDeMArrayLM(
  MArrayObj,
  useComp = NULL,
  outTy = "index",
  groupSep = NULL,
  combPwSep = "combine1",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

MArrayObj	(list or MArray-object) main input, object to examine and extract pairwise question information
useComp	(character or integer, length=1) index or name of pairwise-comparison to be addressed
outTy	(character) choose if just vector of indexes (with <code>outTy="index0"</code>), matrix of indexes (organized by pairwise questions, with <code>outTy="index"</code>), or matrix of group-names (with <code>outTy="names"</code>) or list with <code>\$index0</code> (sorted unique vector or indexes), <code>\$pwGrpNa</code> , <code>\$pwIndex</code> , <code>\$concat</code> , <code>\$sep</code> and <code>\$compIndex</code> will get returned
groupSep	(NULL or character of length=1) separator for pair of names; if NULL a suitable separator (among <code>'-'</code> , <code>'-'</code> , <code>'_'</code> , <code>'_'</code> , <code>'.'</code> , <code>'.'</code> and <code>' '</code>) will be used
combPwSep	(character) sequence of separators for building combined names (may be <code>combPwSep='combine1'</code> or <code>'combine2'</code>); will be used in <code>pwSeparatorList()</code>
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

As main input one gives a list or MArrayLM-object containing testing results from pairwise comparisons, and specific comparisons indicated by useComp to get located in the elements of mean-columns (1stMeans).

Note, that that the numeric indexes should be used with caution as they refer to the levels of the groups which are sorted and thus not necessarily in the order of other elements like the group-means.

This function allows finding inverted questions (eg 'D-C' even though 'C-D' was actually run in testing), but the result will always be presented in the initial order

Value

This function returns if outTy="names" a numeric vector with indexes indicating the sorted (!! columns of (replicate) mean-values corresponding to the comparison specified in useComp; or if outTy="names" or outTy="pwGrpNa" : the (separated) names of pairwise groups will be returned as matrix (each pairwise question as separate line) or if outTy="list" a list with \$index0 (sorted unique vector or indexes), \$pwGrpNa (the separated pairwise group-names), \$pwIndex (the ith pairwise comparison), \$concat (the concatenated pairwise names), \$sep (pairwise separator) and \$compIndex

See Also

[moderTestXgrp](#), this function gets used eg in [MPlotW](#) or [VolcanoPlotW](#)

Examples

```
grp3 <- factor(rep(LETTERS[4:2], c(2,3,3)))
set.seed(2017); t8 <- matrix(round(rnorm(208*8,10,0.4), 2), ncol=8,
  dimnames=list(paste(letters[],rep(1:8,each=26),sep=""), paste0(grp3,c(1:2,1:3,1:3))))
if(requireNamespace("limma", quietly=TRUE)) { # need limma installed...
  test8 <- moderTestXgrp(t8, grp3, useComparison="all")
  head(test8$p.value) # all pairwise comparisons available
  sampNoDeMArrayLM(test8, 3)
  levels(grp3)[sampNoDeMArrayLM(test8, 3)]
  head(test8$means[,sampNoDeMArrayLM(test8, 3, outTy="names")], 3)
  head(test8$means[,sampNoDeMArrayLM(test8, "D-C", outTy="names")], 3) # inverted question
}
```

Description

This function allows convenient rescaling of data in the sense that the range covered will be adjusted to user-specified values. Instead of fixed min and max values for the output it is also possible to fix 2 given quantiles for user-specified values (and rescale by linear transformation).

Usage

```
scaleXY(
  x,
  min = 0,
  max = NULL,
  q = c(0, 1),
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	(numeric vector, matrix or data.frame) object to rescale
min	(numeric) minimum value in output, if of length=2 and max not given/valid its 2nd value will be used as max
max	(numeric) maximum value in output, defaults to 1 if not specified or use 2nd value of min (if min of length=2)
q	(numeric, length=2) vector giving quantile values to be used for setting frame of normalization (defaults to lowest and highest values expected)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a vector (or matrix) of rescaled data (in dimensions of input)

See Also

[scale](#), [normalizeThis](#), [blockNormalize](#)

Examples

```
## simple vector
scale(11:19) # standardizes (base R), is not 'rescaling'
scaleXY(11:19) # range from 0 to 1
scaleXY(11:19, min=1, max=10)
scaleXY(11:19, c(1, 10)) # min & max as single argument
# rescale matrix with NA
## rescale to 20th and 80th quantile (ie other than min or max)
scaleXY(11:19, min=1, max=10, q=c(0.2, 0.8))

## rescale matrix with NA
mat1 <- matrix(11:20, ncol=2, dimnames=list(letters[1:5], c("A","B")))
mat1[2,1] <- NA
scaleXY(mat1)
scaleXY(mat1, min=1, max=10, q=c(0.2, 0.8))
```

```
## rescale for each column individually
dat2 <- apply(mat1, 2, scaleXY, 1, 100)
range(dat2)
summary(dat2)
```

searchDataPairs

Search duplicated data over multiple columns, ie pairs of data

Description

searchDataPairs searches matrix for columns of similar data, ie 'duplicate' values in separate columns or very similar columns if realDupsOnly=FALSE. Initial distance measures will be normalized either to diagonale (normRange=TRUE) of 'window' or to the real max distance observed (equal or less than diagonale). Return data.frame with names for sample-pair, percent of identical values (100 for complete identical pair) and relative (Euclidean) distance (ie max dist observed =1.0). Note, that low distance values do not necessarily imply correlating data.

Usage

```
searchDataPairs(
  dat,
  disThr = 0.01,
  byColumn = TRUE,
  normRange = TRUE,
  altNa = NULL,
  realDupsOnly = TRUE,
  silent = FALSE,
  callFrom = NULL
)
```

Arguments

dat	matrix or data.frame (main input)
disThr	(numeric) threshold to decide when to report similar data (applied on normalized distances, low val fewer reported), applied on normalized distances (norm to diagonale of all data for best relative 'unbiased' view)
byColumn	(logical) rotates main input by 90 degrees (using <code>t</code>), thus allows to read by rows instead of by columns
normRange	(logical) normalize each columns separately if TRUE
altNa	(character, default NULL) vector with alternative names (for display)
realDupsOnly	(logical) if TRUE will consider equal values only, otherwise will also consider very close values (based on argument <code>disThr</code>)
silent	(logical) suppres messages
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a data.frame with names of sample-pairs, percent of identical values (100 for complete identical pair) and rel (Euclidean) distance (ie max dist observed =1.0)

See Also

[duplicated](#)

Examples

```
mat <- round(matrix(c(11:40,runif(20)+12,11:19,17,runif(20)+18,11:20), nrow=10), 1)
colnames(mat) <- 1:9
searchDataPairs(mat,disThr=0.05)
```

searchLinesAtGivenSlope

Search Points Forming Lines At Given Slope

Description

This function searches among set of points (2-dim) those forming line(s) with user-defined slope ('coeff'), ie search optimal (slope-) offset parameter(s) for (regression) line(s) with given slope ('coef'). Note: larger data-sets : segment residuals to 'coeff' & select most homogenous

Usage

```
searchLinesAtGivenSlope(
  dat,
  coeff = 1.5,
  filtExtr = c(0, 1),
  minMaxDistThr = NULL,
  lmCompare = TRUE,
  indexPoints = TRUE,
  displHist = FALSE,
  displScat = FALSE,
  bestCluByDistRat = TRUE,
  neighbDiLim = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

dat	matrix or data.frame, main input
coeff	(numeric) slope to consider

filtExtr	(integer) lower & upper quantile values, remove points with extreme deviation to offset=0, (if single value: everything up to or after will be used)
minMaxDistThr	(logical) optional minimum and maximum distance threshold
lmCompare	(logical) add'l fitting of linear regression to best results, return offset AND slope based on lm fit
indexPoints	(logical) return results as list with element 'index' specifying retained points
displHist	(logical) display histogram of residues
displScat	(logical) display (simple) scatter plot
bestCluByDistRat	(logical) initial selection of decent clusters based on ratio overallDist/averNeighbDist (or by CV & cor)
neighbDiLim	(numeric) additional threshold for (trimmed mean) neighbour-distance
silent	(logical) suppress messages
debug	(logical) for bug-tracking: more/enhanced messages
callFrom	(character) allow easier tracking of messages produced

Details

Note: The package MASS is required when using as `lmCompare=TRUE`. For larger data the function will try using the package NbClust (available from CRAN) if installed.

Value

This functions returns a matrix of line-characteristics (or if `indexPoints` is TRUE then list (line-characteristics & index & lm-results))

See Also

[lm](#)

Examples

```
set.seed(2016); ra1 <- runif(300)
dat1 <- cbind(x=round(c(1:100+ra1[1:100]/5, 4*ra1[1:50]),1),
             y=round(c(1:100+ra1[101:200]/5, 4*ra1[101:150]), 1))
(li1 <- searchLinesAtGivenSlope(dat1, coeff=1))
```

simpleFragFig	<i>Simple figure showing line from start- to end-sites of edges (or fragments) defined by their start- and end-sites simpleFragFig draws figure showing start- and end-sites of edges (or fragments)</i>
---------------	--

Description

Simple figure showing line from start- to end-sites of edges (or fragments) defined by their start- and end-sites

simpleFragFig draws figure showing start- and end-sites of edges (or fragments)

Usage

```
simpleFragFig(
  frag,
  fullSize = NULL,
  sortByHead = TRUE,
  useTit = NULL,
  useCol = NULL,
  displNa = TRUE,
  useCex = 0.7
)
```

Arguments

frag	(matrix) 2 columns defining begin- and end-sites (as interger values)
fullSize	(integer) optional max size used for figure (x-axis)
sortByHead	(logical) sort by begin-sites (if TRUE) or sort by end-sites
useTit	(character) custom title
useCol	(character) specify colors, if numeric vector will be onsidered as score values
displNa	(character) display names of edges (figure may get crowded)
useCex	(numeric) expansion factor, see also par

Value

matrix with mean values

See Also

[buildTree](#), [countSameStartEnd](#), [contribToContigPerFrag](#),

Examples

```
frag2 <- cbind(beg=c(2,3,7,13,13,15,7,9,7, 3,7,5,7,3),end=c(6,12,8,18,20,20,19,12,12, 4,12,7,12,4))
rownames(frag2) <- c("A","E","B","C","D","F","H","G","I", "J","K","L","M","N")
simpleFragFig(frag2,fullSize=21,sortByHead=TRUE)
buildTree(frag2)
```

singleLineAnova	<i>2-factorial Anova on single line of data</i>
-----------------	---

Description

This function runs 2-factorial Anova on a single line of data (using [aov](#) from package `stats`) using a model with two factors (without factor-interaction) and extracts the corresponding p-value.

Usage

```
singleLineAnova(  
  dat,  
  fac1,  
  fac2,  
  inclInteraction = TRUE,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

<code>dat</code>	numeric vector
<code>fac1</code>	(character or factor) vector describing grouping elements of <code>dat</code> for first factor, must be of same length as <code>fac2</code>
<code>fac2</code>	(character or factor) vector describing grouping elements of <code>dat</code> for second factor, must be of same length as <code>fac1</code>
<code>inclInteraction</code>	(logical) decide if factor-interactions (eg synergy) should be included to model
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

This function returns the (uncorrected) p for factor 'Pr(>F)' (see [aov](#))

See Also

[aov](#), [anova](#); for repeated tests using the package [limma](#) including [lmFit](#) and [eBayes](#) see [test2factLimma](#)

Examples

```
set.seed(2012); dat <- round(runif(8),1)  
singleLineAnova(dat, gl(2,4),rep(1:2,4))
```

 sortBy2CategorAnd1IntCol

Sort matrix by two categorical and one integer columns

Description

This function sorts matrix 'mat' subsequently by categorical and numerical columns of 'mat', ie lines with identical values for categor are sorted by numeric value.

Usage

```
sortBy2CategorAnd1IntCol(
  mat,
  categCol,
  numCol,
  findNeighb = TRUE,
  decreasing = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

mat	matrix (or data.frame) from which by 2 columns will be selected for sorting
categCol	(integer or character) which columns of 'mat' to be used as categorical columns
numCol	(integer or character) which column of 'mat' to be used as integer columns
findNeighb	(logical) if 'findNeighb' neighbour cols according to 'numCol' will be identified as groups & marked in new col 'neiGr', orphans marked as NA
decreasing	(logical) order of sort
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a sorted matrix (same dimensions as 'mat')

Examples

```
mat <- cbind(aa=letters[c(3,rep(7:8,3:4),4,4:6,7)],bb=LETTERS[rep(1:5,c(1,3,4,4,1))],
  nu=c(23:21,23,21,22,18:12))
mat[c(3:5,1:2,6:9,13:10),]
sortBy2CategorAnd1IntCol(mat,cate=c("bb","aa"),num="nu",findN=FALSE,decr=TRUE)
sortBy2CategorAnd1IntCol(mat,cate=c("bb","aa"),num="nu",findN=TRUE,decr=FALSE)
```

 sortByNRepeated

Make a list of common occurrences sorted by number of repeats

Description

The aim of this function is to count the number of occurrences of words when comparing separate vectors (x , y and z) or from a list (given as x) and to give an output sorted by their frequency. The output lists the various values/words by their frequency, the names of the resulting list-elements indicate number of times the values/words were found repeated.

Usage

```
sortByNRepeated(
  x,
  y = NULL,
  z = NULL,
  filterIntraRep = TRUE,
  silent = TRUE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	(list, character or integer) main input, if list, arguments y and z will not be used
y	(character or integer) supplemental vector to compare with x
z	(character or integer) supplemental vector to compare with x
filterIntraRep	(logical) allow making vectors x , y and z unique before comparing (defaults to TRUE)
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

In order to compare the frequency of values/words between separate vectors or vectors within a list, it is necessary that these have been made unique before calling this function or using filterIntraRep=TRUE.

In case the input is given as list (in x), there is no restriction to the number of vectors to be compared. With very long lists, however, the computational effort increases (like it does when using table)

Value

This function returns a list sorted by number of occurrences. The names of the list indicate the number of repeats.

See Also

[table](#), [replicateStructure](#)

Examples

```
sortByNRepeated(x=LETTERS[1:11], y=LETTERS[3:13], z=LETTERS[6:12])
sortByNRepeated(x=LETTERS[1:11], y=LETTERS[c(3:13,5:4)], z=LETTERS[6:12])
```

stableMode	<i>Estimate Mode (Most Frequent Value)</i>
------------	--

Description

Estimate mode, ie most frequent value. In case of continuous numeric data, the most frequent values may not be the most frequently repeated exact term. This function offers various approaches to estimate the mode of a numeric vector. Besides, it can also be used to identify the most frequent exact term (in this case also from character vectors).

Usage

```
stableMode(
  x,
  method = "density",
  finiteOnly = TRUE,
  bandw = NULL,
  rangeSign = 1:6,
  silent = FALSE,
  callFrom = NULL,
  debug = FALSE
)
```

Arguments

x	(numeric, or character if 'method='mode') data to find/estimate most frequent value
method	(character) There are 3 options : BBmisc, binning and density (default). If "binning" the function will search context dependent, ie like most frequent class of histogram. Using "binning" mode the search will be refined if either 80 percent of values in single class or >50 percent in single class.
finiteOnly	(logical) suppress non-finite values; allows avoiding NULL as result in presence of some Inf values; NA will be ignored in any case
bandw	(integer) only used when method="binning" or method="density" : defines the number of points to look for density or number of classes used; very "critical" parameter, may change results in strong way. Note: with method="binning": At higher values for "bandw" you will finally loose advantage of histLike-type search of mode !

rangeSign	(integer) only used when method="binning": range of numbers used as number of significant values
silent	(logical) suppress messages
callFrom	(character) allows easier tracking of messages produced
debug	(logical) additional messages for debugging

Details

The argument method allows to choose among (so far) 4 different methods available. If "density" is chosen, the most dense region of sqrt(n) values will be chosen; if "binning", the data will be binned (like in histograms) via rounding to a user-defined number of significant values ("rangeSign"). If method is set to "BBmisc", the function computeMode() from package **BBmisc** will be used. If "mode" is chosen, the first most frequently occurring (exact) value will be returned, if "allModes", all ties will be returned. This last mode also works with character input.

Value

This function returns a numeric vector with value of mode, the name of the value indicates it's position

See Also

computeMode() in package **BBmisc**

Examples

```
set.seed(2012); dat <- round(c(rnorm(50), runif(100)),3)
stableMode(dat)
```

standardW

Standardize (scale) data

Description

This functions work similar to [scale](#), however, it evaluates the entire input and not column-wise (and independtly as scale does). With Standarizing we speak of transforming the data to end up with mean=0 and sd=1. Furthermore, in case of 3-dim arrays, this function returns also an object with the same dimensions as the input.

Usage

```
standardW(
  mat,
  byColumn = FALSE,
  na.rm = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

mat	(matrix, data.frame or array) data that need to get standardized.
byColumn	(logical) if TRUE the function will be run independently over all columns such as <code>apply(mat, 2, standardW)</code>
na.rm	(logical) if NAs in the data don't get ignored via this argument, the output will be all NA
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This functions retruns a vector of rescaled data (in dimensions as input)

See Also

[scale](#)

Examples

```
dat <- matrix(2*round(runif(100),2), ncol=4)
mean(dat); sd(dat)
```

```
dat2 <- standardW(dat)
apply(dat2, 2, sd)
summary(dat2)
```

```
dat3 <- standardW(dat, byColumn=TRUE)
apply(dat2, 2, sd)
summary(dat2)
mean(dat2); sd(dat2)
```

stdErrMedBoot

Standard Error Of Median by Boot-Strap

Description

stdErrMedBoot estimate standard error of median by bootstrap approach. Note: requires package [boot](#)

Usage

```
stdErrMedBoot(x, nBoot = 9, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

x	(numeric) vector to estimate median and it's standard error
nBoot	(integer) number for iterations
silent	(logical) suppress messages
debug	(logical) display additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a (numeric) vector with estimated standard error

See Also

[colMedSds](#) and [rowMedSds](#); based on [boot](#)

Examples

```
set.seed(2014); ra1 <- c(rnorm(9,2,1),runif(8,1,2))
rat1 <- ratioAllComb(ra1[1:9],ra1[10:17])
median(rat1); stdErrMedBoot(rat1)
```

summarizeCols

Summarize columns (as median,mean,min,last or other methods)

Description

summarizeCols summarizes all columns of matrix (or data.frame). In case of text-columns the sorted middle (~median) will be given, unless 'maxAbsLast', 'minAbsLast', .. consider only last column of 'matr' : choose from all columns the line where (max of) last col is at min; 'median-Complete' or 'meanComplete' considers only lines/rows where no NA occur (NA have influence other columns !)

Usage

```
summarizeCols(
  matr,
  meth = "median",
  refCol = NULL,
  nEqu = FALSE,
  supl = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<code>matr</code>	data.frame matrix of data to be summarized by column (may do different method for text and numeric columns)
<code>meth</code>	(character) summarization method, may be 'mean', 'aver', 'median', 'sd', 'CV', 'min', 'max', 'first', 'last', 'medianComplete' or 'meanComplete', 'n' (number of non-NA elements), 'n.NA' (number of NA elements), 'NULL' (returns NULL)
<code>refCol</code>	(character or integer) column to be used as reference
<code>nEq</code>	(logical) if TRUE, add additional column indicating the number of equal lines for choice (only with min or max)
<code>supl</code>	(numeric) supplemental parameters for the various summarizing functions (eg used with <code>meth="trimmedMean"</code> , <code>supl=c(l=0.1,u=0.2)</code> to pass arguments to trimmedMean)
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allows easier tracking of messages produced

Details

The argument `method` allows options that treat (summarize) all columns independently or to select one line (based on argument `refCol`)

Value

vector with summary for each column

See Also

[colSums](#); if data has subgroups to be used in a [tapply](#)-way please see [makeNRedMatr](#)

Examples

```
t1 <- matrix(round(runif(30,1,9)),nc=3); rownames(t1) <- letters[c(1:5,3:4,6:4)]
summarizeCols(t1, me="median")
t(sapply(by(t1,rownames(t1), function(x) x), summarizeCols,me="maxAbsLast"))
t3 <- data.frame(ref=rep(11:15,3), tx=letters[1:15],
  matrix(round(runif(30,-3,2),1), ncol=2), stringsAsFactors=FALSE)
by(t3,t3[,1], function(x) x)
by(t3,t3[,1], function(x) summarizeCols(x, me="maxAbsLast"))
t(sapply(by(t3, t3[,1], function(x) x), summarizeCols, me="maxAbsLast"))
```

sumNAperGroup	<i>Count number of NAs per sub-set of columns</i>
---------------	---

Description

This function will count the number of NAs per group (defined by argument `grp`) while summing over all lines of a matrix or data.frame. The row-position has no influence on the counting. Using the argument `asRelative=TRUE` the result will be given as (average) number of NAs per row and group.

Usage

```
sumNAperGroup(  
  x,  
  grp,  
  asRelative = FALSE,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

<code>x</code>	matrix or data.frame which may contain NAs
<code>grp</code>	factor describing which column of 'dat' belongs to which group
<code>asRelative</code>	(logical) return as count of NAs per row and group
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

This function returns an integer vector with count of NAs per group

See Also

[NA](#), filter NAs by line [presenceFilt](#)

Examples

```
mat <- matrix(1:25, ncol=5)  
mat[lower.tri(mat)] <- NA  
sumNAperGroup(mat, rep(1:2,c(3,2)))  
sumNAperGroup(mat, rep(1:2,c(3,2)), asRelative=TRUE)
```

sysDate	<i>System-date (compressed format)</i>
---------	--

Description

This function returns current date (based on Sys.Date) in different format options.

Usage

```
sysDate(style = "univ1")
```

Arguments

style (character) choose style (default 'univ1' for very compact style)

Details

Multiple options for formatting exist : 'univ1' or 'wr' ... (default) compact style using day, first 3 letters of English name of month (lowercaps) and last 2 letters of year as ddmmmyy, eg 14jun21

'univ2' ... as ddMmmyy, eg 14Jun21

'univ3' ... as ddMonthyyyy, eg 14June2021

'univ4' ... as ddmonthyyyy, eg 14june2021

'univ5' ... as yyyy-mm-dd (output of Sys.Date()), eg 2021-06-14

'univ6' ... as yyyy-number of day (in year), eg 2021-165

'local1' ... compact style using day, first 3 letters of current locale name of month (not necessarily unique !) and last 2 letters of year as ddmmmyy, eg 14jui21

'local2' ... as ddMmmyy, month based on current locale (not necessarily unique !), eg 14Jui21

'local3' ... as ddMonthyyyy, month based on current locale , eg 14Juin2021

'local4' ... as ddmonthyyyy, month based on current locale , eg 14juin2021

'local5' ... as dd-month-yyyy, month based on current locale , eg 14-juin-2021

'local6' ... as yyymonthddd, month based on current locale , eg 2021juin14

Value

character vector with formatted date

See Also

[date](#), [Sys.Date](#) and [Sys.time](#),

Examples

```
sysDate()
```

tableToPlot

Print matrix-content as plot

Description

This function prints all columns of matrix in plotting region for easier inclusion to reports (default values are set to work for output as A4-sized pdf). It was made for integrating listings of text to graphical output to devices like png, jpeg or pdf.

Usage

```
tableToPlot(
  matr,
  colPos = c(0.05, 0.35, 0.41, 0.56),
  useCex = 0.7,
  useAdj = c(0, 1, 1, 0),
  titOffs = 0,
  useCol = 1,
  silent = FALSE,
  callFrom = NULL
)
```

Arguments

matr	(matrix) main (character) matrix to display
colPos	(numeric) position of columns on x-scale (from 0 to 1)
useCex	(numeric) cex expansion factor for size of text (may be different for each column)
useAdj	(numeric) left/center/right alignment for text (may be different for each column)
titOffs	(numeric) offset for title line (relative to 'colPos')
useCol	color specification for text (may be different for each column)
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of message(s) produced

Details

This function was initially designed for listings with small/medium 1st col (eg counter or index), 2nd & 3rd col small and long 3rd col (like file paths). Obviously, the final number of lines one can pack and still read correctly into the graphical output depends on the size of the device (on a pdf of size A4 one can pack up to approx. 110 lines). Of course, [Sweave](#), combined with LaTeX, provides a powerful alternative for wrapping text to pdf-output (and further combining text and graphics). Note: The final result on pdf devices may vary depending on screen-size (ie with of current device), the parameters 'colPos' and 'titOffs' may need some refinements. Note: In view of typical page/figure layouts like A4, the plotting region will be split to avoid too wide spacing between rows with less than 30 rows.

Value

This function returns NULL (no R-object returned), print 'plot' in current device only

See Also

[Sweave](#) for more flexible framework

Examples

```
## as example let's make a listing of file-names and associated parameters in current directory
mat <- dir()
mat <- cbind(no=1:length(mat), fileName=mat, mode=file.mode(mat),
            si=round(file.size(mat)/1024), path=getwd())
## Now, we wrap all text into a figure (which could be saved as jpg, pdf etc)
tableToPlot(mat[, -1], colPos=c(0.01, 0.4, 0.46, 0.6), titOffS=c(0.05, -0.03, -0.01, 0.06))
tableToPlot(mat, colPos=c(0, 0.16, 0.36, 0.42, 0.75), useAdj=0.5, titOffS=c(-0.01, 0, -0.01, 0, -0.1))
```

test2factLimma	<i>2-Factorial Limma-Style t-Test</i>
----------------	---------------------------------------

Description

The aim of this function is to provide convenient acces to two-factorial (linear) testing withing the framework of [makeMAlist](#) including the emprical Bayes shrinkage. The input data 'datMatr' which should already be organized as limma-type MAlist, eg using using [makeMAlist](#). Note: This function uses the Bioconductor package [limma](#) (which must be installed).

Usage

```
test2factLimma(
  datMatr,
  fac1,
  fac2,
  testSynerg = FALSE,
  testOrientation = "=",
  addResults = c("lfdr", "FDR", "Mval", "means"),
  addGenes = NULL,
  silent = FALSE,
  callFrom = NULL,
  debug = FALSE
)
```

Arguments

datMatr	matrix or data.frame with lines as indenpendent series of measures (eg different genes)
fac1	(character or factor) vector describing grouping elements of each line of 'datMatr' for first factor, must be of same length as fac2

fac2	(character or factor) vector describing grouping elements of each line of 'dat-Matr' for second factor, must be of same length as fac1
testSynerg	(logical) decide if factor-interactions (eg synergy) should be tested in model, otherwise additive factors are supposed
testOrientation	(character) default (or any non-recognized input) '=', otherwise either '>', 'greater', 'sup', 'upper' or '<', 'inf', 'lower'
addResults	(character) vector defining which types of information should be included to output, may be 'lfdR', 'FDR' (for BY correction), 'Mval' (M values), 'means' (matrix with mean values for each group of replicates)
addGenes	(matrix or data.frame) additional information to add to output
silent	(logical) suppress messages
callFrom	(character) allow easier tracking of messages produced
debug	(logical) additional messages for debugging

Value

This function returns an object of class "MArrayLM" (from limma) containing/enriched by the testing results

See Also

[makeMAList](#), single line testing [lmFit](#) and the eBayes-family of functions in package [limma](#)

Examples

```
set.seed(2014)
dat0 <- rnorm(30) + rep(c(10,15,19,20),c(9,8,7,6))
fa <- factor(rep(letters[1:4],c(9,8,7,6)))
dat2 <- data.frame(facA=rep(c("-", "A", "-", "A"), c(9,8,7,6)),
  facB= rep(c("-", "-", "B", "B"), c(9,8,7,6)), dat1=dat0, dat2=runif(30))
grpNa <- sub("-", "", sub("\\.", "", apply(dat2[,1:2], 1, paste, collapse="")))
test2f <- test2factLimma(t(dat2[,3:4]), dat2$facA, dat2$facB)
test2f      # just the p-values
# Similarly, you can easily summarize results using topTable from limma
if(requireNamespace("limma", quietly=TRUE)) {
  test2g <- test2factLimma(t(dat2[,3:4]), dat2$facA, dat2$facB, addR=FALSE)
  library(limma)
  topTable(test2g, coef=1, n=5)
  topTable(test2g, coef=2, n=5) }
```

top3mean	<i>Mean Of 3 Highest Values</i>
----------	---------------------------------

Description

This function returns the mean of the top3 highest values.

Usage

```
top3mean(x, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

x	(numeric vector) main input
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Details

Generally, NA will be excluded, if all values are NA this function will return NULL ; thus, in case of (entirely) unsuitable data (non-numeric ...) NULL will be returned. If data has subgroups you may try a tapply -way.

Value

This function returns a vector with single numeric value for mean of top3 (returns NULL with invalid input or if all input is NA)

See Also

[mean](#)

Examples

```
x1 <- c(15:11,NA,16)
top3mean(x1)
```

transpGraySca	<i>Make single vector gray-gradient</i>
---------------	---

Description

This function helps making gray-gradients. Note : The resulting color gradient does not seem linear to the human eye, you may try [gray.colors](#) instead

Usage

```
transpGraySca(startGray = 0.2, endGrey = 0.8, nSteps = 5, transp = 0.3)
```

Arguments

startGray	(numeric) gray shade at start
endGrey	(numeric) gray shade at end
nSteps	(integer) number of levels
transp	(numeric) transparency alpha

Value

character vector (of same length as x) with color encoding

See Also

[gray.colors](#)

Examples

```
layout(1:2)
col1 <- transpGraySca(0.8,0.3,7,0.9)
pie(rep(1,length(col1)), col=col1, main="from transpGraySca")
col2 <- gray.colors(7,0.9,0.3,alph=0.9)
pie(rep(1,length(col2)), col=col2, main="from gray.colors")
```

treatTxtDuplicates	<i>Locate duplicates in text and make non-redundant</i>
--------------------	---

Description

treatTxtDuplicates locates dupliques in character-vector 'x' and return list (length=3) : with \$init (initial), \$nRed .. non-redundant text by adding number at end or beginning, and \$nrLst .. list-version with indexes per unique entry. Note : NAs (if multiple) will be renamed to NA_1, NA_2

Usage

```
treatTxtDuplicates(
  x,
  atEnd = TRUE,
  sep = "_",
  onlyCorrectToUnique = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	(character) vector with character-entries to identify (and remove) duplicates
atEnd	(logical) decide location of placing the counter (at end or at beginning of ID) (see correctToUnique)
sep	(character) separator to add before counter when making non-redundant version
onlyCorrectToUnique	(logical) if TRUE, return only vector of non-redundant
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

list with \$init, \$nRed, \$nrLst

See Also

For simple correction use [correctToUnique](#)

Examples

```
treatTxtDuplicates(c("li0", NA, rep(c("li2", "li3"), 2)))
correctToUnique(c("li0", NA, rep(c("li2", "li3"), 2)))
```

 triCoord

Pairwise x,y Combinations

Description

This function gets pairwise combinations for 'n' elements; returns matrix with x & y coordinates to form all pairwise groups for 1:n elements

Usage

```
triCoord(n, side = "upper", silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

n	(integer) number of elements for making all pair-wise combinations
side	(character) "upper" or "lower"
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a 2-column matrix with indexes for all pairwise combinations of 1:n

See Also

[upperMaCoord](#), [getPWseparator](#), [indexGroupsFromPW](#), [diffCombin](#); [combn](#), [lower.tri](#) or [upper.tri](#), simpler version [upperMaCoord](#)

Examples

```
triCoord(4)
```

trimmedMean	<i>Trimmed Mean</i>
-------------	---------------------

Description

This function allows more flexible options for calculating a trimmed mean compared to mean (from the base-package). For example, the trimming may be asymmetric to the median of the data.

Usage

```
trimmedMean(  
  dat,  
  trim = c(l = 0.2, u = 0.2),  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

Arguments

dat	(numeric) numeric vector
trim	(numeric, length=2) specifies how data should get trimmed, lower and upper fraction(s) to exclude have to be assigned separately. The lower and upper fraction may be named 'l' and 'u'. The value 0 means that all (sorted) data on a given side will be used.
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Details

If the second value of trim is <0.5 it is supposed that this indicates a fraction from the upper end the vector-dat as `mean` does. Otherwise, `trim=c(l=0.2, u=0.7)` will be interpreted indication to use the 20th percentile to 70th percentile of dat.

Please note, that trimmed means - and in particular asymmetric trimmed means - should be used with caution as there is also a risk of introducing bias.

Value

This function returns a (numeric) vector with the trimmed mean

See Also

`mean` (symmetric trimming only)

Examples

```
x <- c(17:11,27:28)
mean(x); mean(x, trim=0.15)
trimmedMean(x, trim=c(l=0, u=0.7)) # asymmetric trim
```

trimRedundText	<i>Trim redundant text</i>
----------------	----------------------------

Description

This function allows trimming/removing redundant text-fragments (redundant from head or tail) out of character vector 'txt'.

Usage

```
trimRedundText(
  txt,
  minNchar = 1,
  side = "both",
  spaceElim = FALSE,
  silent = TRUE,
  callFrom = NULL,
  debug = FALSE
)
```

Arguments

txt	character vector to be treated
minNchar	(integer) minimum number of characters that must remain
side	(character) may be either 'both', 'left' or 'right'
spaceElim	(logical) optional removal of any heading or tailing white space
silent	(logical) suppress messages
callFrom	(character) allows easier tracking of messages produced
debug	(logical) display additional messages for debugging

Value

This function returns a modified character vector

See Also

[rmSharedWords](#); Inverse search : Find/keep common text [keepCommonText](#); [checkUnitPrefix](#);
you may also look for related functions in package [stringr](#)

Examples

```
txt1 <- c("abcd_ccc", "bcd_ccc", "cde_ccc")
trimRedundText(txt1, side="right")      # trim from right

txt2 <- c("ddd_ab", "ddd_bcd", "ddd_cde")
trimRedundText(txt2, side="left")      # trim from left
```

tTestAllVal

t.test on all individual values against all other values

Description

Run `t.test` on each indiv value of `x` against all its neighbours (=remaining values of same vector) in order to test if tis value is likely to belong to vector `x`. This represents a repeated leave-one-out testing. Mutiple choices for multiple testing correction are available.

Usage

```
tTestAllVal(
  x,
  alph = 0.05,
  alternative = "two.sided",
  p.adj = NULL,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<code>x</code>	matrix or data.frame
<code>alph</code>	(numeric) threshold alpha (passed to <code>t.test</code>)
<code>alternative</code>	(character) will be passed to <code>t.test</code> as argument 'alternative', may be "two.sided", ..
<code>p.adj</code>	(character) multiple test correction : may be NULL (no correction), "BH", "BY", "holm", "hochberg" or "bonferroni" (but not 'fdr' since this may be confounded with local false discovery rate), see p.adjust
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

This function returns a numeric vector with p-values or FDR (depending on argument `p.adj`)

See Also

[t.test](#), [p.adjust](#)

Examples

```
set.seed(2016); x1 <- rnorm(100)
allTests1 <- tTestAllVal(x1)
hist(allTests1, breaks="FD")
```

Description

The aim of this function is to provide help in automatically harmonizing enumerators at the end of sample-names. When data have same grouped setup/design, many times this is reflected in their names, eg 'A_sample1', 'A_sample2' and 'B_sample1'. However, human operators may use multiple similar (but not identical) ways of expressing the same meanin, eg writng 'A_Samp_1'. This function allows testing a panel of different extensions of enumerators and (if recognized) to replace them by a user-defined standard text/enumerator. Please note that the more recent function [rmEnumeratorName](#) offers better/more flexible options.

Usage

```
unifyEnumerator(
  x,
  refSep = "_",
  baseSep = c("\\-", "\\ ", "\\."),
  suplEnu = c("Repl", "Rep", "R", "Number", "No", "Sample", "Samp"),
  stringentMatch = TRUE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	(character) main input
refSep	(character) separator for output
baseSep	(character) basic separators to test (you have to protect special characters)
suplEnu	(character) additional text
stringentMatch	(logical) decide if enumerator text has to be found in all instances or only once
silent	(logical) suppress messages
debug	(logical) display additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

This function has been developed for matching series of the same samples passing in parallel through different evaluation software (see R package `wrProteo`). The way human operators may name things may easily leave room for surprises and this function allows testing only a limited number of common ways of writing. Thus, in any case, the user is advised to inspect the results by eye and - if needed- to adjust the parameters.

Basically enumerator separators can be constructed by combing a base-separator `baseSep` (like '-', '_' etc) and an enumerator-abbreviation `suplEnu`. Then, all possible combinations will be tested if they occur in the text `x`. Furthermore, the text searched has to be followed by one or multiple digits at the end of text-entry (decimal comma-separators etc are not allowed). Thus, if there is other 'free text' following to the right after the enumerator-text this function will not find any enumerators to replace.

The argument `stringentMatch` allows defining if this text has to be found in all text-entries of `x` or just one of them. When using `stringentMatch=FALSE` there is risk that other text not meant to design enumerators may be picked up and modified.

Please note, that with large data-sets (ie many columns) testing/checking a larger panel of enumerator-abbreviations may result in slower performance. In cases of larger data-sets it may be more effective to first study the data and then run simple substitutions using `sub` targeted for this very case.

Value

This function returns a character vector of same length as input `x`, with its content as adjusted enumerators

See Also

`rmEnumeratorName` for better/more flexible options; `grep` or `sub()`, etc if exact and consistent patterns are known

Examples

```
unifyEnumerator(c("ab-1", "ab-2", "c-3"))
unifyEnumerator(c("ab-R1", "ab-R2", "c-R3"))
unifyEnumerator(c("ab-1", "c3-2", "dR3"), strin=FALSE);
```

uniquCountReport	<i>Report number of unique and redundant elements (optional figure)</i>
------------------	---

Description

Make report about number of unique and redundant elements of vector 'dat'. Note : fairly slow for long vectors !!

Usage

```
uniquCountReport(
  dat,
  frL = NULL,
  plotDispl = FALSE,
  tit = NULL,
  col = NULL,
  radius = 0.9,
  sizeTo = NULL,
  clockwise = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<code>dat</code>	(character or numeric vector) main input where number of unique (and redundant) should be determined
<code>frL</code>	(logical) optional (re-)introducing results from duplicated to shorten time of execution
<code>plotDispl</code>	(logical) decide if pie-type plot should be produced
<code>tit</code>	(character) optional title in plot
<code>col</code>	(character) custom colors in pie
<code>radius</code>	(numeric) radius passed to pie
<code>sizeTo</code>	(numeric or character) optional reference group for size-population relative adjusting overall surface of pie
<code>clockwise</code>	(logical) argument passed to pie
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

vector with counts of `n` (total), `nUnique` (wo any repeated), `nHasRepeated` (first of repeated), `nRedundant`), optional figure

See Also

[correctToUnique](#), [unique](#)

Examples

```
layout(1:2)
uniqCountReport(rep(1:7,1:7),plot=TRUE)
uniqCountReport(rep(1:3,1:3),plot=TRUE,sizeTo=rep(1:7,1:7))
```

upperMaCoord *(upper) pairwise x,y combinations*

Description

upperMaCoord gets pairwise combinations for 'n' elements; return matrix with x & y coordinates to form all pairwise groups for n elements. But no distinction of 'upper' or 'lower' possible like in [triCoord](#)

Usage

```
upperMaCoord(n, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

n	(integer) number of elements for making all pair-wise combinations
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Value

This function returns a 2-column matrix with indexes for all pairwise combinations of 1:n

See Also

[lower.tri](#), more evolved version [triCoord](#)

Examples

```
upperMaCoord(4)
```

vectorDistAngle	<i>Vector Distance and Angle</i>
-----------------	----------------------------------

Description

Compute the Euclidean distance and angle (in radians) for 2-dimensional vectors defined by start and end points in the first and second columns of arguments x and y.

Usage

```
vectorDistAngle(
  x,
  y,
  addCoord = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	(numeric matrix or data.frame of 2 column, min 2 rows) describes start & end x-coordinates
y	(numeric matrix or data.frame of 2 column, min 2 rows) describes start & end x-coordinates
addCoord	(logical) add original start and end-coordinates to output
silent	(logical) suppress messages
debug	(logical) display additional messages for debugging
callFrom	(character) allow easier tracking of messages produced).

Details

The input `x` and `y` is considered as describing start- and end-points of vectors in two-dim space. Each row of `x` describes the starting and end-points of separate (and independent) vectors along the `x`- and `y`-axis.

Then, the function calculates for each line the **distance** as Euclidean distance and the **angle** as `atan2(y_diff, x_diff)` in radians (range: `[-pi, pi]`), measured counterclockwise from the positive `x`-axis.

This function was designed for movement trajectories or any paired coordinate data where direction and magnitude matter. If `x` and `y` contain more than 2 columns, these additional columns will be ignored.

Value

This function returns a data.frame with the columns:

```
'dist'      Numeric vector of Euclidean distances
'angle'     Numeric vector of angles in radians
```

Optionally the original start and end-coordinates to output may get added if `addCoord=TRUE`

See Also

[dist](#), [Trig](#)

Examples

```
x <- matrix(c(0, 3, 0.5, 4, 1, 1), ncol=2, byrow=TRUE) # x: (0,0)→(3,0), (0,0)→(4,0), (0,0)→(0,0)
y <- matrix(c(0, 0, 1, 3, 0.5, 5), ncol=2, byrow=TRUE) # y: (0,0)→(0,0), (0,0)→(3,0), (0,0)→(5,0)
(vectDist <- vectorDistAngle(x, y))

plot(cbind(x=as.numeric(x),y=as.numeric(y)), main="Example for vectorDistAngle()",las=1)
arrows(x[,1],y[,1],x[,2],y[,2])
text(x[,2], 0.1 +y[,2], paste0("dist=",round(vectDist[,1],2),
", angle=",round(vectDist[,2],2)), adj=1)
```

volcanoFilter

Filter Statistical Testing Results in Volcano-Plot Like Fashion This function allows filtering statistical testing results combined with M-values (log2 fold-change) and other filtering criteria. All suitable values can be extracted from objects created from package wrProteo (and limma) may get used automatically. The outcome can be used for Volcano-plots or exporting tables.

Description

Filter Statistical Testing Results in Volcano-Plot Like Fashion

This function allows filtering statistical testing results combined with M-values (log₂ fold-change) and other filtering criteria. All suitable values can be extracted from objects created from package wrProteo (and limma) may get used automatically. The outcome can be used for Volcano-plots or exporting tables.

Usage

```
volcanoFilter(
  Mvalue,
  pValue = NULL,
  useComp = 1,
  filtFin = NULL,
  FCthrs = NULL,
  FdrList = NULL,
  FdrThrs = NULL,
  FdrType = NULL,
  signifOnly = TRUE,
  annotColumn = c("SpecType", "GeneName", "EntryName", "Accession", "Species", "Contam"),
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

Mvalue	(numeric, list or of class 'MArrayLM') vector of M-values (log ₂ fold-change) or output from testRobustToNAimputation() from package wrProteo
pValue	(numeric) statistical testing results, only used in case argument Mvalue is only a numeric vector
useComp	(integer or character) in case argument Mvalue contains output from testRobustToNAimputation() this argument allows choosing a given pair-wise comparison
filtFin	(logical or matrix) optional vector to provide/include results from other additional filtering (columns should match columns of pValue if multiple questions addressed in data); if argument Mvalue is list or class 'MArrayLM' this argument will be only used if respective information not present from Mvalue
FCthrs	(numeric) threshold for M-values (as log ₂ (fold-change)), defaults to 1
FdrList	(vector, matrix or data.frame) additional statistical testing results for multiple testing correction, used for apply FdrThr; if argument Mvalue is list or class 'MArrayLM' this argument will be only used if respective information not present from Mvalue
FdrThrs	(numeric) threshold for filtering FdrList, defaults to 0.05
FdrType	(character) choose which multiple correction testing should be used for filtering (only if argument Mvalue is list from wrProteo or class 'MArrayLM')
signifOnly	(logical) decide if only filtered data or complete table should be returned

annotColumn	(character) additional elements from \$annot to extract too if Mvalue is list (from wrProteo) or class 'MArrayLM'
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allow easier tracking of messages produced

Details

This function offers support for combined filtering along a significance-threshold (flexible choice of type of multiple testing correction) combined with M-values (log₂ fold-change) and other filtering results (already present in objects from package wrProteo). Even though basic filtering can be performed using separated vectors (see example below), the main advantage relies on automatically recognizing the structure of results from testRobustToNAimputation() from package wrProteo.

In case of using with separate vectors the original p-values may be provided without or with multiple-testing corrected values (argument FdrList. If no multiple-testing correctio is provided it will be calculated using the Benjamini-Hochberg formula from [p.adjust](#).

Note : M-value data is assumed to be log₂-transformed ratios !

Value

This function returns a matrix (or in some instances a data.frame) combining (at least) the columns 'FDRvalue', 'Mvalue', 'pValue', 'filtFin' and 'retain'

See Also

testRobustToNAimputation and extractTestingResults from package wrProteo, or filter_volcano from package genefilter, [p.adjust](#)

Examples

```
set.seed(2025); means1 <- matrix(rnorm(2*95) + seq(1,3, length.out=2*95),
  ncol=2, byrow=TRUE, dimnames=list(NULL, LETTERS[3:2]))
means1 <- rbind(means1, cbind((3:7)/2, c(6:8, -2:-3)))
rownames(means1) <- paste0("li_", sprintf(paste0("%03d"), 1:100))
Mval0 <- means1[,1] - means1[,2]
Mval1 <- matrix(means1[,1] - means1[,2], ncol=1, dimnames=list(rownames(means1), "C-B"))
set.seed(2026); pVal0 <- c(runif(95, max=0.9), (4:8)^(-4:-8))
FdrVal1 <- matrix(p.adjust(pVal0, method="BH"), ncol=1, dimnames=list(rownames(means1), "C-B"))
pVal1 <- matrix(pVal0, ncol=1, dimnames=list(rownames(means1), "C-B"))

## with separate entries ...
filt1 <- volcanoFilter(Mvalue=Mval1, pValue=pVal1)      # separate values
tail(signif(filt1, 3))

## separate entries, retrieve all data for Volcano-Plot
filt2 <- volcanoFilter(Mvalue=Mval1, pValue=pVal1, signifOnly=FALSE)  # separate values
tail(signif(filt2, 3))
plot(filt2[,2], -1*log10(filt2[,3]), col=c("grey", "red")[1+filt2[,5]], pch=16, main="Volcano-Plot")
```

```
## simulate basic/minimal object from wrProteo
Mobj3 <- list(means=means1, BH=FdrVal1, p.value=pVal1)
filt3 <- volcanoFilter(Mobj3)
tail(signif(filt3, 3))
```

 withinRefRange

Check For Values Within Range Of Reference

Description

This function checks which values of numeric vector 'x' are within range +/- 'fa' x 'ref' (ie within range of reference).

Usage

```
withinRefRange(
  x,
  fa,
  ref = NULL,
  absRef = TRUE,
  asInd = FALSE,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

x	matrix or data.frame
fa	(numeric) absolute or relative tolerance value (numeric, length=1), interpreted according to 'absRef' as absolute or relative to 'x' (ie fa*ref)
ref	(numeric) (center) reference value for comparison (numeric, length=1), if not given mean of 'x' (excluding NA or non-finite values) will be used
absRef	(logical) return result as absolute or relative to 'x' (ie fa*ref)
asInd	(logical) if TRUE return index of which values of 'x' are within range, otherwise return values if 'x' within range
silent	(logical) suppress messages
debug	(logical) additional messages for debugging
callFrom	(character) allows easier tracking of messages produced

Value

This function returns a numeric vector containing only the values within range of reference

Examples

```
## within 2.5 +/- 0.7
withinRefRange(-5:6, fa=0.7, ref=2.5)
## within 2.5 +/- (0.7*2.5)
withinRefRange(-5:6, fa=0.7, ref=2.5, absRef=FALSE)
```

writeCsv

Write (And Convert) Csv Files

Description

This functions allows for more options when writing data into csv-files compared to `write.csv`.

Usage

```
writeCsv(
  input,
  inPutFi = NULL,
  expTy = c("Eur", "US"),
  imporTy = "Eur",
  filename = NULL,
  quote = FALSE,
  filterCol = NULL,
  replMatr = NULL,
  returnOut = FALSE,
  SYLKprevent = TRUE,
  digits = 22,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

Arguments

<code>input</code>	either matrix or data.frame
<code>inPutFi</code>	(character or NULL) file-name to be read (format as US or Euro-type may specified via argument <code>imporTy</code>)
<code>expTy</code>	(character) 'US' and/or 'Eur' for sparator and decimal type in output
<code>imporTy</code>	(character) default 'Eur' (otherwise set to 'US')
<code>filename</code>	(character) optional new file name(s)
<code>quote</code>	(logical) will be passed to function <code>write.csv</code>
<code>filterCol</code>	(integer or character) optionally, to export only the columns specified here
<code>replMatr</code>	optional, matrix (1st line:search, 2nd li:use for replacing) indicating which characters need to be replaced)

returnOut	(logical) return output as object
SYLKprevent	(logical) prevent difficulty when opening file via Excel. In some cases Excel presumes (by error) the SYLK format and produces an error when trying to open files : To prevent this, if necessary, the 1st column-name will be changed from 'ID' to 'Id'.
digits	(integer) limit number of signif digits in output (ie file)
silent	(logical) suppress messages
debug	(logical) for bug-tracking: more/enhanced messages
callFrom	(character) allow easier tracking of messages produced

Details

The main input may be given as R-object or read from file 'input'. Then, one can (re-)write using specified conversions. An optional filter to select columns (column-name specified via 'filterCol') is available.

The output may be simultaneously written to multiple formats, as specified in 'expTy', tabulation characters may be converted to avoid accidentally split/shift text to multiple columns. Note: Mixing '.' and ',' as comma separators via text-columns or fused text&data may cause problems lateron, though.

Value

This function writes a file to disk and returns NULL unless returnOut=TRUE

See Also

write.csv in [write.table](#), batch reading using this package [readCsvBatch](#)

Examples

```
dat1 <- data.frame(ini=letters[1:5],x1=1:5,x2=11:15,t1=c("10,10","20.20","11,11","21,21","33.33"),
  t2=c("10,11","20.21","k1;k1","az,az","ze.ze"))
fiNa <- file.path(tempdir(), paste("test",1:2,".csv",sep=""))
writeCsv(dat1, filename=fiNa[1])
dir(path=tempdir(), pattern="cs")

(writeCsv(dat1, replM=rbind(bad=c(";",",",""), replBy="__"), expTy=c("Eur"),
  returnOut=TRUE, filename=fiNa[2]))
```

`XYToDiffPpm`*Express difference as ppm*

Description

This function transforms offset (pairwise-difference) between 'x' & 'y' to ppm (as normalized difference ppm, parts per million, ie $(x-y)/y$). This type of expressing differences is used eg in mass-spectrometry.

Usage

```
XYToDiffPpm(x, y, nSign = NULL, silent = FALSE, debug = FALSE, callFrom = NULL)
```

Arguments

<code>x</code>	(numeric) typically for measured variable
<code>y</code>	(numeric) typically for theoretical/expected value (vector must be of same length as 'x')
<code>nSign</code>	(integer) number of significant digits in output
<code>silent</code>	(logical) suppress messages
<code>debug</code>	(logical) additional messages for debugging
<code>callFrom</code>	(character) allow easier tracking of messages produced

Value

This function returns a numeric vector of (ratio-) ppm values

See Also

[ratioToPpm](#) for classical ppm

Examples

```
set.seed(2017); aa <- runif(10,50,900)
cbind(x=aa,y=aa+1e-3,ppm=XYToDiffPpm(aa,aa+1e-3,nSign=4))
```

Index

- * **character**
 - pasteC, 221
- .addLetterWoLast, 8
- .allRatioMatr1to2, 8
- .allRatios, 9
- .arrLstMean, 10
- .arrLstSEM, 11
- .asDF2, 12
- .breakInSer, 12
- .bringToCtr, 13
- .checkArgNa, 14
- .checkConsistentArrList, 14
- .checkConvt2Vect, 15
- .checkFactor, 16
- .checkFileNameExtensions, 17
- .checkLegendLoc, 17
- .checkLmConfInt, 18
- .checkRegrArguments, 19
- .chooseGrpCol, 19
- .combineListAnnot, 20
- .compareByDiff, 21
- .compareByLogRatio, 22
- .compareByPPM, 23
- .complCols, 23
- .composeCallName, 24
- .convertMatrToNum, 25
- .convertNa, 25
- .corDuplItemsByIncr, 26
- .cutAtSearch, 27
- .cutStr, 28
- .datSlope, 28
- .doubleExt, 29
- .extrNAneighb, 30
- .extrNumHeadingCap, 31
- .extrNumHeadingSepChar, 31
- .filtSize, 34
- .filterNetw, 32
- .filterSw, 33
- .findBorderOverlaps, 34
- .firstMin, 35
- .fuse2ArrBy2ndDim, 36
- .getAmean, 36
- .getAmean2, 37
- .getMvalue2, 38
- .getPWseparator, 38, 169, 244
- .growTree, 40
- .insp1dimByClustering, 40
- .inspectHeader, 41
- .keepCenter1d, 42
- .keepFiniteCol, 43
- .maybeNum, 44
- .medianSpecGrp, 45
- .mergeMatrices, 46
- .minDif, 47
- .neighbDis, 47
- .normConstSlope, 49
- .normalize, 48
- .pasteCols, 50
- .plotCountPie, 51
- .plusLowerCaps, 52
- .predRes, 52
- .raiseCollowest, 53
- .removeCol, 54
- .removeEmptyCol, 55
- .replSpecChar, 56
- .retain1stPart, 56
- .rowGrpCV, 57
- .rowGrpMeans, 58
- .rowGrpSds, 58
- .rowGrpSums, 59
- .rowNorm, 60
- .rowNormFact, 61
- .scale01, 62
- .scaleSpecGrp, 63
- .scaleXY, 64
- .seqCutStr, 64
- .setLowestTo, 65
- .sortMid, 66

- .stackArray, 66
- .summarizeCols, 67
- .trimFromEnd, 68
- .trimFromStart, 69
- .trimLeft, 70
- .trimRight, 71
- .uniqueWName, 71
- .vector2Matr, 72

- addBeforeFileExtension, 73
- addBeforFileExtension, 74
- adjBy2ptReg, 75, 212, 213, 239, 240, 263
- adjustUnitPrefix, 76, 93
- anova, 272
- aov, 272
- append, 19, 29, 78
- appendNR, 77
- array, 36, 216
- arrayCV, 57–59, 78, 248, 256
- as.data.frame, 12
- asSepList, 79, 220

- blockNormalize, 80, 267
- boot, 101, 261, 278
- buildTree, 40, 83, 117, 118, 128, 271

- cbind, 85, 147, 177, 179
- cbindNR, 84
- chartr, 14, 52
- checkAvSd, 85
- checkFilePath, 30, 86
- checkGrpOrder, 88, 92, 215
- checkGrpOrderSEM, 88, 89
- checkSimValueInSer, 21–23, 66, 90, 99, 133, 150, 154, 182
- checkStrictOrder, 91, 215
- checkUnitPrefix, 77, 92, 290
- checkVectLength, 94
- chooseGroupNames, 95, 245
- cleanReplicates, 96
- closeMatchMatrix, 97, 154
- coinPermTest, 99
- colCVs, 100, 255
- colMedSds, 101, 261, 278
- colorAccording2, 20, 101
- colSds, 100, 103, 264
- colSums, 172, 255, 257, 259, 260, 264, 279
- combinatIntTable, 103
- combineAsN, 104
- combineByEitherFactor, 106
- combineOverlapInfo, 107
- combineRedBasedOnCol, 109, 111, 209, 210
- combineRedundLinesInList, 109, 110, 112
- combineRedundLinesInListAcRef, 111
- combineReplFromListToMatr, 112
- combineSingleT, 113
- combn, 104, 243, 288
- completeArrLst, 114
- concatMatch, 115
- confInt, 116
- confint, 117
- contribToContigPerFrag, 84, 117, 128, 271
- conv01toColNa, 118
- convColorToTransp, 119
- convMatr2df, 45, 120
- convPairwiseSetup, 121, 163, 228
- convToNum, 77, 93, 122, 187
- coordOfFilt, 124
- correctToUnique, 34, 51, 125, 146, 149, 166, 209, 210, 287, 294
- correctWinPath, 126
- countCloseToLimits, 21–23, 127, 150
- countSameStartEnd, 84, 128, 271
- cut, 102, 130, 131
- cutArrayInCluLike, 10, 11, 15, 21, 129
- cutAtMultSites, 8, 130, 205, 206
- cutToNgrp, 130

- date, 281
- diff, 132, 133, 196
- diffCombin, 131, 288
- diffPPM, 132
- dist, 13, 47, 54, 67, 220, 296
- duplicated, 26, 34, 146, 149, 156, 208, 245, 269

- elimCloseCoord, 133
- equLenNumber, 15, 134
- exclExtrValues, 135
- exponNormalize, 136, 212, 213, 263
- extr1chan, 113, 114, 138
- extractLast2numericParts, 139
- extrColsDeX, 140, 146
- extrNumericFromMatr, 141
- extrSpcText, 142

- factor, 16, 56
- fdrtool, 226

- file.exists, 88
- file.path, 126
- file_ext, 29, 30
- filt3dimArr, 33, 143
- filterLiColDeList, 33, 144, 144
- filterList, 33, 140, 144, 145
- filterNetw, 33, 146, 219
- filtSizeUniq, 34, 125, 148
- findCloseMatch, 21–23, 97–99, 127, 134, 149, 153, 154
- findHeadAndTail, 151
- findRepeated, 109, 111, 152, 166, 210
- findSimilFrom2sets, 153
- findUsableGroupRange, 154
- firstLineOfDat, 155, 210
- firstOfRepeated, 30, 50, 133, 134, 156, 156, 157, 162, 207, 208, 210
- firstOfRepLines, 85, 109, 111, 136, 156, 157, 210
- fisher.test, 229
- fread, 233, 234
- fuseAnnotMatr, 158
- fuseCommonListElem, 159
- fusePairs, 160
- get1stOfRepeatedByCol, 136, 152, 161, 207, 210
- getPairwiseSetup, 122, 162
- getPWseparator, 39, 122, 163, 164, 165, 169, 228, 244, 288
- getValuesByUnique, 165
- gitDataUrl, 166
- gray.colors, 286
- grep, 9, 27, 31, 116, 139, 152, 163, 171, 176, 183, 186, 201, 228, 250, 293
- head, 42
- htmlSpecCharConv, 167
- indexGroupsFromPW, 39, 122, 163, 165, 168, 228, 244, 288
- is.finite, 44, 55
- justvsn, 212, 213, 263
- keepCommonText, 69–71, 169, 290
- kmeans, 243
- legend, 18
- levIndex, 171
- linModelSelect, 172
- linRegrParamAndPVal, 174
- listBatchReplace, 175
- listGroupsByNames, 176
- lm, 175, 178, 229, 270
- lmFit, 145, 197, 200, 272, 284
- lmSelClu, 177
- LocationTests, 100
- lower.tri, 288, 295
- lrbind, 19, 29, 78, 179
- makeMAList, 9, 37, 38, 180, 283, 284
- makeNRedMatr, 181, 279
- MAplotW, 266
- match, 115, 116, 183–185, 203, 215
- matchMatrixLinesToRef, 182
- matchNamesWithReverseParts, 184
- matchSampToPairw, 185
- matr2list, 186
- matrix, 25, 73
- mean, 285, 289
- merge, 46, 159, 188–193, 195
- mergeMatrices, 46, 187, 189
- mergeMatrixList, 46, 188, 188
- mergeSelCol, 190, 192
- mergeSelCol3, 191, 191
- mergeVectors, 192
- mergeW2, 194
- minDiff, 195
- moderTest2grp, 145, 173, 174, 196, 200
- moderTestXgrp, 39, 152, 163, 165, 169, 173, 174, 186, 198, 228, 266
- multiCharReplace, 201
- multiMatch, 202
- NA, 280
- na.fail, 204, 247
- naOmit, 203, 247
- nchar, 31, 32, 35, 54, 65, 206
- nFragments, 130, 204
- nFragments0, 130, 205
- nNonNumChar, 206
- Node, 84
- nonAmbiguousMat, 207
- nonAmbiguousNum, 30, 50, 85, 156, 157, 162, 208
- nonredDataFrame, 209
- nonRedundLines, 210
- Normal, 254

- normalizeThis, [24](#), [49](#), [50](#), [61](#), [62](#), [82](#), [137](#),
[210](#), [263](#), [267](#)
 normalizeWithinArrays, [180](#)
 numeric, [45](#), [120](#), [124](#)
 numPairDeColNames, [213](#)
- order, [92](#), [174](#)
 orderMatrToRef, [214](#)
 organizeAsListOfRepl, [109](#), [111](#), [113](#), [114](#),
[139](#), [216](#)
- p.adjust, [197](#), [226](#), [291](#), [298](#)
 packageDownloadStat, [217](#)
 pairsAsPropensMatr, [218](#)
 par, [119](#), [271](#)
 partialDist, [219](#)
 partUnlist, [79](#), [80](#), [220](#)
 paste, [8](#), [24](#), [221](#)
 pasteC, [28](#), [65](#), [221](#)
 pie, [238](#)
 presenceFilt, [122](#), [163](#), [222](#), [224](#), [228](#), [280](#)
 presenceGrpFilt, [223](#), [223](#)
 protectSpecChar, [96](#), [225](#)
 pVal2lfdr, [226](#)
 pwSeparatorList, [169](#), [227](#)
- quantile, [82](#)
- randIndex, [228](#)
 randIndFx, [228](#)
 rankToContigTab, [229](#)
 ratioAllComb, [230](#)
 ratioToPpm, [231](#), [302](#)
 read.delim, [167](#), [234](#)
 read.table, [140](#), [233](#), [235](#), [236](#)
 read_excel, [237](#)
 readCsvBatch, [232](#), [234](#), [301](#)
 readTabulatedBatch, [233](#)
 readVarColumns, [235](#)
 readXlsxBatch, [233](#), [236](#)
 reduceTable, [238](#)
 regrBy1or2point, [239](#), [240](#)
 regrMultBy1or2point, [239](#), [240](#)
 renameColumns, [44](#), [55](#), [241](#)
 reorgByCluNo, [242](#)
 replacePWseparator, [39](#), [165](#), [169](#), [243](#)
 replicateStructure, [96](#), [106](#), [183](#), [244](#), [275](#)
 replNAbyLow, [246](#)
 replPlateCV, [57–59](#), [79](#), [247](#), [256](#)
- rgb, [20](#), [119](#)
 rmDupl2colMatr, [248](#)
 rmEnumeratorName, [249](#), [292](#), [293](#)
 rmOrphans, [251](#)
 rmSharedWords, [96](#), [252](#), [290](#)
 rnormW, [253](#)
 rowCVs, [57–59](#), [79](#), [100](#), [248](#), [255](#), [256](#), [260](#)
 rowGrpCV, [57–59](#), [79](#), [100](#), [255](#), [256](#)
 rowGrpMeans, [86](#), [256](#), [259](#), [260](#)
 rowGrpNA, [257](#)
 rowGrpSds, [259](#), [260](#)
 rowGrpSums, [260](#)
 rowMedSds, [261](#), [278](#)
 rowNormalize, [24](#), [61](#), [62](#), [211–213](#), [261](#)
 rowSds, [172](#), [255](#), [257](#), [259](#), [260](#), [263](#), [264](#)
 rowSEMs, [260](#), [264](#)
 rowSums, [100](#)
- sampNoDeMArrayLM, [265](#)
 scale, [62](#), [64](#), [82](#), [212](#), [267](#), [276](#), [277](#)
 scaleXY, [62](#), [64](#), [75](#), [212](#), [213](#), [266](#)
 sd, [103](#), [260](#), [264](#)
 searchDataPairs, [268](#)
 searchLinesAtGivenSlope, [18](#), [41](#), [43](#), [53](#),
[269](#)
 simpleFragFig, [84](#), [128](#), [271](#)
 singleLineAnova, [272](#)
 sortBy2CategorAnd1IntCol, [273](#)
 sortByNRepeated, [274](#)
 sprintf, [135](#)
 stableMode, [275](#)
 standardW, [276](#)
 stdErrMedBoot, [277](#)
 strsplit, [122](#), [130](#), [163](#), [186](#), [203](#), [214](#), [228](#)
 sub, [167](#)
 substr, [28](#), [57](#), [65](#), [142](#)
 summarizeCols, [66–68](#), [182](#), [278](#)
 sumNAperGroup, [280](#)
 Sweave, [282](#), [283](#)
 Sys.time, [281](#)
 sysDate, [281](#)
- t, [268](#)
 t.test, [291](#)
 table, [68](#), [106](#), [238](#), [252](#), [275](#)
 tableToPlot, [282](#)
 tapply, [279](#)
 TDist, [117](#)
 tempfile, [126](#)

test2factLimma, [180](#), [272](#), [283](#)
top3mean, [285](#)
transpGraySca, [286](#)
treatTxtDuplicates, [125](#), [166](#), [286](#)
triCoord, [287](#), [294](#), [295](#)
Trig, [296](#)
trimmedMean, [279](#), [288](#)
trimRedundText, [69–71](#), [77](#), [171](#), [183](#), [245](#),
[253](#), [289](#)
tTestAllVal, [290](#)

unifyEnumerator, [291](#)
uniqCountReport, [51](#), [293](#)
unique, [30](#), [34](#), [50](#), [51](#), [72](#), [125](#), [146](#), [149](#), [156](#),
[157](#), [166](#), [209](#), [294](#)
unlist, [15](#), [80](#), [160](#), [220](#), [249](#)
upperMaCoord, [288](#), [294](#)

vectorDistAngle, [295](#)
volcanoFilter, [296](#)
VolcanoPlotW, [266](#)

which, [124](#)
which.min, [35](#), [45](#), [63](#)
withinRefRange, [91](#), [299](#)
write.table, [301](#)
writeCsv, [233](#), [300](#)

XYToDiffPpm, [231](#), [302](#)